

Part Number: ICS-STD-2X4-220 Fan Filter Unit

About:

Fan Filter Units (FFUs) are essential building blocks, whether constructing new spaces or upgrading existing ones. The Instant Cleanroom Solutions FFUs offer a rapid, flexible, and cost-effective path to achieving stringent ISO cleanliness standards. These lightweight, modular units can be quickly installed in a standard ceiling grid to transform any suitable room into a controlled environment, allowing clients to establish clean workspace immediately without the significant lead times or capital expenditures associated with traditional construction.

Dimensions FFU:		
Width	Length	Depth
23" 9/16	47" 9/16	7" 1/12
605mm	1215mm	315mm

Dimensions HEPA Filter:		
Width	Length	Depth
23" 9/16	47" 9/16	3"

General	
Cabinet	Powder Coated Aluminum T1.0mm
Control	Single Control, 3 level speed rotary switch
Weight	45.9 lb





Power	
Power Supply	220V / 60hz .65AMP 135W
Electrical Connection	3 wire 220V hardwire through 3/8 HALEX Plug Port

Environmental	
Airflow	580CFM - 706CFM (L/M/H)
Velocity	60 - 108 Ft/Min (L/M/H)
Fan Motor	AFLY310, 1600RPM
HEPA Filter Static Pressure (Clean)	0.449" WC
Efficiency:	H14 99.995% @ .3um dry seal type
Noise Level:	52dB - 56 dB



This document is intended for the sole use of the individual or entity to which it is addressed and may contain information that is privileged, confidential, or prohibited from disclosure by law. If the viewer of this document is not the intended recipient or the employee or agent responsible for delivery of this document to the recipient, you are hereby notified that dissemination, distribution, or copying of this document may be prohibited, a violation of the law, or both. If you have received this document in error, please notify the sender immediately. Thank you for your courtesy.



220 V FFU DIAGRAM		NAME	DATE
A / 3	DESIGNED	DV	10/30/2023
	DRAWN	RM	01/08/2024
	CHECKED	PA	03/24/2024
	APPROVED	DV	04/24/2024