



Enhance forklift safety and efficiency with the AI Forklift CCTV Camera Solution, a state-of-the-art system designed for modern industrial operations.

**Advanced Camera Coverage:** 4 intelligent front and rear cameras with 110° front and 130° rear views, eliminating blind spots and enhancing visibility.

**Al-Enabled DVR with HD Display:** A 10.1" waterproof touchscreen display provides clear visuals in any condition, while built-in storage ensures extended recording capacity for incident reviews.

**Al-powered Blind Spot Detection:** It identifies pedestrians and vehicles, providing real-time alerts to reduce collision risks.

**Heavy Duty AV Cables:** Equipped with robust, durable AV cables for secure and reliable camera connections, ensuring high performance in tough conditions.

# **Intelligent Front & Rear Camera (Wired)**

Model NO: SE-04-003/IFC & SE-04-003/IRC

The Intelligent Front & Rear Camera (Wired) system is an advanced solution designed to enhance safety and visibility for vehicles operating in challenging environments. With 1080P high-definition clarity, IP69K-rated waterproofing, and a robust anti-vibration design.



## **Key Features**

Enhanced Durability: Built to withstand extreme temperatures (-20°C to 70°C) and high humidity (RH 95% MAX).

Wide Viewing Angle: 110-130° lens ensures comprehensive coverage of the surroundings.

Smart Day/Night Adjustment: Automatically adapts to varying light conditions for clear imaging.

Anti-vibration Design: Ensures stability and reliability in rugged environments.

Integrated Microphone: Enables audio capture for enhanced monitoring.





# **Key Specifications**

### **Camera Specifications**

Image Sensor	1/2.9" CMOS
Resolution	1920(H) x 1080(V) (1080P)
Frame Rate	25fps/30fps
Lens	f = 3.6mm, 110° viewing angle
Minimum Illumination	0.1 Lux (day), 0 Lux (with IR)

### **Night Vision**

Distance	1/2.9" CMOS
Infrared Lights	1920(H) x 1080(V) (1080P)

### **Video Output**

1.0Vp-p, 75 Ohm

#### **Electrical & Connection**

Power Supply	DC 12V
Current Consumption	Max. 220mA
Connection	4 PIN

### **Environmental Ratings**

Waterproof	IP69K
Operating Temperature	-20°C to 70°C
Humidity	RH 95% MAX

### **Additional Specifications**

Shutter Speed	1/30(1/25)~1/50,000 Seconds
Dynamic Range	Auto
White Balance	Auto
Backlight Compensation (BLC)	Auto
Anti-vibration	Yes
Built-in Microphone	Yes





## AI DVR Display (10" 4CH)

Model: SE-04-003/DD

The AI DVR Display is a cutting-edge 10-inch quad-view monitor with advanced AI capabilities, designed to enhance vehicle safety and surveillance. With real-time pedestrian detection, multiple display modes, and robust storage options.





## **Key Features**

**Al-Powered Pedestrian Detection:** BSD algorithm detects pedestrians in real-time to minimize blind spot accidents.

Quad-View Display: Supports split-screen monitoring for up to 4 HD cameras.

**Touchscreen Interface:** Capacitive screen with gesture support and intuitive menu navigation.

Robust Storage: Supports 2 micro SD cards (512GB each) and 1 SSD (2TB).

**Remote Access:** Built-in WLAN for configuration and live view via web interface.



## **Specifications**

#### **Additional Specifications**

Display	10.1" HD LCD, 1024x600 resolution, brightness 650 cd/m <sup>2</sup>
Viewing Angle	U: 85° / D: 85°, R/L: 85°
Video Input	4 channels, supports 1080P30, 1080P25, 720P30, 720P25, PAL, NTSC
Contrast Ratio	700:1
Audio Input	4 channels
Trigger Inputs	5, with adjustable delay and priority
Storage	2×Micro SD (512GB each) + 1×SSD (2TB)
Power Supply	DC 10V-32V with short circuit protection
Power Consumption	Max 30W
Operating Temperature	-20°C to +70°C, RH 90%
Storage Temperature	-30°C to +80°C, RH 90%
Split-Screen Display	Yes
Speaker	1.5W built-in