




# C20

MAX REACH FROM CENTER  
6'7"



MAX PAYLOAD  
**36 LBS**

MAX SPEED  
**23 FT/S**

#### INCLUDED HARDWARE:

- ROBOT ON PEDESTAL
- CONTROLS CABINET
- FIZ MOTORS
- CAMERA MOUNT
- COMBO CABLE
- REMOVABLE WEIGHTS
- SISU WAND, TABLET & CASE




MAX HEIGHT  
11'2"




LOWEST POSITION  
-2'5"



PEDESTAL FOOTPRINT  
28" x 31"



INTUITIVE  
HAND CONTROL



FAMILIAR TIMELINE  
INTERFACE



TARGET  
TRACKING



TRACK  
CONTROL



ARCS &  
ORBITS



VFX  
INTEGRATION



EXTERNAL  
DEVICES



# DEEPER SPECS

## DIMENSIONS

MAX HEIGHT	11'2"
LOWEST POSITION	-2'5"
MAX REACH FROM CENTER	6'7"
PEDESTAL FOOTPRINT	28" x 31"
WITH OUTRIGGERS	55" x 59"

## REPEATABILITY

REPEATABILITY	0.0016"
---------------	---------

## SHOOTING SPEEDS

MAX LINEAR MOVE	6.6ft/s
MAX OVERALL SPEED	23ft/s

## TEMPERATURE

MIN	40 F
MAX	113 F

## WEIGHT

ROBOT	565lbs
RATED PAYLOAD	35lbs
MAX PAYLOAD	36lbs
CONTROLS CABINET	400lbs
MOBILE PEDESTAL	600lbs
ADDITIONAL WEIGHTS	800lbs

## POWER\*

MAX POWER	8kVA
VOLTAGE	480VAC 3-phase
MAX CURRENT	10A
POWER CABLE	23ft
ROBOT TO CONTROLS CABLE	23ft or 49ft
PLUG TYPE	SCM420P7W
COMPATIBLE SOCKET OUTLETS	IEC60309



# C20



\*Additional power options are available. Contact [sales@sisu.us](mailto:sales@sisu.us) for more information.  
For more detailed specs, see the manual.