



C14

MAX REACH FROM CENTER
1.49M



MAX HEIGHT
2.5M



LOWEST POSITION
0M



PEDESTAL FOOTPRINT
0.7M x 0.8M



MAX PAYLOAD
10KG

MAX SPEED
5.4M/S

INCLUDED HARDWARE:

- ROBOT ON PEDESTAL
- CONTROLS CABINET
- FIZ MOTORS
- CAMERA MOUNT
- COMBO CABLE
- REMOVABLE WEIGHTS
- SISU WAND, TABLET & CASE



INTUITIVE
HAND CONTROL



FAMILIAR
TIMELINE INTERFACE



TARGET
TRACKING



ARCS &
ORBITS



VFX
INTEGRATION



EXTERNAL
DEVICES



DEEPER SPECS

DIMENSIONS

MAX HEIGHT	2.5m
LOWEST POSITION	0m
MAX REACH FROM CENTER	1.49m
PEDESTAL FOOTPRINT	0.7m x 0.8m

REPEATABILITY

REPEATABILITY	0.04mm
---------------	--------

SHOOTING SPEEDS

MAX LINEAR MOVE	2m/s
MAX OVERALL SPEED	5.4m/s

WEIGHT

ROBOT	160kg
MAX PAYLOAD	10kg
CONTROLS CABINET	100kg
MOBILE PEDESTAL	227kg
ADDITIONAL WEIGHTS	363kg

POWER*

MAX POWER	2.4kVA
VOLTAGE	120VAC
MAX CURRENT	20A
POWER CABLE	7m
ROBOT TO CONTROLS CABLE	7m or 15m
PLUG TYPE	NEMA 5-15P
COMPATIBLE SOCKET OUTLETS	NEMA 5-13R

TEMPERATURE

MIN	5 C
MAX	45 C



C14



*Additional power options are available. Contact sales@sisu.us for more information.
For more detailed specs, see the manual.