

MAX REACH FROM CENTER  
2.01m



MAX PAYLOAD  
**16 KG**

MAX SPEED  
**7 M/S**

MAX HEIGHT  
3.4m


LOWEST POSITION  
-0.75m

#### INCLUDED HARDWARE:

- ROBOT ON PEDESTAL
- CONTROLS CABINET
- FIZ MOTORS
- CAMERA MOUNT
- COMBO CABLE
- REMOVABLE WEIGHTS
- SISU WAND, TABLET & CASE



PEDESTAL FOOTPRINT  
0.7m x 0.8m



INTUITIVE  
HAND CONTROL




FAMILIAR TIMELINE  
INTERFACE



TARGET  
TRACKING



TRACK  
CONTROL



ARCS &  
ORBITS



VFX  
INTEGRATION



EXTERNAL  
DEVICES



# DEEPER SPECS

## DIMENSIONS

MAX HEIGHT	3.4m
LOWEST POSITION	-0.75m
MAX REACH FROM CENTER	2.01m
PEDESTAL FOOTPRINT	0.7m x 0.8m
WITH OUTRIGGERS	1.4m x 1.5m

## REPEATABILITY

REPEATABILITY	0.04mm
---------------	--------

## SHOOTING SPEEDS

MAX LINEAR MOVE	2m/s
MAX OVERALL SPEED	7m/s

## WEIGHT

ROBOT	255kg
RATED PAYLOAD	16kg
MAX PAYLOAD	19kg
CONTROLS CABINET	181kg
MOBILE PEDESTAL	272kg
ADDITIONAL WEIGHTS	363kg

## POWER\*

MAX POWER	8kVA
VOLTAGE	480VAC 3-phase
MAX CURRENT	10A
POWER CABLE	7m
ROBOT TO CONTROLS CABLE	7m or 15m
PLUG TYPE	SCM420P7W IP67 20A 3-phase   480 VAC 3P 4W (male)
COMPATIBLE SOCKET OUTLETS	IEC60309

## TEMPERATURE

MIN	5 C
MAX	45 C



# C20



\*Additional power options are available. Contact [sales@sisu.us](mailto:sales@sisu.us) for more information.  
For more detailed specs, see the manual.