

TRIAD PASSIVE SOUNDBARS

TS-PSB13, TS-PSB23, TS-PSB33, TS-PSB14, TS-PSB24, TS-PSB34, TS-PSB15,
TS-PSB25, TS-PSB35, TS-PSB16, TS-PSB26, TS-PSB36



TRIAD PASSIVE SOUNDBARS

Triad Passive Soundbars offer high end sound with enhanced aesthetics and technology. Available in 3", 4", plus new 5" and 6" drivers, three configuration options, and custom lengths up to 86" to fit nearly any display size. Choose from six colorways, veneer or custom paint matching for custom speakers that discreetly blend in or proudly stand out. The new Passive Soundbars uphold Triad's reputation for performance and aesthetics, delivering an audio experience that looks as good as it sounds.

- Available in 3", 4", 5", and 6" driver sizes
- Available in 1.0, 2.0, and 3.0 configurations
- Customizable lengths by 1/8" increments up to 86"
- Six predesigned colorways, plus custom veneer and paint options
- Easy Mount wall mount brackets included

PERFECTLY MATCH THE WIDTH OF ANY TV

Customize length in 1/8" increments up to 86" to match the width of almost any TV on the market for a beautiful, seamless installation.

FULLY CUSTOMIZABLE FINISH OPTIONS

Select from six pre-selected colorways, or customize cabinet and baffle finishes for the perfect look. Paint and veneer matching is available.*

*Charges may apply.

BUILT-TO-ORDER, MADE IN THE USA

Fully engineered, premium MDF enclosures are precision crafted and built to order on-site in our Portland, OR manufacturing facility.

SPECIFICATIONS

PRODUCT	TS-PSB13	TS-PSB23	TS-PSB33
Finished Dimensions (HxD) (mm)	146 x 76	146 x 76	146 x 76
Finished Dimensions (HxD) (in)	5.75" x 3"	5.75" x 3"	5.75" x 3"
Minimum Length (in)	24	44	44
Minimum Length (mm)	609.6	1117.6	1117.6
Maximum Length (in)	86	86	86
Maximum Length (mm)	2184.4	2184.4	2184.4
Weight per speaker w/ grille (lbs)	Varies by Size	Varies by Size	Varies by Size
Weight per speaker w/ grille (kg)	Varies by Size	Varies by Size	Varies by Size
Frequency Response (+/- 3dB 4pi)	130Hz–20kHz	135Hz–20kHz	135Hz–20kHz
Nominal Impedance	6 Ohms	6 Ohms	6 Ohms
Minimum Impedance	5 Ohms	5 Ohms	5 Ohms
Crossover Frequency	3000 Hz	3000 Hz	3000 Hz
Crossover Type / Slope	Linkwitz-Riley / 12 dB	Linkwitz-Riley / 12 dB	Linkwitz-Riley / 12 dB
Max SPL (AES75/1m)	99dBZ	93dBZ	93dBZ Left/Right 99bBZ Cen
Power Handling (Peak)	160W	100W	100W Left/Right 160W Cen
Power Handling (RMS CTA-426B)	80W	50W	50W Left/Right 80W Cen
Recommended Amplifier Power	50W–150W	50W–150W	50W–150W
Sensitivity (dB) @ 2.83V/1M	85dB	83dB	85dB
Woofer Size	3" (76mm)	3" (76mm)	3" (76mm)
Woofer Cone Material	Aluminum	Aluminum	Aluminum
Woofer Surround Material	Rubber	Rubber	Rubber
Woofer Voice Coil Diameter	1" (25mm)	1" (25mm)	1" (25mm)
Woofer Magnet Type	Neodymium	Neodymium	Neodymium
Speaker Connector Type	Spring Loaded Binding Posts	Spring Loaded Binding Posts	Spring Loaded Binding Posts
Tweeter Size	1.1" (28mm)	1.1" (28mm)	1.1" (28mm)
Tweeter Material	Textreme	Textreme	Textreme

SPECIFICATIONS

PRODUCT	TS-PSB14	TS-PSB24	TS-PSB34
Finished Dimensions (HxD) (mm)	171 x 89	171 x 89	171 x 89
Finished Dimensions (HxD) (in)	6.75" x 3.5"	6.75" x 3.5"	6.75" x 3.5"
Minimum Length (in)	26	44	44
Minimum Length (mm)	660.4	1117.6	1117.6
Maximum Length (in)	86	86	86
Maximum Length (mm)	2184.4	2184.4	2184.4
Weight per speaker w/ grille (lbs)	Varies by Size	Varies by Size	Varies by Size
Weight per speaker w/ grille (kg)	Varies by Size	Varies by Size	Varies by Size
Frequency Response (+/- 3dB 4pi)	120Hz–23kHz	125Hz–23kHz	125Hz–23kHz
Nominal Impedance	6 Ohms	6 Ohms	6 Ohms
Minimum Impedance	5 Ohms	5 Ohms	5 Ohms
Crossover Frequency	2700 Hz	2700 Hz	2700 Hz
Crossover Type / Slope	Linkwitz-Riley / 12 dB	Linkwitz-Riley / 12 dB	Linkwitz-Riley / 12 dB
Max SPL (AES75/1m)	102dBZ	96dBZ	96dBZ Left/Right 102dBZ Cen
Power Handling (Peak)	240W	140W	140W Left/Right 240W Cen
Power Handling (RMS CTA-426B)	120W	70W	70W Left/Right 120W Cen
Recommended Amplifier Power	50W–150W	50W–150W	50W–150W
Sensitivity (dB) @ 2.83V/1M	85dB	83dB	85dB
Woofer Size	4" (102mm)	4" (102mm)	4" (102mm)
Woofer Cone Material	Aluminum	Aluminum	Aluminum
Woofer Surround Material	Rubber	Rubber	Rubber
Woofer Voice Coil Diameter	1" (25mm)	1" (25mm)	1" (25mm)
Woofer Magnet Type	Ferrite	Ferrite	Ferrite
Speaker Connector Type	Spring Loaded Binding Posts	Spring Loaded Binding Posts	Spring Loaded Binding Posts
Tweeter Size	1.1" (28mm)	1.1" (28mm)	1.1" (28mm)
Tweeter Material	Textreme	Textreme	Textreme

SPECIFICATIONS

PRODUCT	TS-PSB15	TS-PSB25	TS-PSB35
Finished Dimensions (HxD) (mm)	197 x 102	197 x 102	197 x 102
Finished Dimensions (HxD) (in)	7.75" x 4"	7.75" x 4"	7.75" x 4"
Minimum Length (in)	34	56	56
Minimum Length (mm)	863.6	1422.4	1422.4
Maximum Length (in)	86	86	86
Maximum Length (mm)	2184.4	2184.4	2184.4
Weight per speaker w/ grille (lbs)	Varies by Size	Varies by Size	Varies by Size
Weight per speaker w/ grille (kg)	Varies by Size	Varies by Size	Varies by Size
Frequency Response (+/- 3dB 4pi)	100Hz–23kHz	108Hz–23kHz	108Hz–23kHz
Nominal Impedance	6 Ohms	6 Ohms	6 Ohms
Minimum Impedance	5 Ohms	5 Ohms	5 Ohms
Crossover Frequency	2500 Hz	2500 Hz	2500 Hz
Crossover Type / Slope	Linkwitz-Riley / 12 dB	Linkwitz-Riley / 12 dB	Linkwitz-Riley / 12 dB
Max SPL (AES75/1m)	104dBZ	98dBZ	98dBZ Left/Right 104dBZ Cen
Power Handling (Peak)	240W	160W	160W Left/Right 240W Cen
Power Handling (RMS CTA-426B)	120W	80W	80W Left/Right 120W Cen
Recommended Amplifier Power	50W–200W	50W–200W	50W–200W
Sensitivity (dB) @ 2.83V/1M	85dB	83dB	85dB
Woofer Size	5.25" (133mm)	5.25" (133mm)	5.25" (133mm)
Woofer Cone Material	Aluminum	Aluminum	Aluminum
Woofer Surround Material	Rubber	Rubber	Rubber
Woofer Voice Coil Diameter	1.2" (30mm)	1.2" (30mm)	1.2" (30mm)
Woofer Magnet Type	Ferrite	Ferrite	Ferrite
Speaker Connector Type	Spring Loaded Binding Posts	Spring Loaded Binding Posts	Spring Loaded Binding Posts
Tweeter Size	1.1" (28mm)	1.1" (28mm)	1.1" (28mm)
Tweeter Material	Textreme	Textreme	Textreme

SPECIFICATIONS

PRODUCT	TS-PSB16	TS-PSB26	TS-PSB36
Finished Dimensions (HxD) (mm)	222 x 108	222 x 108	222 x 108
Finished Dimensions (HxD) (in)	8.75" x 4.25"	8.75" x 4.25"	8.75" x 4.25"
Minimum Length (in)	39	64	64
Minimum Length (mm)	990.6	1625.6	1625.6
Maximum Length (in)	86	86	86
Maximum Length (mm)	2184.4	2184.4	2184.4
Weight per speaker w/ grille (lbs)	Varies by Size	Varies by Size	Varies by Size
Weight per speaker w/ grille (kg)	Varies by Size	Varies by Size	Varies by Size
Frequency Response (+/- 3dB 4pi)	110Hz–23kHz	123Hz–23kHz	123Hz–23kHz
Nominal Impedance	6 Ohms	6 Ohms	6 Ohms
Minimum Impedance	5 Ohms	5 Ohms	5 Ohms
Crossover Frequency	2500 Hz	2500 Hz	2500 Hz
Crossover Type / Slope	Linkwitz-Riley / 12 dB	Linkwitz-Riley / 12 dB	Linkwitz-Riley / 12 dB
Max SPL (AES75/1m)	106dBZ	100dBZ	100dBZ Left/Right 106dBZ Cen
Power Handling (Peak)	240W	180W	180W Left/Right 240W Cen
Power Handling (RMS CTA-426B)	120W	90W	90W Left/Right 120W Cen
Recommended Amplifier Power	50W–200W	50W–200W	50W–200W
Sensitivity (dB) @ 2.83V/1M	88dB	88dB	88dB
Woofer Size	6.5" (160mm)	6.5" (160mm)	6.5" (160mm)
Woofer Cone Material	Aluminum	Aluminum	Aluminum
Woofer Surround Material	Rubber	Rubber	Rubber
Woofer Voice Coil Diameter	1.2" (30mm)	1.2" (30mm)	1.2" (30mm)
Woofer Magnet Type	Ferrite	Ferrite	Ferrite
Speaker Connector Type	Spring Loaded Binding Posts	Spring Loaded Binding Posts	Spring Loaded Binding Posts
Tweeter Size	1.1" (28mm)	1.1" (28mm)	1.1" (28mm)
Tweeter Material	Textreme	Textreme	Textreme