

# T5 SERIES IN-WALL TOUCHSCREENS



## 8" T5 IN-WALL TOUCHSCREEN (C4-T5IW8-MB/WH)

## 11" T5 IN-WALL TOUCHSCREEN (C4-T5IW11-MB/WH)

Designed for effortless installation and a refined finish, these magnetic trims attach securely to T5 In-Wall Touchscreens in seconds.

### Sleek, Smart Design

- Refined, sleek design hugs the wall with a flush surface mount and thin bezel, creating a sleek look that blends into any space.
- Magnetic trims are available to match most Lux product colors.\*
- Paint-Ready Trim: The Primer color option can be custom-painted on-site, allowing for a perfect match with any room's painted surfaces.

### Effortless Installation

- The new one-piece POE design simplifies setup by eliminating pogo pins.
- An optional AC accessory is available when POE is not available.
- Improved wall bracket for more precise wall leveling during installation.

### Enhanced User Experience

- As users approach, a built-in proximity sensor brings the display to life with a dynamic screensaver, offering fast access to active media and frequently used controls.
- Includes front-facing quad-array microphones that deliver clearer, more reliable audio capture.

### Future Ready Capabilities

- Built to support upcoming OS releases and next-generation features, T5 includes auto firmware updates for consistent enhancements.

# CONTROL4 T5 SERIES IN-WALL TOUCHSCREENS

Model Numbers	11" Midnight Black (Matte): C4-T5IW11-MB 11" White (Gloss): C4-T5IW11-WH 8" Midnight Black (Matte): C4-T5IW8-MB 8" White (Gloss): C4-T5IW8-WH
Screen	Resolution: 1920 × 1200 Diagonal: 11" (C4-T5IW11-xx), 8" (C4-T5IW8-xx) Capacitive touch
Camera	-720p (1280 × 960, 4:3 aspect ratio)
Networks Supported	802.11b/g/n 2.4 GHz 802.11a/n/ac 5 GHz Security: WEP, WPA/WPA2/WPA3 PSK, 802.1x EAP, PEAP
Minimum Supported OS	Control4 X4.2
Power Supply	PoE: IEEE 802.3af, 13W peak AC: 120-240V 50/60Hz, via optional power supply (C4-T5IW-AC)
Included Trim Ring Color	Midnight Black (Matte) or White (Gloss) (model dependent)
Audio	Quad-mic array
Sensors	Proximity sensor Ambient light sensor
Operating Environment	Operating temperature: Indoor use only, 0-40°C (32-104°F) Storage temperature: -30-70°C (-22-158°F)
Dimensions (H × W × D)	11" models: 183 × 268 × 24 mm (7.20" × 10.55" × 1"), 16 mm (0.62") on-wall 8" models: 146 × 210 × 24 mm (5.75" × 8.27" × 1"), 16 mm (0.62") on-wall
Backbox Compatibility	Standard US-style 2-gang J-Box (C4-NWB57C-P*, C4-NWB57C-M, C4-RWB57C-P*, C4-RWB57C-M) *Plastic Control4 branded wall boxes are not compatible with AC power supply adapter
Included in Box	1 × T5 Unit (PoE, built-in) 1 × Trim Ring (pre-installed; 11" or 8" depending on model) 1 × Wall mounting bracket & screw kit 1 × Security screwdriver (2mm hex)
Weight	8" model: 0.63 kg (1.4 lb) 11" model: 0.86 kg (1.9 lb)