


SL 1632

Automated Print & Cut Workflow Solution

Designed to seamlessly integrate with any 1.6m wide digital printer to provide a smooth print & cut workflow for sheet materials. With integrated panel feeding and up-take, this high-speed performance solution, ensures continuous productivity.



Ultra-High Speed
3m/s



Platform
Docking



Automatic Material
Collection

- ◆ **Seamlessly integrates with printing equipment**
Fully automated, offering material loading and unloading
- ◆ **High speed performance**
Processing speeds up to 360/day (12 hours)
- ◆ **Integrated Panel Feeding and Collection(optional)**
Easy access forklift transport for efficient material handling
- ◆ **Featuring Automatic Material Information Recognition for uninterrupted continuous workflow**

Materials



Acrylic board



PVC board



Space board



Magnetic sticker



Aluminium-plastic panel

Tools



Electric Oscillating Tool



Electric Foam Cutting Tool



Electric Rotary Tool



Kiss-cut Tool



Router Tool



Centered/Off-centered Drag Knife



Press Cutting Tool



V-CUT Tool For Honeycomb



V-CUT Tool For Grey Board



V-CUT Tool For Rahmen



V-CUT Tool For Cardboard



Creasing Wheel Tool

Product Specifications

JWEI reserves the right of final interpretation of the following parameters, subject to change without prior notice.

Model	SL1632
Multi-functional Tool Head	Multi-tool fixing holes, tool quick insert fixing, easy to replace cutting tools, plug and play, set cutting, creasing, drawing, router and other functions in one, optional ATC module.
Tools	Electric oscillating tool, drag knife, rotary tool, router tool module, plotting tools etc.
Max. Operating speed	3000mm/s
Max. Cutting Thickness	50mm *
Repeat Precision	< 0.05mm
Cutting Materials	ABS board, PVC board, space board, aluminum-plastic board, lamp sheet, back glue, PVC board, KT board, acrylic, magnetic sticker, self-adhesive etc.
Material Fixation Mode	Vacuum absorption
Software resolution	0.025、0.01、0.1 optional
Transmission Mode	Ethernet port
Drive System	Bus controller, advanced servo system, imported linear guide rail, lead screw, linear motor drive
Instruction system	HP-GL compatible format
Automatic knife setting	Non-contact tool setting mode for drag knife, rotary tool, electric oscillating tool, creasing wheel tool, v-cut tool etc.
Automatic tool setting accuracy	0.05mm
Rated Power	16kW
Rated Voltage	380V±10%
Machine Weight	2600kg
Effective Cutting Size (WxL)	1600mm×3200mm
Machine Size (WxLxH)	3630mm×4200mm×1672mm(Single size) 3630mm×13165mm×1672mm(Send cut size)

Note: * Dependent on materials and application