

AMC TRI-RATED

AMC TRI-RATED



Tri-rated Flexible PVC Cable

H05V2-K / H07V2-K / BS 6231 / UL758* / CSA 22.2*

Application

Specialist cable, heat and flame retardant, suitable for industrial applications, such as; switch control, instrumentation panels for switchgear, for example motor control.

Approvals

BASEC Approved Product

Test report no: W1TTA2870

BS 6231 / EN 50525-2-31 / UL758* / CSA 22.2* / IEC 60228

Flame retardant in accordance with IEC 60332-1-2

Quality statement

AMC are a certified BASEC Approved Manufacturer, and accredited to ISO 9001 by NQA.

Environmental statement

AMC take every action possible to ensure we are a sustainable, and environmentally aware manufacturer. **End of life care;** ensure that all cable product is disposed of inline with relevant WEEE Regulations.

Characteristic	Declared Performance	Standards
Temperature range	*UL / CSA: -15°C to +90°C BS 6231: -15°C to +90°C Suitable at -40°C for fixed installations	
Operating voltage	0.6 / 1kV	
Application of insulation	PASS	
Durability	PASS	
Legibility	PASS	
Marking legend	PASS	
Voltage test	PASS	
Overall diameter	PASS	
Flame propagation	PASS	
Conductor construction	PASS	
Bending at low temperature	PASS	
Long term resistance of insulation to D.C.	PASS	
Pressure test at high temperature	PASS	
Resistance to cracking insulation (heat shock)	PASS	
Thickness of insulation	PASS	
Maximum diameter of wires	PASS	
Conductor resistance	PASS	
Insulation resistance insulation	PASS	
Tensile test on insulation	PASS	
Loss of mass insulation	PASS	

BS 6231: 2006, UL758*, CSA 22.2*

*AMC tri-rated cable is certified to BS 6231 and compliant to UL758 and CSA 22.2

Tri-rated Flexible PVC Cable

H05V2-K / H07V2-K / BS 6231 / UL758* / CSA 22.2*

Product options

As the manufacturer, AMC are able to offer several product options, some of which are available upon request only, please contact our Sales Team should you have a special requirement, our options are as follows:-

Packaging:-

- Standard branded card reels
- Larger wooden, or plastic reels
- Card box-pack for improved storage at larger quantities
- Card barrel-pack; secure, and waterproof
- Returnable packaging can be agreed upon request

Colours:-

- AMC have 12 standard colours (see below), however any colour can be produced upon request
- Any combination of two colours can be manufactured to produce a bi-colour striped cable

Multicore:-

- AMC can produce the cable in any core quantity up to 13core as standard
- AMC can produce higher quantity core cable types on request
- Various cable core types can be combined into a 'hybrid' multicore should you have a special design requirement

Part No	Conductor Specification (mm)	Maximum Overall Diameter (mm)	Maximum Resistance Per Metre at 20°C (Ohms)	Colour	Reel & Packaging
3TR.5	0.5	2.5	0.0371		
3TR.75	0.75	2.7	0.0247		
3TR1	1	2.8	0.0185		
3TR1.5	1.5	3.05	0.0127		
3TR2	2	3.4	0.00942		
3TR2.5	2.5	3.5	0.0076		
3TR3	3	4	0.00615		
3TR4	4	4.2	0.00471		
3TR4.5	4.5	4.65	0.00406		
3TR6	6	4.8	0.00314		
3TR7	7	5.2	0.00279		
3TR8.5	8.5	5.6	0.0022		
3TR10	10	6.3	0.00182		
3TR16	16	7.65	0.00116		
3TR25	25	9.4	0.000743		
3TR35	35	10.4	0.00056		

Tri-Rated cables are available in the following colours:

(R) RED, (B) BLACK, (G) GREEN, (LG) LIGHT GREEN, (U) BLUE, (Y) YELLOW, (N) BROWN, (P) PURPLE, (K) PINK, (S) SLATE GREY, (W) WHITE, (O) ORANGE

Any combination of two of the above colours can be made available upon request

All cable are available as 10/30/50/100/250/500m reels.

Barrel pack up to 10,000m dependant upon cable.

Box pack up to 6,000m dependant upon cable.

**If you have a special packaging request please contact our Sales Team.*

*AMC tri-rated cable is certified to BS 6231 and compliant to UL758 and CSA 22.2