



AMC SPEAKER

Application

Figure 8 Stereo Speaker Cable (2-core, 60V, low-voltage rated) is a versatile, flexible, and economical cable designed for secure audio and low-power, non-grounded applications. Its signature “figure of 8” construction allows for easy separation of conductors for quick, efficient installation.

Environmental statement

AMC take every action possible to ensure we are a sustainable, and environmentally aware manufacturer. End of life care; ensure that all cable product is disposed of inline with relevant WEEE Regulations.

Specification

Voltage	60v
Cores	Class 5 Conductor
Sheath	PVC
Operating Temperature	-40° to 105°C

Standards (Compliance / Certification)

BS EN 60228:2005
ISO6722-1:2011 Class B

Part No.	Conductor Specification (mm)*	Conductor Cross Section (mm ²)	Maximum Overall Dimensions (mm)	Nominal Current Rating (Amps)**	Sheath Colours	Reel Sizes (Metres)
550	2 x 12/0.20	2 x 0.35	3.6 x 1.7	2	Black-Black/White	30, 100, 500
551	2 x 16/0.20	2 x 0.5	3.9 x 1.9	3	Black-Black/White	30, 100, 500
552	2 x 24/0.20	2 x 0.75	4.3 x 2.1	6	Black-Black/Red	30, 100, 500
553	2 x 32/0.20	2 x 1.0	4.7 x 2.3	10	Black-Black/Blue	30, 100
554	2 x 21/0.30	2 x 1.5	5.9 x 2.9	15	Black-Black/White	30, 100

Typical Applications



AUDIO & ENTERTAINMENT SYSTEMS



APPLIANCES



SECURITY SYSTEMS

The conductor specifications shown are representative configurations; actual cable strand may differ slightly, but will meet the resistance values shown. Nominal current amperage ratings are provided as a guide only, and can vary depending on the application, condition and environmental factors. If in doubt, please consult a qualified electrician.