Twist-on Splice Connectors

600V | Pressure Type for Copper-Clad Aluminum (CCA)

Engineering Specifications:

- **Standards:** Certified in UL 486C; Conforms to CSA STD C22.2# 188
- **Listings:** ETL: 5027144
- **Identification and Usage:**

  Listed for use as a pressure-type wire connector on the following solid and/or stranded: Copper (CU) to Copper (CU) or Copper-Clad Aluminum (CC) to Copper-Clad Aluminum (CC) or Copper (CU) to Copper-Clad Aluminum (CC). Suitable for use with Copperweld® CCA Building Wire. Identified for intermixing between Copper (CU) and Copper-Clad Aluminum (CC) conductors.









Specifications	22-10 AWG (Solid/Stranded)	18-8 AWG (Solid/Stranded)	14-6 AWG (Solid/Stranded)
Part Number	**CWLD12-TAN**	**CWLD13-RED**	**CWLD17-BLUE**
Identification Marking	P12 CC	P13 CC	P17 CC
Color	Tan	Red	Blue
Temperature Rating (Max.)	105°C (221°F)	105°C (221°F)	105°C (221°F)
Voltage Rating (Max.)	600V	600V	600V
Wire Range*	22-10 AWG	18-8 AWG	14-6 AWG
Quantity per Bag	1000 Pieces	1000 Pieces	500 Pieces
Bag Part Number	CWLD12-TAN-1000	CWLD13-RED-1000	CWLD17-BLUE-500
Quantity per Barrel	37,000 Pieces	25,000 Pieces	9,000 Pieces
Barrel Part Number	CWLD12-TAN-37000	CWLD13-RED-25000	CWLD17-BLUE-9000

* Size range is approximate. Does not reflect full range of wire combinations.

Wire Combinations:

For a complete list of wire combinations, scan the QR code below or visit **copperweld.com/wire-combos**

COPPERWELD® BUILDING WIRE

CW-SPEC-BW-TWISTON-ETL-V001-10.2026 | ©2026 Copperweld Bimetallics, LLC. All rights reserved.
Copperweld® and Copperweld Building Wire® are a registered trademarks of Copperweld Bimetallics, LLC.

615-377-4200
buildingwire@copperweld.com