

SUMMIT NRC+



RECYCLED
CONTENT



FIRE
PERFORMANCE



100%
ASBESTOS-FREE



15 YEAR
WARRANTY

MATERIAL	Mineral Fibre
SURFACE	Fleece face
PATTERN	Non directional pattern design
FIRE RATING	NCC GROUP 1 (ISO 9705:2016)

COLOURS	 
ENVIRONMENT	ISO 14001 and ISO 9001
RECYCLED %	60% recycled content


PERFORMANCE	Thickness	NRC	CAC	LRV	RH
	19mm	0.85	35	0.90	99

SIZE GUIDE


Note: more module and size options available.

	MODULE	LENGTH	WIDTH	C SPLINE
APOLLO TWO-WAY TOP HAT GRID	1200mm	1188mm	396mm / 3 Tiles	25mm
		1188mm	297mm / 4 Tiles	25mm
		1188mm	237.6mm / 5 Tiles	25mm
	1350mm	1338mm	446mm / 3 Tiles	35mm
		1338mm	334.5mm / 4 Tiles	25mm
		1338mm	267.6mm / 5 Tiles	25mm
	1500mm	1488mm	496mm / 3 Tiles	35mm
		1488mm	372mm / 4 Tiles	35mm
		1488mm	297.6mm / 5 Tiles	25mm
APOLLO ONE-WAY TOP HAT GRID	MODULE	LENGTH	WIDTH	C SPLINE
	1200mm	1188mm	600mm max.	25mm
	1350mm	1338mm	450mm max.	25mm / 35mm
	1500mm	1488mm	500mm max.	25mm / 35mm
APOLLO T-BAR GRID	MODULE	LENGTH	WIDTH	T BAR
	1200x600mm	1195mm	595mm	15mm / 24mm
	600x600mm	595mm	595mm	


EDGE DETAILS




Top Hat Grid
with c-spline edge
Ref: CS



Top Hat Grid
with square edge
Ref: SQ



T-Bar Grid
with square edge
Ref: SQ



15mm T-Bar Grid
with tegular edge
Ref: TG15



24mm T-Bar Grid
with tegular edge
Ref: TG24