

SIROCCO



RECYCLED
CONTENT



FIRE
PERFORMANCE



BIO-SOLUBLE
(NOTE Q)



100%
ASBESTOS-FREE



25 YEAR
WARRANTY

MATERIAL	Mineral Fibre
SURFACE	Sand textured face
PATTERN	Non directional pattern design
FACE FINISH	





COLOURS	 				
ENVIRONMENT	ISO 14001 and ISO 9001				
RECYCLED %	60% recycled content				
FIRE RATING	NCC GROUP 1 (ISO 9705:2016)				
PERFORMANCE	Thickness	NRC	CAC	LRV	RH
	15mm	0.50	35	0.86	99
	19mm	0.55	40	0.86	99

SIZE GUIDE

Note: more module and size options available.

	MODULE	LENGTH	WIDTH	C SPLINE
APOLLO TWO-WAY TOP HAT GRID	1200mm	1188mm	396mm / 3 Tiles	25mm
		1188mm	297mm / 4 Tiles	25mm
		1188mm	237.6mm / 5 Tiles	25mm
	1350mm	1338mm	446mm / 3 Tiles	35mm
		1338mm	334.5mm / 4 Tiles	25mm
		1338mm	267.6mm / 5 Tiles	25mm
	1500mm	1488mm	496mm / 3 Tiles	35mm
		1488mm	372mm / 4 Tiles	35mm
		1488mm	297.6mm / 5 Tiles	25mm
APOLLO ONE-WAY TOP HAT GRID	MODULE	LENGTH	WIDTH	C SPLINE
	1200mm	1188mm	600mm max.	25mm
	1350mm	1338mm	450mm max.	25mm / 35mm
	1500mm	1488mm	500mm max.	25mm / 35mm
APOLLO T-BAR GRID	MODULE	LENGTH	WIDTH	T BAR
	1200x600mm	1195mm	595mm	15mm / 24mm
	600x600mm	595mm	595mm	

EDGE DETAILS

				
Top Hat Grid with c-spline edge Ref: CS	Top Hat Grid with square edge Ref: SQ	T-Bar Grid with square edge Ref: SQ	15mm T-Bar Grid with tegular edge Ref: TG15	24mm T-Bar Grid with tegular edge Ref: TG24