

ASTRID



FIRE
PERFORMANCE



BIO-SOLUBLE
(NOTE Q)



100%
ASBESTOS-FREE



15 YEAR
WARRANTY

MATERIAL

SURFACE

PATTERN

FACE FINISH

Mineral Fibre

Latex paint with perforated face

Non directional pattern design



COLOURS

ENVIRONMENT

FIRE RATING

PERFORMANCE

○ ●

ISO 14001 and ISO 9001

NCC GROUP 1 (ISO 9705:2016)

Thickness	NRC	CAC	LRV	RH
15mm	0.60	35	0.86	99
19mm	0.70	40	0.86	99

SIZE GUIDE

Note: more module and size options available.

APOLLO TWO-WAY TOP HAT GRID

MODULE	LENGTH	WIDTH	C SPLINE
1200mm	1188mm	396mm / 3 Tiles	25mm
	1188mm	297mm / 4 Tiles	25mm
	1188mm	237.6mm / 5 Tiles	25mm
1350mm	1338mm	446mm / 3 Tiles	35mm
	1338mm	334.5mm / 4 Tiles	25mm
	1338mm	267.6mm / 5 Tiles	25mm
1500mm	1488mm	496mm / 3 Tiles	35mm
	1488mm	372mm / 4 Tiles	35mm
	1488mm	297.6mm / 5 Tiles	25mm


APOLLO ONE-WAY TOP HAT GRID

MODULE	LENGTH	WIDTH	C SPLINE
1200mm	1188mm	600mm max.	25mm
1350mm	1338mm	450mm max.	25mm / 35mm
1500mm	1488mm	500mm max.	25mm / 35mm


APOLLO T-BAR GRID

MODULE	LENGTH	WIDTH	T BAR
1200x600mm	1195mm	595mm	15mm / 24mm
600x600mm	595mm	595mm	

EDGE DETAILS




Top Hat Grid
with c-spline edge
Ref: CS



Top Hat Grid
with square edge
Ref: SQ



T-Bar Grid
with square edge
Ref: SQ



15mm T-Bar Grid
with tegular edge
Ref: TG15



24mm T-Bar Grid
with tegular edge
Ref: TG24