

MEDISHIELD



FIRE
PERFORMANCE



BIO-SOLUBLE
(NOTE Q)



100%
ASBESTOS-FREE



15 YEAR
WARRANTY

MATERIAL

Mineral Fibre Laminated with Transparent Acoustic Tissue

SURFACE

Advanced antibacterial properties

PATTERN

Non directional pattern design

FACE FINISH



COLOURS

ENVIRONMENT

ISO 14001 and ISO 9001

FIRE RATING

NCC GROUP 1 (ISO 9705:2016)

PERFORMANCE

Thickness	NRC	CAC	LRV	RH
15mm	0.65	35	0.90	95
19mm	0.70	40	0.90	99

SIZE GUIDE


Note: more module and size options available.

APOLLO TWO-WAY TOP HAT GRID	MODULE	LENGTH	WIDTH	C SPLINE
	1200mm	1188mm	396mm / 3 Tiles	25mm
		1188mm	297mm / 4 Tiles	25mm
		1188mm	237.6mm / 5 Tiles	25mm
	1350mm	1338mm	446mm / 3 Tiles	35mm
		1338mm	334.5mm / 4 Tiles	25mm
		1338mm	267.6mm / 5 Tiles	25mm
	1500mm	1488mm	496mm / 3 Tiles	35mm
		1488mm	372mm / 4 Tiles	35mm
		1488mm	297.6mm / 5 Tiles	25mm


APOLLO ONE-WAY TOP HAT GRID	MODULE	LENGTH	WIDTH	C SPLINE
	1200mm	1188mm	600mm max.	25mm
	1350mm	1338mm	450mm max.	25mm / 35mm
	1500mm	1488mm	500mm max.	25mm / 35mm

APOLLO T-BAR GRID	MODULE	LENGTH	WIDTH	T BAR
	1200x600mm	1195mm	595mm	15mm / 24mm
	600x600mm	595mm	595mm	

EDGE DETAILS




Top Hat Grid
with c-spline edge
Ref: CS



Top Hat Grid
with square edge
Ref: SQ



T-Bar Grid
with square edge
Ref: SQ



15mm T-Bar Grid
with tegular edge
Ref: TG15



24mm T-Bar Grid
with tegular edge
Ref: TG24