HF525Z Product Highlight

Protects Flooring up to 95% RH

HappyFeet INTERNATIONAL

Moisture Vapor Barrier & Encapsulator

HF525Z is a simple way to protect what's on top. Engineered to fight moisture, HF525Z can also be used as an encapsulator, eliminating the need to remove existing or cutback adhesive residue. It is uniquely adaptable to varying moisture levels depending on your needs.



Product Benefits

- 1-part, roller-applied system cures within 1-2 hours
- Encapsulates old adhesive residue (including cutback)
- pH blocker protects from alkali attack
- Primes porous substrates (including gypcrete)
- LEED v4 contributing
  - VOC content 0 g/L *(meets SCAQMD Rule 1168)*
  - CDPH/EHLB Standard Method v1.2
  - Does not contain methylene chloride and perchloroethylene
  - Contributes to low emitting materials

**Data icons

*RH
93 - 95%**

pH
NTR*(14)

*MVER
10 - 15 lbs**

CURE TIME
1- 2 hrs

For Glue-Down Applications

1. **HF525Z**, Moisture Vapor Barrier
2. **HF9100**, Flooring Adhesive

Certifications

floor score
GREENGUARD GOLD
CRI GREEN LABEL +PLUS
mindful MATERIALS

Application Methods

1. 350 sf/gal (1 coat)
2. 200 sf/gal (2 coats)

Note: Coverage range dependent upon substrate composition and porosity and application method.

Made in the USA

Available in 4-Gallon Pail
Shelf Life: 2 Years

***NTR** = No Testing Required
****Data icons** reference 1 or 2-coat applications see technical data sheet for details

happyfeetinternational.com | 706.937.2500 | info@happyfeet.com