

HF9100 Transitional Pressure Sensitive LVP Adhesive (Hybrid Acrylic)



Product Highlights

- Made specifically for Luxury Vinyl Plank (LVP).
- Hard setting adhesive that locks the product in. Other inferior adhesives stay sticky and do not have the same Tackifier (TAC) strength and are never fully bonded.
- Moisture tolerant up to 99% Relative Humidity (RH). Average Relative Humidity (RH) on comparable inferior adhesives is 80%.
- Semi wet installation is recommended for maximum bond.
- 25 lbs Tackifier (TAC) advantage compared to inferior, competing adhesives at 5 lbs Tackifier (TAC).
- All substrates must be tested for moisture content prior to installation.
- All floor patch and leveling compounds must be rated as moisture resistant.
- Adhesive pails should be acclimated in conjunction with the LVP.
- All glue down applications require the use of HF525Z moisture mitigating primer.

Spread Rates & Trowel Sizes

- 175-200 sq. ft. per gallon
- Up to 800 sq. ft. per gallon pail
- **Trowel Size** - 1/16" x 1/16" x 1/16" square notch

Cleaning Instructions

- **While product is still wet** - Use a damp cloth and water to remove.
- **While product is still soft** - Use Denatured alcohol or mineral spirits with a clean cloth.

Storage

- Store at temperature between 50–90 degrees.
- Product is freeze/thaw stable to 10 degrees.
- Shelf Life - 2 years

Working & Flash Times

- Allow the adhesive to flash (*20-30 minutes depending on temperature and humidity*) then install product within 3 hours of the flash stage.
- Roll and cross roll with a 75-100 lb roller.
- **Light Traffic** - Immediately
- **Heavy Traffic** - 24 Hours
- **Heavy Rolling Loads** - 48 Hours

