

WD23U – Unlimited Moisture Vapor Barrier, Urethane Adhesive

- All floor patch and leveling compounds must be rated as moisture resistant
- Adhesive pails should be acclimated in conjunction with the hardwood



Spread Rates & Trowel Sizes

Bond Only

- Up to 35 sq. ft. per gallon
- **Trowel Size** - 1/4" x 1/4" x 1/4" Square Notch
- When applying as **bond only**, there is no moisture control. Do not use moisture mitigating primers including HF525Z. With this application it is imperative to know the moisture content of the concrete.
- Wait 10 minutes once adhesive is spread to install flooring – 45-60 minute working time.
- Roll and cross roll with a 75-100lb roller within 2 hours.



Bond & Moisture Barrier

- Up to 20 sq. ft. per gallon
- **Trowel Size** - 1/2" x 15/32" V Notch
- No moisture testing required, concrete must be porous
- Wait 10 minutes once adhesive is spread to install flooring – 45-60 minute working time.
- Roll and cross roll with a 75-100lb roller within 2 hours.

Cleaning Instructions

- Immediately remove any adhesive using a damp cloth with an approved adhesive remover (Oil Flow 141) or mineral spirits.

Storage

- Store at temperature between 50–90 degrees.
- Product is freeze/thaw stable to 10 degrees.
- **Shelf Life** - 1 Year