

WD24R – Unlimited Moisture Vapor Barrier, Elastometric Adhesive



- All floor patch and leveling compounds must be rated as moisture resistant
- Adhesive pails should be acclimated in conjunction with the hardwood

Spread Rates & Trowel Sizes

Bond Only

- Up to 50 sq. ft. per gallon
- **Trowel Size** - 3/16" x 1/4" x 5/16" V Notch
- When applying as **bond only**, there is no moisture control. Do not use moisture mitigating primers including HF525Z. With this application it is imperative to know the moisture content of the concrete.
- Install flooring immediately upon troweling adhesive – 45 minute working time.
- Roll and cross roll with a 75-100lb roller within 2 hours.



Bond & Moisture Barrier

- Up to 20 sq. ft. per gallon
- **Trowel Size** - 1/2" x 15/32" V Notch
- No moisture testing required, concrete must be porous.
- Install flooring immediately upon troweling adhesive – 45 minute working time.
- Roll and cross roll with a 75-100lb roller within 2 hours.

Cleaning Instructions

- **While product is still wet:** Use a damp cloth and water to remove
- **While product is still soft:** Use an approved adhesive remover (Oil Flow 141) or mineral spirits.

Storage

- Store at temperature between 50–90 degrees.
- Product is freeze/thaw stable to 10 degrees.
- **Shelf Life - 1 Year**