



SALES & LEASING

Specification

Montracon 4.2m

*Tri-Axle Postless ENXL Curtainsider
(Barn Doors & Tail Lift)*

16.06.2026



External Dimensions

External length	13600mm	External width	2550mm
Overall height	4200mm	Wheelbase	7900mm
Coupling height	1250mm	Kingpin position	1600mm

Internal Dimensions

Side aperture length	13395mm	Door aperture width	2412mm
Door aperture height	2785mm	Aperture under cant rail	2600mm

Plating WT.

Kingpin	15000 kg	Suspension UK	24000 kg
Gross Trailer Wt.	39000 kg	Operation	To suit 44 tns

Load Compartment Rating

Load compartment rated to EN12642 'XL' standard for a 29 tonne payload, side aperture 3280mm maximum. EN12642-XL decal fitted.

Chassis

Neck depth	150mm (inc. PU plate) to ISO1726	King-pin type	Bolt-in kingpin
Rubbing plate	8mm high tensile steel	Rail/rave section	'G' section steel
Deck lashings	13 pairs lashing cleats in rave	Beam/bogie centres	1200mm
Rope hooks	Optional extra	Ferry lashings	Optional extra



Specification

Montracon 4.2m Tri-Axle Postless ENXL Curtainsider

Floor

Type	29mm phenolic coated plywood (RIGA TEX brand)	Floor bearer	80mm x 46mm 'I' section
Floor bearer pitch	430mm with 300mm from rear axle	Dump plate	Optional extra

Support Legs

Make Feet	Montracon Compensating	Model	Heavy Duty
------------------	------------------------	--------------	------------

Axles

Make Size Cartridge bearings Hubodometer	3 off BPW 420 x 180 Optional extra Optional extra	Type Steer axle Lift axle	Drum (10 stud) Optional extra Optional extra
---	--	----------------------------------	--

Suspension

Make Spread	BPW 1310mm	Model	ECO Air
--------------------	---------------	--------------	---------

Wheels

Type Spare wheel carrier	Steel Optional extra	Finish Spare wheel & tyre	Factory silver Optional extra
---------------------------------	-------------------------	--------------------------------------	----------------------------------

Tyres

Make Data	Premium brand See tyre manufacturers website for tyre labelling data	Size	385/65 R22.5
------------------	---	-------------	--------------



Tail Lift

Make	Dhollandia	Model	DH-RM tuckaway tail lift
Platform	1500mm	Capacity	1500 kg
Controls	Wander lead		

Brake System

Brake system	2 line colour coded system	Antiskid	Haldex
Load sensing valve	Included	Park brake	Spring brake chambers to axle manufacturers recommendation
Park shunt valve	Trailer Emergency Module featuring 'safe parking' function		

Pneumatics

Coupling type	'C' on stainless steel raised connector panel	Raise/lower	Included with auto reset
Dump valve	Optional extra		

Lighting

Type	24v single pole via 7 pin 24N & 24S and ISO 7638 EBS connector	Rear lamp	Trucklite type 800 inc. fog & reverse lamp and triangular reflector
Separate reverse lamp	Optional extra	Separate fog lamp	Optional extra
No Plate Lamp	As per No. Plate Holder Supplied	Rear marker Lamp	Trucklite L.E.D.
Side marker Lamp	5 x Trucklite L.E.D. Indicator	Front marker lamp (btm)	Trucklite L.E.D.
Front marker lamp (top)	Trucklite L.E.D.	Interior lamps	Optional extra
Rear lamp mounting	Part of tail lift		

Sideguards

Type	Hinged, galvanised	Horizontals	Anodised aluminium
-------------	--------------------	--------------------	--------------------



Spray Suppression

Type	Mudwings on bolt on galvanised stays	Flaps	On rear wings with STC logo
-------------	--------------------------------------	--------------	-----------------------------

Rear End

Underrun	Square section steel	No plate holder	Type / model / location to suit application
Protection	To suit tail lift		

Finish

Paint system	All painted steel shotblasted and coated with high build primer and 2 pack single colour top coat		
Chassis colour	Black		
Landing legs	OEM standard black	Axles	OEM standard black
Hubs	OEM standard black		

Miscellaneous

Licence plate holder	Fitted	VTG6A Certificate	Included
Ministry 'C' Number	Stamped on plate - fitted to chassis	VIN Number	Stamped on chassis

Front

Frame	Pressed steel posts bolted to 300mm kickstrip	Bulkhead	18mm GRP-ply bulkhead panel with belts for strap retention
Frame fixing	Bolted		

Rear (Barn Doors)

Rear frame	Bolted rolled steel channel posts	Doors	19mm ply-metal
-------------------	-----------------------------------	--------------	----------------



Montracon 4.2m Tri-Axle Postless ENXL Curtainsider

Lockbars	2 galvanised lockbars per door	Hinges	4 hinges per door
Holdbacks	Plastic coated steel wire & clip	Access	Pull-out ladder and grab handle

Roof

Top/Cantrail	FHT Postless roof cant rail (TAPERED)	Roofsheets	One piece 0.8mm aluminium
Roof support	N/A - Postless roof design	Pelmets	Black

Sides

Curtain type	900g/m ² , 2x2 weave, welded strap curtains to EN12642XL	Hardware	Stainless steel new HD Montracon buckle
Curtain pole	34mm galvanised	Features	300mm bottom hem, top rain flap
Tensioning	Ratchet, front & rear	Curtain colour	Aircraft Blue

Cargo Control

Type Straps	Henderson 13 pairs	Position	Outboard vertical
--------------------	-----------------------	-----------------	-------------------

Finish (Body)

Front frame	Hot dip galvanised	Rear frame	Hot dip galvanised
Front panel	Aircraft Blue	Rear closure	Aircraft Blue
Paint system	All painted steel shotblasted and coated with high build primer and a 2 pack single colour top coat		

Miscellaneous (Body)

Conspicuity marking	Red tape to rear, white tape to sides (dashed type used).
Long vehicle boards	Optional extra
Decals	Montracon standard decals only



STOCKPORT TRUCK CENTRE LTD

16th June 2026

Specification

Montracon 4.2m Tri-Axle Postless ENXL Curtainsider

Customer Sign-Off

Signed

Print Name

Position

Date
