



SALES & LEASING

Specification

2026 SDC PSK

11/06/2026



STOCKPORT TRUCK CENTRE LTD

19th July 2024

Quotation & Specification

DON-BUR 13.7m Tri-Axle Stepframe Palletmaster
Curtain Sided Trailer With Fixed Second Deck

Specification

DIMENSIONS

External length: $\pm 13,590$ mm
Fifth wheel height: $\pm 1,250$ mm
Width outside: $\pm 2,550$ mm

KING PIN

2" kingpin bolt-in, assembled in 8 mm rubbing plate.
Kingpin weight stated as 15,000 kg

CHASSIS

Full Length constructed in Steel
Couplings are plate mounted on the front crossmember.
Sideguards: Aluminium Sideguards complete with Galvanised Folding Mounting Brackets fitted. 2 of side guard downstays fitted.
Lashing rings: 4 pair of chassis lashing rings fitted to the trailer.
Rope Hooks: Heavy Duty 16mm rope hooks fitted to every crossmember.
Rear underrun: Steel Separate Rear Infills complete with 100x100 Crashbar fitted complete with plastic end caps.
VTG 6A holder model no. TTC 20068 fitted to beam rear of landing legs near side.

LANDING LEGS

Two speed JOST landing legs with rocking/flat feet designed for trailers with air suspension.
Landing leg handle fitted UK nearside.

AXLE AND SUSPENSIONS

3 axles, BPW axles. BPW Drum brakes.



STOCKPORT TRUCK CENTRE LTD

19th July 2024

Quotation & Specification

DON-BUR 13.7m Tri-Axle Stepframe Palletmaster
Curtain Sided Trailer With Fixed Second Deck

WHEELS AND TYRES

6 x Goodyear 385/65 x R22.5 tyres fitted - KMAX pattern: Fuel D: Grip B: DB 71 or premium brand tyres on Steel rims* (*unless sales option varied).

BRAKES

2 line air brakes to current EU regulations.
Electronic braking system Knorr Bremse EB+ 2S2M including QRV c/w TEM
Parking brake through spring brakes.
Automatic slack adjusters Spring brakes fitted.
Pull Valves fitted off side.
60 l steel air tanks.

ELECTRICS

24 V system with 24S, 24N and ISO 7638 permanent connections.
Front marker lights are Rubbolite TL34 LED
Sidelights are Rubbolite 890 LED.
Rear lamps are single Rubbolite 800 bulb.
Number plate holder with top light.

SPRAY SUPPRESSION

6 x VOSA regulation Bolt On Full Length Thermo Plastic Mudwing, 2 Off Mudflaps Fitted

BODY

Front Bulkhead
Headboard: 1500 mm high detachable headboard.
Floor Construction
Side rails: 125mm x 75 mm x 8mm angle side rail with horizontal leg fitted above cross members.
Cross members: are IPEA80 spaced at 450mm pitches.
Floor surface: 28 mm Keruing floor fitted between the beams
Lashing rings: 13 pair of T Bar deck lashing rings fitted.
Rope Hooks: Heavy Duty 16mm rope hooks fitted to every crossmember.



STOCKPORT TRUCK CENTRE LTD

19th July 2024

Quotation & Specification

DON-BUR 13.7m Tri-Axle Stepframe Palletmaster
Curtain Sided Trailer With Fixed Second Deck

Sockets: 6 pairs (12 total) of 100 x 100 sockets fitted to side rails. (1 pair fitted at rear corners and others equal spaced between)

Posts: 10 off 80 x 80 posts fitted. (Posts fitted with top loop to form fall arrest system. 10 off post extensions supplied complete with suitable storage. Extensions to add 1200mm to post height).

Posts: 1500 mm high above floor.

Twistlocks: 8 off fully retractable multi-stroke twistlocks fitted (container spacings: 2 x 20, 1 x 40 containers).

Pin rack fitted for storage

FINISHING

Axles and suspension with manufacturer's black anti corrosive coating. Primer and top coats both 2 pack paint for both chassis and body. Temperature baked in oven for correct hardness. Conspicuity markings side (white- solid line type) and rear (red) (UK) 50 Fitted to chassis (not siderails). Ministry 'C' Number Applied for & stamped to chassis plate

Chassis paint colour: Aircraft Blue

Customer Sign-Off

Signed

Print Name

Position

Date
