


BRECOflex CO., L.L.C.

High Precision Drive Components

The World Leader In Polyurethane Timing Belts

Connecting Timing Belts

Solutions for Field Installation



Connecting Timing Belts


Solutions for Field Installation

BRECOflex CO., L.L.C. offers 3 different technologies for installation of conveyor belts with prepared ends. No time consuming equipment tear down is required when using the following technologies:


1. Field Welder - a self-contained heat welding press
2. Connecting Kit/ Belt Lock - mechanical connection kit comprised of plates and inserts to join T/AT/ATN belts
3. PinLock - mechanical connection kit comprised of lateral screws through the teeth

A comparison chart of the four technologies can be found on page 7.

Field Welder



Connecting Kit / Timing Belt Lock



PinLock



Connecting Timing Belts

Solutions for Field Installation

Field Welder - Connecting Kit for Field Assembly


BRECOflex CO., L.L.C. offers Field Welders for installation and replacement of endless polyurethane timing belts in machinery and equipment on location. Field Welder belts are prepared with high precision, pre-cut finger spliced ends to be welded on-site.

- No costly machine disassembly necessary
- Minimize down time - replacement time 30-45 minutes
- Only 120V or 240V 60Hz required (no water cooling)
- Tensile strength of the field welded belt equals factory weld strength
- Available for all standard pitches, including ATN, HTD, self-tracking, and double sided belts
- Available in widths from 12mm to 150mm. Various widths can be welded by using filler material or a tooth plate set for each belt pitch / width. Lengths over 900mm
- Custom top plates can accommodate profiles and many backing materials (contact Applications Engineering for details)

Ordering Example

50 T10/1000 FW

Belt ends prepared for field welding



Timing Belt Lock - AT10 / T10

BRECOflex CO., L.L.C. offers a mechanical timing belt connection technology for T10 and AT10 pitch timing belts in conveyor applications.

The Timing Belt Locks are compatible with standard AT10 and T10 belts and pulleys for direct replacement. Timing Belt Locks are available in widths of 32, 50, 75 and 100mm.

- Designed for rapid belt assembly on the machinery using just a screw driver
- Belt ends are factory machined to accept hardware consisting of 10 connecting plates, 10 tooth inserts, and the requisite screws
- Spare parts kits are available to change out the inserts in applications with frequent reassembly

Ordering Example

75 T10 DC/8400 DC

belt prepared for belt lock connecting kit

-kit included, not installed-



Connecting Timing Belts

Solutions for Field Installation


ATN - Connecting Kit for Field Assembly

BRECOflex CO., L.L.C. offers mechanical ATN Connecting Kits for rapid belt assembly and disassembly in the field directly on the conveyor system.

- Mechanical hardware connection to clamp together finger stamped belt ends.
- Hardware consists of polyamide, stainless steel, and brass inserts, steel top plates, and the requisite screws.
- Connection technology has option to allow ATN profiles to attach in joined area.

Version “C” (standard)


- Available for pitches ATN10, ATN12.7, ATN10K6 and ATN12.7K6
- Belt thickness = 4.5mm, without any self-tracking guide
- Number of connection elements = 10
- Threaded hole size = M2.5
- Top plates are 0.9mm above the belt back
- Not suitable for mounting profiles in connecting kit area



Ordering Example 50 ATN10/1400 C
prepared for a C connecting kit
-kit included, not installed-

Version “DC” (deep connection - recessed top plates)


- Use when product must lay flat across the connecting kit area
- Available for pitches ATN10, ATN12.7, ATN20, ATN10K6 and ATN12.7K6
- Belt thickness = 5.4mm (ATN10, ATN12.7) and 8.0mm (ATN20) without any self-tracking guide
- Number of connection elements = 10 (ATN10, ATN12.7) and 9 (ATN20)
- Threaded hole size = M2.5 (ATN10, ATN12.7) and M3 (ATN20)
- Not suitable for mounting profiles in connecting kit area



Ordering Example 75 ATN10 DC/3600 DC
prepared for a DC connecting kit
-kit included, not installed-

Version “DC-PRO” (deep connection and profiles)

- A version of the flush connecting kit DC above but additionally suitable for mounting up to 5 profiles in connecting kit area
- Available for pitches ATN10, ATN12.7, ATN20, ATN10K6 and ATN12.7K6
- Belt pitches, thickness, number of connection elements and threaded hole sizes comparable to version “DC”



Ordering Example 75 ATN10 DC/2800 DC
prepared for a DC-PRO connecting kit
-kit included, not installed-

Connecting Timing Belts

Solutions for Field Installation


PinLock - Connecting Kit for Field Assembly

The BRECOflex CO., L.L.C. PinLock Connecting Kit enables you to quickly replace timing belts in the field using a manual or electric screwdriver to screw threaded pins through precision cut holes in the belt teeth.

- Precise water-jet finger pattern
- Hardware consists of stainless threaded pins
- Connection may be assembled/disassembled several times
- Possible with back covers or profiles
- Available with 6 pins (PL6) or 10 pins (PL10)

Ordering Example

25 T10/2670 PL
prepared for a 10-pin PinLock connecting kit
-kit included, not installed-



Connecting Timing Belts

Solutions for Field Installation

Maximum Allowable Tensile Strength Chart (N)

	Width (mm)	T10	T20	AT10	AT20	ATN10/ ATN10K6	ATN12.7/ ATN12.7K6	ATN20
C	25	-	-	-	-	-	-	-
DC	25	-	-	-	-	-	-	-
DC - PRO	25	-	-	-	-	-	-	-
FW	25	1100	1750	2125	-	1000	1000	1350
PL6	25	-	520	260	650	-	-	-
PL10	25	390	910	520	1300	-	-	-
C	32	-	-	-	-	-	-	-
DC	32	500	-	550	-	-	-	-
DC - PRO	32	-	-	-	-	-	-	-
FW	32	1408	2240	2720	3400	1280	1280	1728
PL6	32	-	700	420	840	-	-	-
PL10	32	560	1260	700	1680	-	-	-
C	50	-	-	-	-	750	750	-
DC	50	750	-	750	-	750	750	750
DC - PRO	50	-	-	-	-	750	750	750
FW	50	2200	3500	4250	5330	2000	2000	2700
PL6	50	-	1250	600	1500	-	-	-
PL10	50	900	2250	1200	3000	-	-	-
C	75	-	-	-	-	1150	1150	-
DC	75	1000	-	1000	-	1150	1150	1150
DC - PRO	75	-	-	-	-	1150	1150	1150
FW	75	3300	5250	6375	8000	3000	3000	4050
PL6	75	-	1920	960	2400	-	-	-
PL10	75	1440	3520	1920	4800	-	-	-
C	100	-	-	-	-	1500	1500	1500
DC	100	1500	-	1500	-	1500	1500	1500
DC - PRO	100	-	-	-	-	1500	1500	1500
FW	100	4400	7000	8500	10660	4000	4000	5400
PL6	100	-	2560	1280	3200	-	-	-
PL10	96/100	1920	4800	2560	6400	-	-	-

Note: 96 width for T10 and AT10, all others are 100


Note: Field welded belts (FW) are available for all belt pitches and in-between widths. For a complete list of strength numbers please see the polyurethane timing belt specifications charts in catalog B212 or contact customer service. Additional pitches are possible with PinLock such as self-tracking versions in the B105 PinLock Connecting Kit catalog pg. 3.

Connecting Timing Belts

Solutions for Field Installation

Field Connection Technologies - Comparison											
	Availability of Product Range	Strength	Short Belt Length Possible	Available Widths	Low Initial Cost	Low Recurring Cost	Suitable for Multiple Plant Locations	Suitable for Reassembly	Ease of Assembly and Disassembly	Use with Profiles (In Connection areas)	Use with Backings
C	*	*	**	*	**	**	***	***	**	⊘	⊘
DC	*	*	**	*	**	**	***	***	**	⊘	⊘
DC-PRO	*	*	**	*	**	**	***	***	**	***	⊘
FW	***	***	**	***	*	***	⊘	⊘	*	**	**
PL	**	*	**	*	**	**	***	***	**	*	**

Legend:
 *** Most
 ** Suitable
 * Acceptable
 ⊘ Not Applicable





SO 9001 CERTIFIED COMPANY

BRECOflex CO., L.L.C.

High Precision Drive Components

Contact Us

222 Industrial Way West • Eatontown, NJ 07724

Tel: 732-460-9500 • Fax: 732-542-6725

www.brecoflex.com • e-mail: info@brecoflex.com

Copyright 2025 BRECOflex CO., L.L.C. • BRECO®, BRECOFLEX® & ATN® are registered trademarks of BRECO Antriebstechnik GmbH • ARC-POWER® is a registered trademark of BRECOflex CO., L.L.C. • Kevlar® is a registered trademark of DuPont Patents Pending.

All recommendations for the use of the products described herein and all other data or information set forth in this publications, whether concerning such products or otherwise, are furnished without any guarantee, warranty representations or inducement of any kind whether expressed or implied, including but not limited to warranties of merchantability and fitness for a particular purpose. BRECOflex CO., L.L.C. expressly disclaims liability under any theory, including without limitation, contract negligence, misrepresentation or breach of any obligation relating to the recommendation, data or information set forth herein. Readers and customers are encouraged to conduct their own test before using any product. Read its label and all related instructions. BRECOflex CO., L.L.C. reserves the right to make changes in the technical and dimensional specifications of its products without prior notice. Responsibility for expenses incurred as a result of product changes or discontinuance or a product lies solely with the purchaser.