



NATALIA LANDOWSKA CERAMICS

PORCELAIN WALL SCONCE

REQUIRED SELECTIONS:

Please mark the selected installation type:

- ☐ Hardwired (mounted over a junction box). AC 110-120V line voltage for US,
- ☐ Hardwired AC 220-240V line voltage for Europe and Asia,
- ☐ Hardwired DC 12V low voltage - requires an LED driver installed by the Buyer

TERMS AND CONDITIONS:

1. Designer's medium is glazed porcelain and due to nature of material and techniques, no two pieces can be made identical. EACH PIECE IS UNIQUE BY DETAILS OF SHAPE, BRUSH STROKES AND SLIGHT COLOR VARIATIONS. DIMENSIONS MAY VARY UP TO ONE INCH.
2. Detailed high resolution photos will be sent for Buyer's approval before each piece is shipped.
3. General lead time for pieces made to order is 8-10 weeks excluding shipping, unless stated otherwise on the quotation. Designer will notify the Buyer if lead times are temporarily extended or pieces are available in stock.
4. All items ship cushioned, double boxed for US orders and wood crated for overseas. Cost of crating and shipping to be paid by Buyer.
5. If the piece is delivered damaged – the Buyer should take photos of the packaging and its contents and send to Designer within 2 days. The Designer will make a new piece in an expedited manner and start a claim process with the shipper.
6. All fixtures are made to order, no exchanges, refunds, or returns.
7. Pieces made to order require a 50% deposit. Balance payment must be received prior to shipping.

TECHNICAL SPECIFICATIONS:

1. Stained porcelain, glaze, unfinished brass fittings, LED bulbs.
2. All ceramic elements are fired to minimum 2250F / 1230C.
3. For pieces shipped within the US: all electrical components are UL listed. For pieces shipped to Europe, CE compliance declaration is included.
4. Bulbs installed are dimmable with most LED-compatible dimmers, up to 7.5W total per sconce.

INSTALLATION REQUIREMENTS:

1. 110-240V sconces require a recessed sconce junction box.
2. Low voltage sconces require a small recess in the wall (not smaller than 2in dia. and 1in deep) to curl and hide the wires. Use soft stranded wires for the in-wall wiring, 12AWG or thinner.

.....
Client's signature

.....
date