

# XM 2/650

forced action mixer



## When professional want peak performance

Planetary gearing: High force transmission

2 mixing speeds for flexible use

All viscosities and types of material can be processed

The XM 2-650 forced action mixer was developed specially for high performance. Wherever high quality mixing results and high throughputs are of the essence, this is where the XM models come in.

### Technical specifications

Size of mixing bucket	65 litres
Max. mixing volume	50 litres
Power supply	110 volts
Mixer output	1.5 hp
Mixer rotational speed	2 x 120 / 1 x 630 rpm
Rotational speed rim scraper	37 rpm
Adjustable mixing times	90 / 180 / Duration
Weight	105 kgs
Dimensions	1075mm x 690mm x 845mm
Item number	39014

Supplied by



*Making your job easier!*

09 42 68 101

[sales@everitts.co.nz](mailto:sales@everitts.co.nz)

[www.everitts.co.nz](http://www.everitts.co.nz)

## XM 2/650 forced action mixer



Planetary gearing



Bucket Dolly (accessory)



Rugged design

## Factors which make the XM such value for money

- Short mixing cycles
- High material throughput (up to 1 ton/hr)
- Reproducible mixing quality means quality assurance
- All viscosities and types of material can be processed
- Powerful drive system with various speeds
- Mixing bucket changed quickly
- Durable, low-maintenance machine
- One-man operation
- Mobile
- High standard of occupational safety
- Bucket dolly (practical accessory)

### Areas of application:

Industrial flooring coatings • Concrete refurbishing • Screed construction  
External wall insulating systems • Color granulate flooring • ECC / PCC systems  
Synthetic resin systems • Pavement fillers • Acid-proof construction  
Sewer and water-reservoir renovation • Clay mortar • Rubber granulate for sports ground

Supplied by



*Making your job easier!*

09 42 68 101

[sales@everitts.co.nz](mailto:sales@everitts.co.nz)

[www.everitts.co.nz](http://www.everitts.co.nz)