

E-Z WELD 210 ABS Medium Body Black

Version number: 2.0
Replaces version of: 2024-09-16 (1)

Revision: 2025-12-18

SECTION 1: Identification
1.1 Product identifier

Trade name **E-Z WELD 210 ABS Medium Body Black**

1.2 Relevant identified uses of the substance or mixture and uses advised against

Relevant identified uses
adhesive
ABS Solvent Cement

1.3 Details of the supplier of the safety data sheet

IPS Corporation (E-Z WELD)
100 Trousdale Way
Hartsville Tennessee
United States

Telephone: (310) 886-7600
Website: www.e-zweld.com

1.4 Emergency telephone number

Emergency information service
24 Hours - CHEMTEL: (800) 255-3924; International
(813) 248-0585

SECTION 2: Hazard(s) identification
2.1 Classification of the substance or mixture

Classification acc. to OSHA "Hazard Communication Standard" (29 CFR 1910.1200)

Hazard class	Category
serious eye damage/eye irritation	2
carcinogenicity	2
specific target organ toxicity - single exposure (narcotic effects, drowsiness)	3
flammable liquid	2

For full text of abbreviations: see SECTION 16.

The most important adverse physicochemical, human health and environmental effects

The product is combustible and can be ignited by potential ignition sources.

2.2 Label elements

Labelling acc. to OSHA "Hazard Communication Standard" (29 CFR 1910.1200)

- Signal word **danger**

- Pictograms

GHS02, GHS07, GHS08



E-Z WELD 210 ABS Medium Body Black

Version number: 2.0
Replaces version of: 2024-09-16 (1)

Revision: 2025-12-18

- Hazard statements

H225	Highly flammable liquid and vapor.
H319	Causes serious eye irritation.
H336	May cause drowsiness or dizziness.
H351	Suspected of causing cancer.

- Precautionary statements

P101	If medical advice is needed, have product container or label at hand.
P102	Keep out of reach of children.
P201	Obtain special instructions before use.
P210	Keep away from heat, hot surfaces, sparks, open flames and other ignition sources. No smoking.
P240	Ground and bond container and receiving equipment.
P241	Use explosion-proof electrical/ventilating/lighting equipment.
P242	Use non-sparking tools.
P243	Take action to prevent static discharge.
P261	Avoid breathing dust/fume/gas/mist/vapors/spray.
P271	Use only outdoors or in a well-ventilated area.
P280	Wear protective gloves/protective clothing/eye protection/face protection/hearing protection.
P303+P361+P353	If on skin (or hair): Take off immediately all contaminated clothing. Rinse skin with water or shower.
P304+P340	If inhaled: Remove person to fresh air and keep comfortable for breathing.
P305+P351+P338	If in eyes: Rinse cautiously with water for several minutes. Remove contact lenses, if present and easy to do. Continue rinsing.
P312	Call a poison center/doctor if you feel unwell.
P370+P378	In case of fire: Use sand, carbon dioxide or powder extinguisher to extinguish.
P403+P233	Store in a well-ventilated place. Keep container tightly closed.
P403+P235	Store in a well-ventilated place. Keep cool.
P405	Store locked up.
P501	Dispose of contents/container to industrial combustion plant.

- Hazardous ingredients for labelling

tetrahydrofuran (impurity - NIAS), methyl ethyl ketone, Carbon Black, acetone

2.3 Other hazards

Hazards not otherwise classified

Repeated exposure may cause skin dryness or cracking.

Results of PBT and vPvB assessment

Does not contain a PBT-/vPvB-substance at a concentration of $\geq 0.1\%$.

Endocrine disrupting properties

Does not contain an endocrine disruptor (ED) in a concentration of $\geq 0.1\%$.

SECTION 3: Composition/information on ingredients

3.1 Substances

Not relevant (mixture)

3.2 Mixtures

E-Z WELD 210 ABS Medium Body Black

Version number: 2.0
Replaces version of: 2024-09-16 (1)

Revision: 2025-12-18

Description of the mixture

Name of substance	Identifier	Wt%
methyl ethyl ketone	CAS No 78-93-3	25 – < 50
acetone	CAS No 67-64-1	10 – < 25
tetrahydrofuran (impurity - NIAS)	CAS No 109-99-9	0.1 – < 1
Carbon Black	CAS No 1333-86-4	0.1 – < 1

Remarks

For full text of abbreviations: see SECTION 16

SECTION 4: First-aid measures

4.1 Description of first-aid measures

General notes

Do not leave affected person unattended. Remove victim out of the danger area. Keep affected person warm, still and covered. Take off immediately all contaminated clothing. In all cases of doubt, or when symptoms persist, seek medical advice. In case of unconsciousness place person in the recovery position. Never give anything by mouth.

Following inhalation

If breathing is irregular or stopped, immediately seek medical assistance and start first aid actions. Provide fresh air.

Following skin contact

Wash with plenty of soap and water.

Following eye contact

Remove contact lenses, if present and easy to do. Continue rinsing. Irrigate copiously with clean, fresh water for at least 10 minutes, holding the eyelids apart.

Following ingestion

Rinse mouth with water (only if the person is conscious). Do NOT induce vomiting.

4.2 Most important symptoms and effects, both acute and delayed

Narcotic effects.

4.3 Indication of any immediate medical attention and special treatment needed

none

SECTION 5: Fire-fighting measures

5.1 Extinguishing media

Suitable extinguishing media

Water spray, BC-powder, Carbon dioxide (CO₂)

Unsuitable extinguishing media

Water jet

5.2 Special hazards arising from the substance or mixture

In case of insufficient ventilation and/or in use, may form flammable/explosive vapor-air mixture. Solvent vapors are heavier than air and may spread along floors. Places which are not ventilated, e.g. unventilated below ground level areas such as trenches, conduits and shafts, are particularly prone to the presence of flammable substances or mixtures.

E-Z WELD 210 ABS Medium Body Black

Version number: 2.0
Replaces version of: 2024-09-16 (1)

Revision: 2025-12-18

Hazardous combustion products

Nitrogen oxides (NOx), Carbon monoxide (CO), Carbon dioxide (CO₂)

Flash point

1.4 °F closed cup

5.3 Advice for firefighters

In case of fire and/or explosion do not breathe fumes. Coordinate firefighting measures to the fire surroundings. Do not allow firefighting water to enter drains or water courses. Collect contaminated firefighting water separately. Fight fire with normal precautions from a reasonable distance.

SECTION 6: Accidental release measures**6.1 Personal precautions, protective equipment and emergency procedures**

For non-emergency personnel

Remove persons to safety.

For emergency responders

Wear breathing apparatus if exposed to vapors/dust/aerosols/gases.

6.2 Environmental precautions

Keep away from drains, surface and ground water. Retain contaminated washing water and dispose of it.

6.3 Methods and material for containment and cleaning up

Advice on how to contain a spill

Covering of drains

Advice on how to clean up a spill

Wipe up with absorbent material (e.g. cloth, fleece). Collect spillage: sawdust, kieselgur (diatomite), sand, universal binder

Appropriate containment techniques

Use of adsorbent materials.

Other information relating to spills and releases

Place in appropriate containers for disposal. Ventilate affected area.

6.4 Reference to other sections

Hazardous combustion products: see section 5. Personal protective equipment: see section 8. Incompatible materials: see section 10. Disposal considerations: see section 13.

SECTION 7: Handling and storage**7.1 Precautions for safe handling**

Recommendations

- Measures to prevent fire as well as aerosol and dust generation

Use local and general ventilation. Avoidance of ignition sources. Keep away from sources of ignition - No smoking. Take precautionary measures against static discharge. Use only in well-ventilated areas. Due to danger of explosion, prevent leakage of vapours into cellars, flues and ditches. Ground/bond container and receiving equipment. Use explosion-proof electrical/ventilating/lighting/equipment. Use only non-sparking tools.

- Specific notes/details

Places which are not ventilated, e.g. unventilated below ground level areas such as trenches, conduits and shafts, are particularly prone to the presence of flammable substances or mixtures. Vapors are heavier than air, spread along floors and form explosive mixtures with air. Vapors may form explosive mixtures with air.

Advice on general occupational hygiene

Wash hands after use. Do not eat, drink and smoke in work areas. Remove contaminated clothing and protective equipment before entering eating areas. Never keep food or drink in the vicinity of chemicals. Never place chemicals in containers that are normally used for food or drink. Keep away from food, drink and animal feedingstuffs.

E-Z WELD 210 ABS Medium Body Black

Version number: 2.0
Replaces version of: 2024-09-16 (1)

Revision: 2025-12-18

7.2 Conditions for safe storage, including any incompatibilities

Managing of associated risks

- Explosive atmospheres

Keep container tightly closed and in a well-ventilated place. Use local and general ventilation. Keep cool. Protect from sunlight.

- Flammability hazards

Keep away from sources of ignition - No smoking. Keep away from heat, hot surfaces, sparks, open flames and other ignition sources. No smoking. Take precautionary measures against static discharge. Protect from sunlight.

- Ventilation requirements

Use local and general ventilation. Ground/bond container and receiving equipment.

- Packaging compatibilities

Only packagings which are approved (e.g. acc. to the Dangerous Goods Regulations) may be used.

7.3 Specific end use(s)

See section 16 for a general overview.

SECTION 8: Exposure controls/personal protection**8.1 Control parameters**

Occupational exposure limit values (Workplace Exposure Limits)										
Country	Name of substance	Identifier	TWA [ppm]	TWA [mg/m³]	STEL [ppm]	STEL [mg/m³]	Ceiling-C [ppm]	Ceiling-C [mg/m³]	Notation	Source
US	tetrahydrofuran (impurity - NIAS)	REL	200 (10 h)	590 (10 h)	250	735				NIOSH REL
US	tetrahydrofuran (impurity - NIAS)	PEL	200	590						29 CFR 1910.1000
US	tetrahydrofuran (impurity - NIAS)	TLV®	50	147	100	295			H	ACGIH® 2025
US	tetrahydrofuran (impurity - NIAS)	PEL (CA)	200	590	250	735				Cal/OSHA PEL
US	Carbon Black	PEL (CA)		3.5						Cal/OSHA PEL
US	Carbon Black	PEL		3.5						29 CFR 1910.1000
US	Carbon Black	REL		3.5 (10 h)					appx-A, appx-C	NIOSH REL
US	Carbon Black	TLV®		3					i	ACGIH® 2025
US	Carbon Black	REL		0.1 (10 h)					PAHs, appx-A, appx-C	NIOSH REL
US	acetone	PEL (CA)	500	1,200	750	1,780	3,000			Cal/OSHA PEL
US	acetone	REL	250 (10 h)	590 (10 h)						NIOSH REL
US	acetone	TLV®	250	594	500	1,187				ACGIH®

E-Z WELD 210 ABS Medium Body Black

Version number: 2.0
Replaces version of: 2024-09-16 (1)

Revision: 2025-12-18

Occupational exposure limit values (Workplace Exposure Limits)

Country	Name of substance	Identifier	TWA [ppm]	TWA [mg/m³]	STEL [ppm]	STEL [mg/m³]	Ceiling-C [ppm]	Ceiling-C [mg/m³]	Notation	Source
										2025
US	acetone	PEL	1,000	2,400						29 CFR 1910.1000
US	methyl ethyl ketone	REL	200 (10 h)	590 (10 h)	300	885				NIOSH REL
US	methyl ethyl ketone	PEL	200	590						29 CFR 1910.1000
US	methyl ethyl ketone	TLV®	75		150				H	ACGIH® 2025
US	methyl ethyl ketone	PEL (CA)	200	590	300	885				Cal/OSHA PEL

Notation

appx-A NIOSH Potential Occupational Carcinogen (Appendix A)

appx-C Appendix C - Supplementary Exposure Limits

Ceiling-C ceiling value is a limit value above which exposure should not occur

H absorbed through the skin

i inhalable fraction

PAHs as polycyclic aromatic hydrocarbons (PAHs)

STEL short-term exposure limit: a limit value above which exposure should not occur and which is related to a 15-minute period (unless otherwise specified)

TWA time-weighted average (long-term exposure limit): measured or calculated in relation to a reference period of 8 hours time-weighted average (unless otherwise specified)

Biological limit values

Country	Name of agent	Parameter	Notation	Identifier	Value	Source
US	tetrahydrofuran	tetrahydrofuran		BEI®	2 mg/l	ACGIH® 2025
US	acetone	acetone		BEI®	25 mg/l	ACGIH® 2025
US	methyl ethyl ketone	methyl ethyl ketone		BEI®	2 mg/l	ACGIH® 2025

Relevant DNELs of components

Name of substance	CAS No	Endpoint	Threshold level	Protection goal, route of exposure	Used in	Exposure time
methyl ethyl ketone	78-93-3	DNEL	600 mg/m³	human, inhalatory	worker (industry)	chronic - systemic effects
methyl ethyl ketone	78-93-3	DNEL	1,161 mg/kg bw/day	human, dermal	worker (industry)	chronic - systemic effects
acetone	67-64-1	DNEL	1,210 mg/m³	human, inhalatory	worker (industry)	chronic - systemic effects
acetone	67-64-1	DNEL	2,420 mg/m³	human, inhalatory	worker (industry)	acute - local effects
acetone	67-64-1	DNEL	186 mg/kg	human, dermal	worker (industry)	chronic - systemic ef-

E-Z WELD 210 ABS Medium Body Black

Version number: 2.0
Replaces version of: 2024-09-16 (1)

Revision: 2025-12-18

Relevant DNELs of components

Name of substance	CAS No	Endpoint	Threshold level	Protection goal, route of exposure	Used in	Exposure time
			bw/day			fects
tetrahydrofuran (impurity - NIAS)	109-99-9	DNEL	72.4 mg/m ³	human, inhalatory	worker (industry)	chronic - systemic effects
tetrahydrofuran (impurity - NIAS)	109-99-9	DNEL	96 mg/m ³	human, inhalatory	worker (industry)	acute - systemic effects
tetrahydrofuran (impurity - NIAS)	109-99-9	DNEL	150 mg/m ³	human, inhalatory	worker (industry)	chronic - local effects
tetrahydrofuran (impurity - NIAS)	109-99-9	DNEL	300 mg/m ³	human, inhalatory	worker (industry)	acute - local effects
tetrahydrofuran (impurity - NIAS)	109-99-9	DNEL	12.6 mg/kg bw/day	human, dermal	worker (industry)	chronic - systemic effects

Relevant PNECs of components

Name of substance	CAS No	Endpoint	Threshold level	Organism	Environmental compartment	Exposure time
methyl ethyl ketone	78-93-3	PNEC	55.8 mg/l	aquatic organisms	freshwater	short-term (single instance)
methyl ethyl ketone	78-93-3	PNEC	55.8 mg/l	aquatic organisms	marine water	short-term (single instance)
methyl ethyl ketone	78-93-3	PNEC	709 mg/l	aquatic organisms	sewage treatment plant (STP)	short-term (single instance)
methyl ethyl ketone	78-93-3	PNEC	284.7 mg/kg	aquatic organisms	freshwater sediment	short-term (single instance)
methyl ethyl ketone	78-93-3	PNEC	284.7 mg/kg	aquatic organisms	marine sediment	short-term (single instance)
methyl ethyl ketone	78-93-3	PNEC	22.5 mg/kg	terrestrial organisms	soil	short-term (single instance)
acetone	67-64-1	PNEC	10.6 mg/l	aquatic organisms	freshwater	short-term (single instance)
acetone	67-64-1	PNEC	1.06 mg/l	aquatic organisms	marine water	short-term (single instance)
acetone	67-64-1	PNEC	100 mg/l	aquatic organisms	sewage treatment plant (STP)	short-term (single instance)
acetone	67-64-1	PNEC	30.4 mg/kg	aquatic organisms	freshwater sediment	short-term (single instance)
acetone	67-64-1	PNEC	3.04 mg/kg	aquatic organisms	marine sediment	short-term (single instance)
acetone	67-64-1	PNEC	29.5 mg/kg	terrestrial organisms	soil	short-term (single instance)
tetrahydrofuran (impurity - NIAS)	109-99-9	PNEC	4.32 mg/l	aquatic organisms	freshwater	short-term (single instance)
tetrahydrofuran (impurity - NIAS)	109-99-9	PNEC	0.432 mg/l	aquatic organisms	marine water	short-term (single instance)

E-Z WELD 210 ABS Medium Body Black

Version number: 2.0
Replaces version of: 2024-09-16 (1)

Revision: 2025-12-18

Relevant PNECs of components

Name of substance	CAS No	Endpoint	Threshold level	Organism	Environmental compartment	Exposure time
tetrahydrofuran (impurity - NIAS)	109-99-9	PNEC	4.6 mg/l	aquatic organisms	sewage treatment plant (STP)	short-term (single instance)
tetrahydrofuran (impurity - NIAS)	109-99-9	PNEC	23.3 mg/kg	aquatic organisms	freshwater sediment	short-term (single instance)
tetrahydrofuran (impurity - NIAS)	109-99-9	PNEC	2.33 mg/kg	aquatic organisms	marine sediment	short-term (single instance)
tetrahydrofuran (impurity - NIAS)	109-99-9	PNEC	2.13 mg/kg	terrestrial organisms	soil	short-term (single instance)

8.2 Exposure controls

Appropriate engineering controls

General ventilation.

Individual protection measures (personal protective equipment)

Eye/face protection

Wear eye/face protection.

Skin protection

- Hand protection

Wear suitable gloves. Chemical protection gloves are suitable, which are tested according to EN 374. Check leak-tightness/impermeability prior to use. In the case of wanting to use the gloves again, clean them before taking off and air them well. For special purposes, it is recommended to check the resistance to chemicals of the protective gloves mentioned above together with the supplier of these gloves.

- Other protection measures

Take recovery periods for skin regeneration. Preventive skin protection (barrier creams/ointments) is recommended. Wash hands thoroughly after handling.

Respiratory protection

In case of inadequate ventilation wear respiratory protection.

Environmental exposure controls

Use appropriate container to avoid environmental contamination. Keep away from drains, surface and ground water.

SECTION 9: Physical and chemical properties

9.1 Information on basic physical and chemical properties

Physical state	liquid
Color	black - dark gray
Odor	characteristic
Melting point/freezing point	not determined
Boiling point or initial boiling point and boiling range	56.05 °C
Flammability	flammable liquid in accordance with GHS criteria

E-Z WELD 210 ABS Medium Body Black

Version number: 2.0
Replaces version of: 2024-09-16 (1)

Revision: 2025-12-18

Lower and upper explosion limit	not determined
Flash point	-17 °C
Auto-ignition temperature	465 °C (auto-ignition temperature (liquids and gases))
Decomposition temperature	not relevant
pH (value)	not determined
Solubility(ies)	not determined

Partition coefficient

Partition coefficient n-octanol/water (log value)	this information is not available
---	-----------------------------------

Vapor pressure	240 hPa at 20 °C
----------------	------------------

Density and/or relative density

Density	0.9 g/cm ³ at 73 °F
Relative vapour density	information on this property is not available

Particle characteristics	not relevant (liquid)
--------------------------	-----------------------

Other safety parameters

Flash point	1.4 °F
-------------	--------

9.2 Other information

Information with regard to physical hazard classes	there is no additional information
--	------------------------------------

Other safety characteristics

- VOC content	When applied as directed, per SCAQMD Rule 1168, Test Method 316A, VOC content is: <= 325 g/L
Temperature class (USA, acc. to NEC 500)	T1 (maximum permissible surface temperature on the equipment: 450°C)

SECTION 10: Stability and reactivity

10.1 Reactivity

Concerning incompatibility: see below "Conditions to avoid" and "Incompatible materials". The mixture contains reactive substance(s). Risk of ignition.

If heated:

E-Z WELD 210 ABS Medium Body Black

Version number: 2.0
Replaces version of: 2024-09-16 (1)

Revision: 2025-12-18

Risk of ignition

10.2 Chemical stability

See below "Conditions to avoid".

10.3 Possibility of hazardous reactions

No known hazardous reactions.

10.4 Conditions to avoid

Keep away from heat, hot surfaces, sparks, open flames and other ignition sources. No smoking.

Hints to prevent fire or explosion

Use explosion-proof electrical/ventilating/lighting/equipment. Use only non-sparking tools. Take precautionary measures against static discharge.

10.5 Incompatible materials

Oxidizers

10.6 Hazardous decomposition products

Reasonably anticipated hazardous decomposition products produced as a result of use, storage, spill and heating are not known. Hazardous combustion products: see section 5.

SECTION 11: Toxicological information**11.1 Information on toxicological effects**

Test data are not available for the complete mixture.

Classification procedure

The method for classification of the mixture is based on ingredients of the mixture (additivity formula).

Classification acc. to OSHA "Hazard Communication Standard" (29 CFR 1910.1200)

Acute toxicity

Shall not be classified as acutely toxic.

GHS of the United Nations, annex 4: May be harmful if swallowed.

Acute toxicity estimate (ATE) of components

Name of substance	CAS No	Exposure route	ATE
methyl ethyl ketone	78-93-3	oral	2,054 mg/kg
tetrahydrofuran (impurity - NIAS)	109-99-9	oral	500 mg/kg
tetrahydrofuran (impurity - NIAS)	109-99-9	dermal	>2,000 mg/kg

Skin corrosion/irritation

Shall not be classified as corrosive/irritant to skin.

Serious eye damage/eye irritation

Causes serious eye irritation.

Respiratory or skin sensitization

Shall not be classified as a respiratory or skin sensitizer.

Germ cell mutagenicity

Shall not be classified as germ cell mutagenic.

Carcinogenicity

Suspected of causing cancer.

E-Z WELD 210 ABS Medium Body Black

Version number: 2.0
Replaces version of: 2024-09-16 (1)

Revision: 2025-12-18

IARC Monographs on the Evaluation of Carcinogenic Risks to Humans

Name of substance	CAS No	Classification	Number
Carbon Black	1333-86-4	2B	
tetrahydrofuran (impurity - NIAS)	109-99-9	2B	

Legend

2B Possibly carcinogenic to humans

National Toxicology Program (United States): Report on Carcinogens

Name of substance	CAS No	Classification	Number
Carbon Black	1333-86-4	Known to be human carcinogens	1st Report on Carcinogens

Reproductive toxicity

Shall not be classified as a reproductive toxicant.

Specific target organ toxicity - single exposure

May cause drowsiness or dizziness.

Specific target organ toxicity - repeated exposure

Shall not be classified as a specific target organ toxicant (repeated exposure).

Aspiration hazard

Shall not be classified as presenting an aspiration hazard.

Other information

Repeated exposure may cause skin dryness or cracking.

SECTION 12: Ecological information

12.1 Toxicity

Shall not be classified as hazardous to the aquatic environment.

12.2 Persistence and degradability

Data are not available.

12.3 Bioaccumulative potential

Data are not available.

12.4 Mobility in soil

Data are not available.

12.5 Results of PBT and vPvB assessment

Does not contain a PBT-/vPvB-substance at a concentration of $\geq 0.1\%$.

12.6 Endocrine disrupting properties

Does not contain an endocrine disruptor (ED) in a concentration of $\geq 0.1\%$.

12.7 Other adverse effects

Data are not available.

E-Z WELD 210 ABS Medium Body Black

Version number: 2.0
Replaces version of: 2024-09-16 (1)

Revision: 2025-12-18

SECTION 13: Disposal considerations**13.1 Waste treatment methods**

Waste treatment-relevant information

Solvent reclamation/regeneration.

Sewage disposal-relevant information

Do not empty into drains. Avoid release to the environment. Refer to special instructions/safety data sheets.

Waste treatment of containers/packages

Only packagings which are approved (e.g. acc. to DOT) may be used. Completely emptied packages can be recycled. Handle contaminated packages in the same way as the substance itself.

Remarks

Please consider the relevant national or regional provisions. Waste shall be separated into the categories that can be handled separately by the local or national waste management facilities.

SECTION 14: Transport information**14.1 UN number**

DOT UN 1133

IMDG-Code UN 1133

ICAO-TI UN 1133

14.2 UN proper shipping name

DOT Adhesives

IMDG-Code ADHESIVES

ICAO-TI Adhesives

14.3 Transport hazard class(es)

DOT 3

IMDG-Code 3

ICAO-TI 3

14.4 Packing group

DOT II

IMDG-Code II

ICAO-TI II

14.5 Environmental hazards

non-environmentally hazardous acc. to the dangerous goods regulations

14.6 Special precautions for user

There is no additional information.

14.7 Transport in bulk according to IMO instruments

The cargo is not intended to be carried in bulk.

Information for each of the UN Model Regulations**Transport of dangerous goods by road or rail (49 CFR US DOT) - Additional information**

E-Z WELD 210 ABS Medium Body Black

Version number: 2.0
Replaces version of: 2024-09-16 (1)

Revision: 2025-12-18

Particulars in the shipper's declaration UN1133, Adhesives, 3, II
Reportable quantity (RQ) 11,655 lbs (5,291 kg) (methyl ethyl ketone) (acetone)
Danger label(s) 3



Special provisions (SP) 149, B52, IB2, T4, TP1, TP8
ERG No 128

International Maritime Dangerous Goods Code (IMDG) - Additional information

Marine pollutant - (not hazardous to the aquatic environment)
Danger label(s) 3



Special provisions (SP) -
Excepted quantities (EQ) E2
Limited quantities (LQ) 5 L
EmS F-E, S-D
Stowage category B

International Civil Aviation Organization (ICAO-IATA/DGR) - Additional information

Danger label(s) 3



Special provisions (SP) A3
Excepted quantities (EQ) E2
Limited quantities (LQ) 1 L

SECTION 15: Regulatory information

15.1 Safety, health and environmental regulations specific for the product in question

National regulations (United States)

Toxic Substance Control Act (TSCA) all ingredients are listed as ACTIVE

Comprehensive Environmental Response, Compensation, and Liability Act (CERCLA)

- List of Hazardous Substances and Reportable Quantities (CERCLA section 102a) (40 CFR 302.4)

Name of substance	CAS No	Remarks	Statutory code	Final RQ pounds (Kg)
methyl ethyl ketone	78-93-3		4	5000 (2270)
acetone	67-64-1		4	5000 (2270)
tetrahydrofuran (impurity - NIAS)	109-99-9		4	1000 (454)

E-Z WELD 210 ABS Medium Body Black

Version number: 2.0
Replaces version of: 2024-09-16 (1)

Revision: 2025-12-18

Legend

4 "4" indicates that the source is section 3001 of the Resource Conservation and Recovery Act (RCRA)

Right to Know Hazardous Substance List**- Cleaning Product Right to Know Act Substance List (CA-RTK)**

Name of substance	CAS No	Functionality	Authoritative Lists
methyl ethyl ketone	78-93-3		ATSDR Neurotoxicants CA TACs OEHH RELs
acetone	67-64-1		ATSDR Neurotoxicants
tetrahydrofuran (impurity - NIAS)	109-99-9		IARC Carcinogens - 2B IRIS Neurotoxicants Prop 65
Carbon Black	1333-86-4		IARC Carcinogens - 2B Prop 65

- Toxic or Hazardous Substance List (MA-TURA)

Name of substance	CAS No	DEP CODE	PBT / HHS / LHS	PBT / HHS Threshold	De Minimis Concentration Threshold
methyl ethyl ketone	78-93-3				1.0 %
acetone	67-64-1				1.0 %
tetrahydrofuran (impurity - NIAS)	109-99-9				1.0 %

- Hazardous Substances List (MN-ERTK)

Name of substance	CAS No	References	Remarks
methyl ethyl ketone	78-93-3	A, N, O	
acetone	67-64-1	A, N, O	
Carbon Black	1333-86-4	A, N, O, R, *	

Legend

- * Substances which are regulated by OSHA as carcinogens; have been categorized by the ACGIH as either "human carcinogens" or "suspect of carcinogenic potential for man"; have been evaluated by the International Agency for Research on Cancer (IARC) and found to be carcinogens or potential carcinogens; or have been listed as a carcinogen or potential carcinogen in the Annual Report on Carcinogens published by the National Toxicology Program (NTP).
- A American Conference of Governmental Industrial Hygienists (ACGIH), "Threshold Limit Values for Chemical Substances and Physical Agents and Biological Exposure Indices for 1992-93", available from ACGIH
- N National Institute for Occupational Safety and Health (NIOSH), "Recommendations for Occupational Safety and Health Standards," August 1988, available from NIOSH, Publications Dissemination Office, Division of Standards Development and Technology Transfer
- O Occupational Safety and Health Administration (OSHA), Safety and Health Standards, Code of Federal Regulations, title 29, part 1910, subpart Z, "Toxic and Hazardous Substances, 1990." General information: Minnesota Department of Labor and Industry, Occupational Safety and Health Division
- R International Agency for Research on Cancer (IARC) Monographs on the Evaluation of the Carcinogenic Risks to Humans; Overall Evaluations of Carcinogenicity: An Updating of IARC Monographs Volumes 1 to 42, Supplement 7 (1987). Available from: WHO Publications Centre USA

E-Z WELD 210 ABS Medium Body Black

Version number: 2.0
Replaces version of: 2024-09-16 (1)

Revision: 2025-12-18

- Hazardous Substance List (NJ-RTK)

Name of substance	CAS No	Remarks	Classifications
methyl ethyl ketone	78-93-3		F3
acetone	67-64-1		F3
Carbon Black	1333-86-4		CA
tetrahydrofuran (impurity - NIAS)	109-99-9		F3 R1

Legend

CA Carcinogenic
F3 Flammable - Third Degree
R1 Reactive - First Degree

- Hazardous Substance List (Chapter 323) (PA-RTK)

Name of substance	CAS No	Classification
methyl ethyl ketone	78-93-3	E
acetone	67-64-1	E
Carbon Black		S
tetrahydrofuran (impurity - NIAS)	109-99-9	E

Legend

E Environmental hazard
S Special hazardous substance

- Hazardous Substance List (RI-RTK)

Name of substance	CAS No	References
methyl ethyl ketone	78-93-3	T, F
acetone	67-64-1	T, F
Carbon Black	1333-86-4	T
tetrahydrofuran (impurity - NIAS)	109-99-9	T, F
tetrahydrofuran (impurity - NIAS)	109-99-9	T, F
tetrahydrofuran (impurity - NIAS)	109-99-9	T, F

Legend

F Flammability (NFPA®)
T Toxicity (ACGIH®)

California Environmental Protection Agency (Cal/EPA): Proposition 65 - Safe Drinking Water and Toxic Enforcement Act of 1987

Proposition 65 List of chemicals			
Name acc. to inventory	CAS No	Remarks	Type of the toxicity
styrene	100-42-5		cancer

E-Z WELD 210 ABS Medium Body Black

Version number: 2.0
Replaces version of: 2024-09-16 (1)

Revision: 2025-12-18

Proposition 65 List of chemicals

Name acc. to inventory	CAS No	Remarks	Type of the toxicity
1,3-butadiene	106-99-0		cancer
1,3-butadiene	106-99-0		developmental, female, male
acrylonitrile	107-13-1		cancer
tetrahydrofuran	109-99-9		cancer
vinyl chloride	75-01-4		cancer

Industry or sector specific available guidance(s)

The IARC/GHS carcinogen classification for carbon black is only in its respirable particulate form. Since this product binds carbon black in a liquid matrix, the GHS carcinogen classification and subsequent California Proposition 65 notation is not applicable.

NPCA-HMIS® III

Hazardous Materials Identification System. American Coatings Association.

Category	Rating	Description
Chronic	*	chronic (long-term) health effects may result from repeated overexposure
Health	2	temporary or minor injury may occur
Flammability	3	material that can be ignited under almost all ambient temperature conditions
Physical hazard	0	material that is normally stable, even under fire conditions, and will not react with water, polymerize, decompose, condense, or self-react. Non-explosive
Personal protection	-	

NFPA® 704

National Fire Protection Association: Standard System for the Identification of the Hazards of Materials for Emergency Response (United States).

Category	Degree of hazard	Description
Flammability	3	material that can be ignited under almost all ambient temperature conditions
Health	0	material that, under emergency conditions, would offer no hazard beyond that of ordinary combustible material
Instability	0	material that is normally stable, even under fire conditions
Special hazard		

National inventories

Country	Inventory	Status
AU	AIIC	all ingredients are listed
CA	DSL	all ingredients are listed
CN	IECSC	all ingredients are listed
EU	ECSI	all ingredients are listed

E-Z WELD 210 ABS Medium Body Black

Version number: 2.0
Replaces version of: 2024-09-16 (1)

Revision: 2025-12-18

Country	Inventory	Status
JP	CSCL-ENCS	not all ingredients are listed
KR	KECI	all ingredients are listed
MX	INSQ	all ingredients are listed
NZ	NZIoC	all ingredients are listed
PH	PICCS	all ingredients are listed
TW	TCSI	all ingredients are listed
US	TSCA	all ingredients are listed (ACTIVE)
EU	REACH Reg.	not all ingredients are listed
TR	CICR	not all ingredients are listed

Legend

AIIC	Australian Inventory of Industrial Chemicals
CICR	Chemical Inventory and Control Regulation
CSCL-ENCS	List of Existing and New Chemical Substances (CSCL-ENCS)
DSL	Domestic Substances List (DSL)
ECSI	EC Substance Inventory (EINECS, ELINCS, NLP)
IECSC	Inventory of Existing Chemical Substances Produced or Imported in China
INSQ	National Inventory of Chemical Substances
KECI	Korea Existing Chemicals Inventory
NZIoC	New Zealand Inventory of Chemicals
PICCS	Philippine Inventory of Chemicals and Chemical Substances (PICCS)
REACH Reg.	REACH registered substances
TCSI	Taiwan Chemical Substance Inventory
TSCA	Toxic Substance Control Act

15.2 Chemical Safety Assessment

Chemical safety assessments for substances in this mixture were not carried out.

SECTION 16: Other information, including date of preparation or last revision**Indication of changes (revised safety data sheet)**

Section	Former entry (text/value)	Actual entry (text/value)	Safety-relevant
2.1		Classification acc. to OSHA "Hazard Communication Standard" (29 CFR 1910.1200): change in the listing (table)	yes
2.2		- Pictograms: change in the listing (table)	yes
2.2		- Hazard statements: change in the listing (table)	yes
2.2		- Precautionary statements: change in the listing (table)	yes
2.2	- Hazardous ingredients for labelling: methyl ethyl ketone, acetone	- Hazardous ingredients for labelling: tetrahydrofuran (impurity - NIAS), methyl ethyl ketone, Carbon Black, acetone	yes
3.2		Description of the mixture:	yes

E-Z WELD 210 ABS Medium Body Black

Version number: 2.0
Replaces version of: 2024-09-16 (1)

Revision: 2025-12-18

Section	Former entry (text/value)	Actual entry (text/value)	Safety-relevant
		change in the listing (table)	
8.1		Occupational exposure limit values (Workplace Exposure Limits): change in the listing (table)	yes
8.1		Biological limit values: change in the listing (table)	yes
8.1		Relevant DNELs of components: change in the listing (table)	yes
8.1		Relevant PNECs of components: change in the listing (table)	yes
9.1	Appearance		yes
9.1	Flammability (solid, gas): not relevant, (fluid)	Flammability: flammable liquid in accordance with GHS criteria	yes
9.1		Lower and upper explosion limit: not determined	yes
9.1		Decomposition temperature: not relevant	yes
9.1		Density and/or relative density	yes
9.1		Relative vapour density: information on this property is not available	yes
9.1	Evaporation rate: not determined		yes
9.1	Vapor density: this information is not available		yes
9.1	Viscosity		yes
9.1	Dynamic viscosity: 1,400 – 1,800 cP at 73 °F		yes
9.1	Explosive properties: none		yes
9.1	Oxidizing properties: none		yes
9.2		Information with regard to physical hazard classes: there is no additional information	yes
9.2		Other safety characteristics	yes
11.1		Acute toxicity estimate (ATE) of components: change in the listing (table)	yes
11.1	Carcinogenicity: Shall not be classified as carcinogenic.	Carcinogenicity: Suspected of causing cancer.	yes
11.1		IARC Monographs on the Evaluation of Carcinogenic Risks to Humans: change in the listing (table)	yes
12.5	Results of PBT and vPvB assessment: According to the results of its assessment, this substance is not a PBT or a vPvB. Does not contain a PBT-/vPvB-substance at a concentration of $\geq 0.1\%$.	Results of PBT and vPvB assessment: Does not contain a PBT-/vPvB-substance at a concentration of $\geq 0.1\%$.	yes
15.1		List of Hazardous Substances and Reportable	yes

E-Z WELD 210 ABS Medium Body Black

Version number: 2.0
Replaces version of: 2024-09-16 (1)

Revision: 2025-12-18

Section	Former entry (text/value)	Actual entry (text/value)	Safety-relevant
		Quantities (CERCLA section 102a) (40 CFR 302.4): change in the listing (table)	
15.1		Cleaning Product Right to Know Act Substance List (CA-RTK): change in the listing (table)	yes
15.1		Toxic or Hazardous Substance List (MA-TURA): change in the listing (table)	yes
15.1		Hazardous Substance List (NJ-RTK): change in the listing (table)	yes
15.1		Hazardous Substance List (Chapter 323) (PA-RTK): change in the listing (table)	yes
15.1		Hazardous Substance List (RI-RTK): change in the listing (table)	yes
15.1		California Environmental Protection Agency (Cal/EPA): Proposition 65 - Safe Drinking Water and Toxic Enforcement Act of 1987	yes
15.1		Proposition 65 List of chemicals: change in the listing (table)	yes
15.1		National inventories: change in the listing (table)	yes

Abbreviations and acronyms

Abbr.	Descriptions of used abbreviations
29 CFR 1910.1000	29 CFR 1910.1000, Tables Z-1, Z-2, Z-3 - Occupational Safety and Health Standards: Toxic and Hazardous Substances (permissible exposure limits)
49 CFR US DOT	49 CFR U.S. Department of Transportation
ACGIH®	American Conference of Governmental Industrial Hygienists
ACGIH® 2025	From ACGIH®, 2025 TLVs® and BEIs® Book. Copyright 2025. Reprinted with permission. Information on the proper use of the TLVs® and BEIs®: http://www.acgih.org/tlv-bei-guidelines/policies-procedures-presentations/tlv-bei-position-statement
ATE	Acute Toxicity Estimate
Cal/OSHA PEL	California Division of Occupational Safety and Health (Cal/OSHA): Permissible Exposure Limits (PELs)
CAS	Chemical Abstracts Service (service that maintains the most comprehensive list of chemical substances)
Ceiling-C	Ceiling value
DEP CODE	Department of Environmental Protection Code
DGR	Dangerous Goods Regulations (see IATA/DGR)
DNEL	Derived No-Effect Level
DOT	Department of Transportation (USA)
ED	Endocrine disruptor
EINECS	European Inventory of Existing Commercial Chemical Substances
ELINCS	European List of Notified Chemical Substances
EmS	Emergency Schedule

E-Z WELD 210 ABS Medium Body Black

Version number: 2.0
Replaces version of: 2024-09-16 (1)

Revision: 2025-12-18

Abbr.	Descriptions of used abbreviations
ERG No	Emergency Response Guidebook - Number
GHS	"Globally Harmonized System of Classification and Labelling of Chemicals" developed by the United Nations
HHS	Higher hazard substance
IARC	International Agency for Research on Cancer
IATA	International Air Transport Association
IATA/DGR	Dangerous Goods Regulations (DGR) for the air transport (IATA)
ICAO	International Civil Aviation Organization
ICAO-TI	Technical instructions for the safe transport of dangerous goods by air
IMDG	International Maritime Dangerous Goods Code
IMDG-Code	International Maritime Dangerous Goods Code
LHS	Lower hazard substance
NFPA®	National Fire Protection Association (United States)
NIOSH REL	National Institute for Occupational Safety and Health (NIOSH): Recommended Exposure Limits (RELs)
NLP	No-Longer Polymer
NPCA-HMIS® III	National Paint and Coatings Association: Hazardous Materials Identification System - HMIS® III, Third Edition
OSHA	Occupational Safety and Health Administration (United States)
PBT	Persistent, Bioaccumulative and Toxic
PEL	Permissible exposure limit
PNEC	Predicted No-Effect Concentration
ppm	Parts per million
RTECS	Registry of Toxic Effects of Chemical Substances (database of NIOSH with toxicological information)
STEL	Short-term exposure limit
TLV®	Threshold Limit Values
TWA	Time-weighted average
VOC	Volatile Organic Compounds
vPvB	Very Persistent and very Bioaccumulative

Key literature references and sources for data

OSHA Hazard Communication Standard (HCS), 29 CFR 1910.1200.

Transport of dangerous goods by road or rail (49 CFR US DOT). International Maritime Dangerous Goods Code (IMDG).

Dangerous Goods Regulations (DGR) for the air transport (IATA).

Classification procedure

Physical and chemical properties: The classification is based on tested mixture.

Health hazards, Environmental hazards: The method for classification of the mixture is based on ingredients of the mixture (additivity formula).

Disclaimer

This information is based upon the present state of our knowledge. This SDS has been compiled and is solely intended for this product.