


Address: 128 City Road, London, EC1V 2NX

Website: www.wuduwash.com

Tel: 0333 255 9775

WuduWash Anti Ligature Wheelchair Unit





Product Description

- Wheelchair-accessible layout with clear open front for user approach
- · Front access panel provided for installation and maintenance
- Supplied anti-ligature tap s push-button
- · Fully welded stainless steel construction for durability and hygiene
- Smooth, easy-clean surface resistant to corrosion
- Wall-fixing via keyhole slots and floor fixing holes

- **Product Code:** WW-W1
- **Lead Time:** Lead time: 3–5 working days **Material:** 1.2mm & 2mm Stainless Steel 304

- Product Name WuduWash Anti Ligature Wheelchair Unit Product Code WW-W1
- Product Type Wheelchair accessible Wudu foot wash bath Construction Material High-quality stainless steel
- Design Inclusive design with open-front layout providing clear wheelchair access. The unit measures 800mm in width and is suitable for single-user installation. Finish Smooth, easy-clean stainless steel surface hygienic and corrosion-resistant

 Mounting Type, Well mounted, with keybale slots and providing helps into the floor legality. Described from the formula of the providing helps into the floor legality.

 Mounting Type, Well mounted, with keybale slots and providing helps into the floor legality. Democrable front access namely for the floor legality in the floor legality in the floor legality in the floor legality.

 Mounting Type, Well mounted and the floor legality in the floor
- Mounting Type Wall mounted with keyhole slots and pre-drilled fixing holes into the floor Installation Details Removable front access panel for
 convenient installation and maintenance access Tap Type Supplied with anti-ligature tap & push-button for safety and ease of operation
- Waste Outlet Integrated front waste outlet 45mm diameter
- Usage Designed for performing ritual ablution (Wudu) in mosques, schools, universities, and prayer areas requiring inclusive access
- Hygiene Features Fully welded stainless-steel construction with smooth, easy-clean finish to maintain hygiene standards and resist corrosion User Capacity -Single user
- Dimensions Width 800mm (see product page for detailed technical drawing)
- Lead Time Typically 3–5 working days
- Additional Notes Ideal for accessible prayer areas and communal wash facilities. Designed for safety, inclusivity, and long-term performance.