

• YOUR
• SMART
• ENERGY



Preliminary Datasheet

SMILE-M5-S

RESIDENTIAL SERIES

POWER

5 kW Hybrid Inverter
Single Phase

CAPACITY

5 ~ 30 kWh with
5 kWh Battery Module



Quick Setup with Stackable Design

Fast-Suppression Aerosol Fire Defense

Boost Profits with 200% PV Oversizing

Expert in All-in-One System



SMILE-M5-S

Model	SMILE-M5-S
System Specification	
Nominal Output Power	5000 W
Max. Battery Capacity	5 ~ 30 kWh (100% DoD)
Battery Chemistry	LFP (LiFePO ₄)
Warranty	10 Years Warranty
Inverter Technical Specification	
Model	SMILE-M5-S-INV
Inverter Type	Hybrid Inverter
Max. PV Input Current (per MPPT)	16A
Max. PV Input Power	10000W
MPPT Number / Max. Input Strings Number per MPPT	2/1
MPPT Voltage Range	100 ~ 550V
Max. PV Short-Circuit Current (per MPPT)	25A
Max. Charging / Discharging Current	100A
Max. Charging / Discharging Power	5000 W
Rated Frequency	50 / 60 Hz
Rated Voltage	230 V
Phase	Single Phase
Backup	UPS
Communication	Ethernet / WiFi
Dimensions (W*H*D)	620 * 240 * 412.5 mm
Weight	19.5 kg
Ingress Protection(IP) Rating	IP 65
Safety	IEC62109-1/-2, IEC62477
EMC	IEC 61000-6-1/3, IEC61000-302/3
Grid Regulation	AS / NZ4777.2
Battery Technical Specification	
Module Model	SMILE-M-BAT-5P
Nominal Capacity	5 kWh
Modules Connection	1 ~ 6 in parallel
Max. Charging/Discharging Current	100 / 100A
Operating Temperature Range	0 ~ 50 °C(Charge); -10 ~ 50 °C(Discharge)
IP Protection	IP65
Dimensions (W*H*D)	620 * 390 * 240 mm
Weight	49.5kg

