

AL-86

Version number: 1.0

Date of compilation: 2025-02-06

1 Identification

1.1 Product identifier

Trade name **AL-86**
Alternative name(s) Drying Agent

1.2 Relevant identified uses of the substance or mixture and uses advised against

Relevant identified uses polish

1.3 Details of the supplier of the safety data sheet

Transchem Inc.
1225 Franklin Blvd.
Cambridge Ontario N1R 7E5
Canada

Telephone: +1.800.265.9100
e-mail: info@transchem.com
Website: https://transchem.com/

e-mail (competent person) kberzitis@transchem.com (Karl Berzitis)

1.4 Emergency telephone number

Emergency information service INFOTRAC 1-800-535-5053, 24 Hours

2 Hazard identification

2.1 Classification of the substance or mixture

Classification acc. to GHS

| Section | Hazard class | Category | Hazard class and category | Hazard statement |
|---------|-----------------------------------|----------|---------------------------|------------------|
| 2.6 | flammable liquid | 4 | Flam. Liq. 4 | H227 |
| 3.2 | skin corrosion/irritation | 2 | Skin Irrit. 2 | H315 |
| 3.3 | serious eye damage/eye irritation | 1 | Eye Dam. 1 | H318 |

For full text of abbreviations: see SECTION 16.

The most important adverse physicochemical, human health and environmental effects

The product is combustible and can be ignited by potential ignition sources.

2.2 Label elements

Labeling

- Signal word danger

- Pictograms

GHS05



- Hazard statements

H227 Combustible liquid.
H315 Causes skin irritation.
H318 Causes serious eye damage.

AL-86

Version number: 1.0

Date of compilation: 2025-02-06

- Precautionary statements

| | |
|----------------|--|
| P210 | Keep away from heat, hot surfaces, sparks, open flames and other ignition sources. No smoking. |
| P264 | Wash hands and face thoroughly after handling. |
| P280 | Wear eye protection or face protection. |
| P302+P352 | IF ON SKIN: Wash with plenty of water. |
| P305+P351+P338 | IF IN EYES: Rinse cautiously with water for several minutes. Remove contact lenses, if present and easy to do. Continue rinsing. |
| P310 | Immediately call a POISON CENTER or doctor. |
| P362+P364 | Take off contaminated clothing and wash it before reuse. |
| P370+P378 | In case of fire: Use sand, carbon dioxide or powder extinguisher to extinguish. |
| P403 | Store in a well-ventilated place. |
| P501 | Dispose of contents and container in accordance with local, regional, national and international regulations. |

3.2 Other hazards

This material is combustible, but will not ignite readily.

Endocrine disrupting properties

Does not contain an endocrine disruptor (ED) in a concentration of $\geq 0.1\%$.

3 Composition/ Information on ingredients

3.1 Substances

Not relevant (mixture)

3.2 Mixtures

Description of the mixture

| Name of substance | Other names or synonyms | Identifier | Wt% | Classification acc. to GHS |
|--|--|-------------------|----------|---|
| Distillates (petroleum), straight-run middle | Mineral seal oil | CAS No 64741-44-2 | 5 – < 10 | Flam. Liq. 3 / H226 Acute Tox. 4 / H332 Asp. Tox. 1 / H304 |
| Quaternary ammonium compounds, dicoco alkyl dimethyl, chlorides | Di-Alkyl Quaternary Ammonium Chloride | CAS No 61789-77-3 | 5 – < 10 | Acute Tox. 4 / H302 Skin Corr. 1C / H314 Eye Dam. 1 / H318 |
| 2-butoxyethanol | ethyleneglycol monobutyl ether butyl cellosolve | CAS No 111-76-2 | 1 – < 5 | Flam. Liq. 4 / H227 Acute Tox. 4 / H302 Acute Tox. 3 / H311 Acute Tox. 3 / H331 Skin Irrit. 2 / H315 Eye Irrit. 2 / H319 |
| Amines, C10-16-alkyldimethyl, N-oxides | Lauryl Dimethyl Amine Oxide | CAS No 70592-80-2 | 1 – < 5 | Acute Tox. 4 / H302 Skin Irrit. 2 / H315 Eye Dam. 1 / H318 |
| 1-Propanaminium, 3-amino-N-(carboxymethyl)-N,N-dimethyl-, N-coco acyl derivs., hydroxides, inner salts | Cocamidopropyl Betaine | CAS No 61789-40-0 | 1 – < 5 | Skin Irrit. 2 / H315 Eye Irrit. 2 / H319 |
| propan-2-ol | isopropyl alcohol isopropanol Propan-2-ol | CAS No 67-63-0 | 1 – < 5 | Flam. Liq. 2 / H225 Eye Irrit. 2 / H319 STOT SE 3 / H336 |
| Amines, C14-18 and C16-18-unsatd. alkyl, ethoxylated | Ethoxylated Fatty Acid Amine | CAS No 68155-39-5 | 1 – < 5 | Acute Tox. 3 / H301 Skin Irrit. 2 / H315 Eye Dam. 1 / H318 |

AL-86

Version number: 1.0

Date of compilation: 2025-02-06

Remarks

The specific chemical identity and/or exact percentage of composition (concentration) has been withheld as a trade secret. For full text of abbreviations: see SECTION 16.

4 First-aid measures

4.1 Description of first-aid measures

General notes

Do not leave affected person unattended. Remove victim out of the danger area. Keep affected person warm, still and covered. Take off immediately all contaminated clothing. In all cases of doubt, or when symptoms persist, seek medical advice. In case of unconsciousness place person in the recovery position. Never give anything by mouth.

Following inhalation

If breathing is irregular or stopped, immediately seek medical assistance and start first aid actions. In case of respiratory tract irritation, consult a physician. Provide fresh air.

Following skin contact

Wash with plenty of soap and water.

Following eye contact

Remove contact lenses, if present and easy to do. Continue rinsing. Irrigate copiously with clean, fresh water for at least 10 minutes, holding the eyelids apart.

Following ingestion

Rinse mouth with water (only if the person is conscious). Do NOT induce vomiting.

4.2 Most important symptoms and effects, both acute and delayed

Impairment of vision. Production of tissue damage in the eye. Conjunctivitis (pink eye). Localized redness, edema, pruritis and/or pain.

4.3 Indication of any immediate medical attention and special treatment needed

Rinse immediately carefully and thoroughly with eye shower or water. Treat symptomatically.

5 Fire-fighting measures

5.1 Extinguishing media

Suitable extinguishing media

Water spray, BC-powder, Carbon dioxide (CO₂)

Unsuitable extinguishing media

Water jet

5.2 Special hazards arising from the substance or mixture

In case of insufficient ventilation and/or in use, may form flammable/explosive vapor-air mixture. Solvent vapors are heavier than air and may spread along floors. Places which are not ventilated, e.g. unventilated below ground level areas such as trenches, conduits and shafts, are particularly prone to the presence of flammable substances or mixtures.

Hazardous combustion products

Nitrogen oxides (NO_x), Carbon monoxide (CO), Carbon dioxide (CO₂)

5.3 Advice for firefighters

In case of fire and/or explosion do not breathe fumes. Coordinate firefighting measures to the fire surroundings. Do not allow firefighting water to enter drains or water courses. Collect contaminated firefighting water separately. Fight fire with normal precautions from a reasonable distance.

Special protective equipment for firefighters

Chemical protective clothing, Eye and face protection, Wear self-contained breathing apparatus

AL-86

Version number: 1.0

Date of compilation: 2025-02-06

6 Accidental release measures

6.1 Personal precautions, protective equipment and emergency procedures

For non-emergency personnel

Remove persons to safety. Prevent skin contact. Wearing of suitable protective equipment (including personal protective equipment referred to under Section 8 of the safety data sheet) to prevent any contamination of skin, eyes and personal clothing.

For emergency responders

Wear breathing apparatus if exposed to vapors/dust/aerosols/gases.

6.2 Environmental precautions

Keep away from drains, surface and ground water. Retain contaminated washing water and dispose of it.

6.3 Methods and material for containment and cleaning up

Advice on how to contain a spill

Eliminate all ignition sources if safe to do so, Set up barriers, Covering of drains

Advice on how to clean up a spill

Wipe up with absorbent material (e.g. cloth, fleece). Collect spillage: sawdust, kieselgur (diatomite), sand, universal binder

Appropriate containment techniques

Use of adsorbent materials.

Other information relating to spills and releases

Place in appropriate containers for disposal. Ventilate affected area.

6.4 Reference to other sections

Hazardous combustion products: see section 5. Personal protective equipment: see section 8. Incompatible materials: see section 10. Disposal considerations: see section 13.

7 Handling and storage

7.1 Precautions for safe handling

Recommendations

- Measures to prevent fire as well as aerosol and dust generation

Use local and general ventilation. Avoidance of ignition sources. Keep away from sources of ignition - No smoking. Take precautionary measures against static discharge. Use only in well-ventilated areas. Due to danger of explosion, prevent leakage of vapours into cellars, flues and ditches. Ground/bond container and receiving equipment. Use explosion-proof electrical/ventilating/lighting/equipment. Use only non-sparking tools.

- Specific notes/details

Places which are not ventilated, e.g. unventilated below ground level areas such as trenches, conduits and shafts, are particularly prone to the presence of flammable substances or mixtures. Vapors are heavier than air, spread along floors and form explosive mixtures with air. Vapors may form explosive mixtures with air.

Advice on general occupational hygiene

Wash hands after use. Do not eat, drink and smoke in work areas. Remove contaminated clothing and protective equipment before entering eating areas. Never keep food or drink in the vicinity of chemicals. Never place chemicals in containers that are normally used for food or drink. Keep away from food, drink and animal feedingstuffs.

7.2 Conditions for safe storage, including any incompatibilities

- Explosive atmospheres

Keep container tightly closed and in a well-ventilated place. Use local and general ventilation. Keep cool. Protect from sunlight.

- Flammability hazards

Keep away from sources of ignition - No smoking. Keep away from heat, hot surfaces, sparks, open flames and other ignition sources. No smoking. Take precautionary measures against static discharge. Protect from sunlight.

- Incompatible substances or mixtures

Oxidizers

AL-86

Version number: 1.0

Date of compilation: 2025-02-06

- General rule

Keep out of reach of children. Store in a dry place. Store in a closed container. Store in a well-ventilated place. Keep away from incompatible materials.

- Ventilation requirements

Use local and general ventilation. Ground/bond container and receiving equipment.

7.3 Specific end use(s)

See section 16 for a general overview.

8 Exposure controls/ Personal protection

8.1 Control parameters

| Occupational exposure limit values (Workplace Exposure Limits) | | | | | | | | | | | |
|--|---|----------|--------------|-----------|-------------|------------|--------------|-----------------|-------------------|----------|-----------------|
| Country | Name of agent | CAS No | Identifier | TWA [ppm] | TWA [mg/m³] | STEL [ppm] | STEL [mg/m³] | Ceiling-C [ppm] | Ceiling-C [mg/m³] | Notation | Source |
| CA | 2-butoxyethanol | 111-76-2 | PEV/VE A | 20 | | | | | | | Regulation OHS |
| CA | 2-butoxyethanol (EGBE) | 111-76-2 | OEL (BC) | 20 | | | | | | | "BC Regulation" |
| CA | 2-butoxyethanol (EGBE) | 111-76-2 | OEL (ON-MoL) | 20 | | | | | | | MoL |
| CA | 2-butoxyethanol (ethylene glycol monobutyl ether) | 111-76-2 | OEL (AB) | 20 | 97 | | | | | | OHS Code |
| CA | 2-propanol | 67-63-0 | OEL (ON-MoL) | 200 | | 400 | | | | | MoL |
| CA | 2-propanol (isopropyl alcohol) (propan-2-ol) | 67-63-0 | OEL (AB) | 200 | 492 | 400 | 984 | | | | OHS Code |
| CA | isopropanol (isopropyl alcohol) (2-propanol) | 67-63-0 | OEL (BC) | 200 | | 400 | | | | | "BC Regulation" |
| CA | isopropyl alcohol | 67-63-0 | PEV/VE A | 200 | | 400 | | | | | Regulation OHS |

Notation

Ceiling-C ceiling value is a limit value above which exposure should not occur

STEL short-term exposure limit: a limit value above which exposure should not occur and which is related to a 15-minute period (unless otherwise specified)

TWA time-weighted average (long-term exposure limit): measured or calculated in relation to a reference period of 8 hours
time-weighted average (unless otherwise specified)

| Relevant DNELs of components | | | | | | |
|--|------------|----------|-----------------|------------------------------------|-------------------|----------------------------|
| Name of substance | CAS No | Endpoint | Threshold level | Protection goal, route of exposure | Used in | Exposure time |
| Distillates (petroleum), straight-run middle | 64741-44-2 | DNEL | 16.4 mg/m³ | human, inhalatory | worker (industry) | chronic - systemic effects |
| Distillates (petroleum), straight-run middle | 64741-44-2 | DNEL | 1,501 mg/m³ | human, inhalatory | worker (industry) | acute - systemic effects |

AL-86

Version number: 1.0

Date of compilation: 2025-02-06

| Relevant DNELs of components | | | | | | |
|--|------------|----------|-------------------------|------------------------------------|-------------------|----------------------------|
| Name of substance | CAS No | Endpoint | Threshold level | Protection goal, route of exposure | Used in | Exposure time |
| Distillates (petroleum), straight-run middle | 64741-44-2 | DNEL | 2.91 mg/kg bw/day | human, dermal | worker (industry) | chronic - systemic effects |
| 2-butoxyethanol | 111-76-2 | DNEL | 98 mg/m ³ | human, inhalatory | worker (industry) | chronic - systemic effects |
| 2-butoxyethanol | 111-76-2 | DNEL | 1,091 mg/m ³ | human, inhalatory | worker (industry) | acute - systemic effects |
| 2-butoxyethanol | 111-76-2 | DNEL | 246 mg/m ³ | human, inhalatory | worker (industry) | acute - local effects |
| 1-Propanaminium, 3-amino-N-(carboxymethyl)-N,N-dimethyl-, N-coco acyl derivs., hydroxides, inner salts | 61789-40-0 | DNEL | 8.22 mg/m ³ | human, inhalatory | worker (industry) | chronic - systemic effects |
| 1-Propanaminium, 3-amino-N-(carboxymethyl)-N,N-dimethyl-, N-coco acyl derivs., hydroxides, inner salts | 61789-40-0 | DNEL | 2.33 mg/kg bw/day | human, dermal | worker (industry) | chronic - systemic effects |
| propan-2-ol | 67-63-0 | DNEL | 500 mg/m ³ | human, inhalatory | worker (industry) | chronic - systemic effects |
| propan-2-ol | 67-63-0 | DNEL | 888 mg/kg bw/day | human, dermal | worker (industry) | chronic - systemic effects |

| Relevant PNECs of components | | | | | | |
|--|------------|----------|-----------------|-----------------------|------------------------------|------------------------------|
| Name of substance | CAS No | Endpoint | Threshold level | Organism | Environmental compartment | Exposure time |
| 2-butoxyethanol | 111-76-2 | PNEC | 8.8 mg/l | aquatic organisms | freshwater | short-term (single instance) |
| 2-butoxyethanol | 111-76-2 | PNEC | 0.88 mg/l | aquatic organisms | marine water | short-term (single instance) |
| 2-butoxyethanol | 111-76-2 | PNEC | 463 mg/l | aquatic organisms | sewage treatment plant (STP) | short-term (single instance) |
| 2-butoxyethanol | 111-76-2 | PNEC | 34.6 mg/kg | aquatic organisms | freshwater sediment | short-term (single instance) |
| 2-butoxyethanol | 111-76-2 | PNEC | 3.46 mg/kg | aquatic organisms | marine sediment | short-term (single instance) |
| 2-butoxyethanol | 111-76-2 | PNEC | 2.33 mg/kg | terrestrial organisms | soil | short-term (single instance) |
| 1-Propanaminium, 3-amino-N-(carboxymethyl)-N,N-dimethyl-, N-coco acyl derivs., hydroxides, inner salts | 61789-40-0 | PNEC | 3.2 µg/l | aquatic organisms | freshwater | short-term (single instance) |
| 1-Propanaminium, 3-amino-N-(carboxymethyl)-N,N-dimethyl-, N-coco acyl derivs., hydroxides, inner salts | 61789-40-0 | PNEC | 0.32 µg/l | aquatic organisms | marine water | short-term (single instance) |
| 1-Propanaminium, 3- | 61789-40-0 | PNEC | 300 mg/l | aquatic organisms | sewage treatment | short-term (single instance) |

AL-86

Version number: 1.0

Date of compilation: 2025-02-06

| Relevant PNECs of components | | | | | | |
|--|------------|----------|-----------------|-----------------------|------------------------------|------------------------------|
| Name of substance | CAS No | Endpoint | Threshold level | Organism | Environmental compartment | Exposure time |
| amino-N-(carboxymethyl)-N,N-dimethyl-, N-coco acyl derivs., hydroxides, inner salts | | | | | plant (STP) | instance) |
| 1-Propanaminium, 3-amino-N-(carboxymethyl)-N,N-dimethyl-, N-coco acyl derivs., hydroxides, inner salts | 61789-40-0 | PNEC | 0.219 mg/kg | aquatic organisms | freshwater sediment | short-term (single instance) |
| 1-Propanaminium, 3-amino-N-(carboxymethyl)-N,N-dimethyl-, N-coco acyl derivs., hydroxides, inner salts | 61789-40-0 | PNEC | 21.9 µg/kg | aquatic organisms | marine sediment | short-term (single instance) |
| 1-Propanaminium, 3-amino-N-(carboxymethyl)-N,N-dimethyl-, N-coco acyl derivs., hydroxides, inner salts | 61789-40-0 | PNEC | 41.9 µg/kg | terrestrial organisms | soil | short-term (single instance) |
| propan-2-ol | 67-63-0 | PNEC | 140.9 mg/l | aquatic organisms | freshwater | short-term (single instance) |
| propan-2-ol | 67-63-0 | PNEC | 140.9 mg/l | aquatic organisms | marine water | short-term (single instance) |
| propan-2-ol | 67-63-0 | PNEC | 2,251 mg/l | aquatic organisms | sewage treatment plant (STP) | short-term (single instance) |
| propan-2-ol | 67-63-0 | PNEC | 552 mg/kg | aquatic organisms | freshwater sediment | short-term (single instance) |
| propan-2-ol | 67-63-0 | PNEC | 552 mg/kg | aquatic organisms | marine sediment | short-term (single instance) |
| propan-2-ol | 67-63-0 | PNEC | 28 mg/kg | terrestrial organisms | soil | short-term (single instance) |

8.2 Exposure controls

Appropriate engineering controls

General ventilation.

Individual protection measures (personal protective equipment)

Eye/face protection

Wear eye/face protection. Use protective eyewear to guard against splash of liquids.

Skin protection

- Hand protection

Wear suitable gloves. Chemical protection gloves are suitable, which are tested according to EN 374. Check leak-tightness/impermeability prior to use. In the case of wanting to use the gloves again, clean them before taking off and air them well. For special purposes, it is recommended to check the resistance to chemicals of the protective gloves mentioned above together with the supplier of these gloves.

- Other protection measures

Take recovery periods for skin regeneration. Preventive skin protection (barrier creams/ointments) is recommended. Wash hands thoroughly after handling.

Body protection

Protective clothing against liquid chemicals.

AL-86

Version number: 1.0

Date of compilation: 2025-02-06

Respiratory protection

Full face mask/half mask/quarter mask (EN 136/140). Type : A (against organic gases and vapors with a boiling point of > 65 °C , color code: Brown).

Environmental exposure controls

Avoid release to the environment. Keep away from drains, surface and ground water.

9 Physical and chemical properties

9.1 Information on basic physical and chemical properties

| | |
|--|--|
| Physical state | liquid |
| Color | clear - pink |
| Odor | characteristic |
| Odor threshold | no data available |
| Melting point/freezing point | not determined |
| Boiling point or initial boiling point and boiling range | not determined |
| Evaporation rate | not determined |
| Flammability | flammable liquid in accordance with GHS criteria |
| Lower and upper explosion limit | not determined |
| Flash point | 69 °C (c.c.) |
| Auto-ignition temperature | not determined |
| Decomposition temperature | not relevant |
| pH (value) | 7 – 9 |
| Kinematic viscosity | not determined |
| Solubility(ies) | not determined |

Partition coefficient

| | |
|---|-----------------------------------|
| Partition coefficient n-octanol/water (log value) | this information is not available |
|---|-----------------------------------|

| | |
|----------------|----------------|
| Vapor pressure | not determined |
|----------------|----------------|

Density and/or relative density

| | |
|-------------------------|---|
| Density | not determined |
| Relative vapour density | information on this property is not available |
| Relative density | 0.97 at 23 °C (water = 1) |

AL-86

Version number: 1.0

Date of compilation: 2025-02-06

| | |
|--------------------------|-----------------------|
| Particle characteristics | not relevant (liquid) |
|--------------------------|-----------------------|

9.2 Other information

| | |
|--|------------------------------------|
| Information with regard to physical hazard classes | there is no additional information |
| Other safety characteristics | there is no additional information |

10 Stability and reactivity

10.1 Reactivity

This material is not reactive under normal ambient conditions. Concerning incompatibility: see below "Conditions to avoid" and "Incompatible materials". The mixture contains reactive substance(s). Risk of ignition.

If heated:

Risk of ignition

10.2 Chemical stability

The material is stable under normal ambient and anticipated storage and handling conditions of temperature and pressure. See below "Conditions to avoid".

10.3 Possibility of hazardous reactions

No known hazardous reactions.

10.4 Conditions to avoid

Keep away from heat, hot surfaces, sparks, open flames and other ignition sources. No smoking.

Hints to prevent fire or explosion

Use explosion-proof electrical/ventilating/lighting/equipment. Use only non-sparking tools. Take precautionary measures against static discharge.

10.5 Incompatible materials

Oxidizers

10.6 Hazardous decomposition products

Reasonably anticipated hazardous decomposition products produced as a result of use, storage, spill and heating are not known. Hazardous combustion products: see section 5.

11 Toxicological information

11.1 Information on toxicological effects

Test data are not available for the complete mixture.

Classification procedure

The method for classification of the mixture is based on ingredients of the mixture (additivity formula).

Classification acc. to GHS

Acute toxicity

Shall not be classified as acutely toxic.

GHS of the United Nations, annex 4: May be harmful if swallowed.

| Acute toxicity estimate (ATE) of components | | | |
|---|------------|-----------------------|---------------------------|
| Name of substance | CAS No | Exposure route | ATE |
| Distillates (petroleum), straight-run middle | 64741-44-2 | inhalation: vapour | 11 mg _I /4h |
| Distillates (petroleum), straight-run middle | 64741-44-2 | inhalation: dust/mist | >2.53 mg _I /4h |
| Quaternary ammonium compounds, dicoco alkyl dimethyl, chlorides | 61789-77-3 | oral | 500 mg/kg |

AL-86

Version number: 1.0

Date of compilation: 2025-02-06

| Acute toxicity estimate (ATE) of components | | | |
|--|------------|--------------------|--------------|
| Name of substance | CAS No | Exposure route | ATE |
| 2-butoxyethanol | 111-76-2 | oral | 530 mg/kg |
| 2-butoxyethanol | 111-76-2 | dermal | 667 mg/kg |
| 2-butoxyethanol | 111-76-2 | inhalation: vapour | ≥3.9 mg/l/4h |
| Amines, C10-16-alkyldimethyl, N-oxides | 70592-80-2 | oral | >600 mg/kg |
| Amines, C14-18 and C16-18-unsatd. alkyl, ethoxylated | 68155-39-5 | oral | 300 mg/kg |

| Acute toxicity of components | | | | | |
|--|------------|-----------------------|----------|-------------------|---------|
| Name of substance | CAS No | Exposure route | Endpoint | Value | Species |
| Distillates (petroleum), straight-run middle | 64741-44-2 | inhalation: dust/mist | LC50 | >2.53 mg/l/4h | rat |
| Distillates (petroleum), straight-run middle | 64741-44-2 | dermal | LD50 | >2,000 mg/kg | rabbit |
| 2-butoxyethanol | 111-76-2 | oral | LD50 | 530 mg/kg | rat |
| 2-butoxyethanol | 111-76-2 | inhalation: vapour | LC50 | ≥3.9 mg/l/4h | rat |
| 2-butoxyethanol | 111-76-2 | inhalation: vapour | LC50 | 2.175 mg/l/4h | rat |
| 2-butoxyethanol | 111-76-2 | dermal | LD50 | 667 – 1,060 mg/kg | rabbit |
| 2-butoxyethanol | 111-76-2 | dermal | LD50 | 400 – 500 mg/kg | rabbit |
| Amines, C10-16-alkyldimethyl, N-oxides | 70592-80-2 | oral | LD50 | >600 mg/kg | rat |
| Amines, C10-16-alkyldimethyl, N-oxides | 70592-80-2 | oral | LD50 | >520 mg/kg | rabbit |
| 1-Propanaminium, 3-amino-N-(carboxymethyl)-N,N-dimethyl-, N-coco acyl derivs., hydroxides, inner salts | 61789-40-0 | oral | LD50 | >5,000 mg/kg | rat |
| Amines, C14-18 and C16-18-unsatd. alkyl, ethoxylated | 68155-39-5 | oral | LD50 | 300 – 2,000 mg/kg | rat |

Skin corrosion/irritation

Causes skin irritation. In vitro skin corrosion: human skin model test. Shall not be classified as corrosive to skin.

Serious eye damage/eye irritation

Causes serious eye damage.

Respiratory or skin sensitization

Shall not be classified as a respiratory or skin sensitizer.

Germ cell mutagenicity

Shall not be classified as germ cell mutagenic.

Carcinogenicity

Shall not be classified as carcinogenic.

AL-86

Version number: 1.0

Date of compilation: 2025-02-06

- IARC Monographs (WHO)

| IARC Monographs on the Evaluation of Carcinogenic Risks to Humans | | | |
|---|----------|----------------|--------|
| Name of substance | CAS No | Classification | Number |
| 2-butoxyethanol | 111-76-2 | 3 | |
| propan-2-ol | 67-63-0 | 3 | |

Legend

3 Not classifiable as to carcinogenicity in humans

Reproductive toxicity

Shall not be classified as a reproductive toxicant.

Specific target organ toxicity - single exposure

Shall not be classified as a specific target organ toxicant (single exposure).

Specific target organ toxicity - repeated exposure

Shall not be classified as a specific target organ toxicant (repeated exposure).

Aspiration hazard

Shall not be classified as presenting an aspiration hazard.

Information on likely routes of exposure

If on skin, If inhaled, If in eyes

Symptoms related to the physical, chemical and toxicological characteristics

If swallowed:

Diarrhoea, Vomiting, Abdominal pain

If in eyes:

Causes tears, Production of tissue damage in the eye, Conjunctivitis (pink eye), Risk of blindness

If inhaled:

Localized redness, edema, pruritis and/or pain, Cough, Headache

If on skin:

Localized redness, edema, pruritis and/or pain

Delayed and immediate effects as well as chronic effects from short and long-term exposure

Irritation and significant inflammation of the skin (dermatitis) due to the defatting properties of the product may be caused by repeated or prolonged exposure.

12 Ecological information

12.1 Toxicity

Toxic to aquatic life with long lasting effects.

| Aquatic toxicity (acute) of components | | | | | |
|--|------------|----------|-------------|--------------------------------|---------------|
| Name of substance | CAS No | Endpoint | Value | Species | Exposure time |
| Distillates (petroleum), straight-run middle | 64741-44-2 | LL50 | >100 mg/l | fish | 24 h |
| Distillates (petroleum), straight-run middle | 64741-44-2 | EL50 | >1,000 mg/l | aquatic invertebrates | 24 h |
| Quaternary ammonium compounds, dicoco alkyldimethyl, chlorides | 61789-77-3 | LC50 | 1.04 mg/l | bluegill (Lepomis macrochirus) | 96 h |
| Quaternary ammonium compounds, dicoco al- | 61789-77-3 | LC50 | 0.16 mg/l | daphnia magna | 48 h |

AL-86

Version number: 1.0

Date of compilation: 2025-02-06

| Aquatic toxicity (acute) of components | | | | | |
|--|------------|----------|----------------|-------------------------------------|---------------|
| Name of substance | CAS No | Endpoint | Value | Species | Exposure time |
| kyldimethyl, chlorides | | | | | |
| Quaternary ammonium compounds, dicoco alkyl dimethyl, chlorides | 61789-77-3 | EC50 | 0.46 mg/l | algae | 96 h |
| 2-butoxyethanol | 111-76-2 | LC50 | 1,474 mg/l | fish | 96 h |
| 2-butoxyethanol | 111-76-2 | EC50 | 1,550 mg/l | aquatic invertebrates | 48 h |
| 2-butoxyethanol | 111-76-2 | ErC50 | 1,840 mg/l | algae | 72 h |
| Amines, C10-16-alkyl dimethyl, N-oxides | 70592-80-2 | LC50 | 1,010 µg/l | daphnia magna | 96 h |
| Amines, C10-16-alkyl dimethyl, N-oxides | 70592-80-2 | LC50 | 2.6 – 3.5 mg/l | fish | 96 h |
| 1-Propanaminium, 3-amino-N-(carboxymethyl)-N,N-dimethyl-, N-coco acyl derivs., hydroxides, inner salts | 61789-40-0 | LC50 | 2 mg/l | fish | 96 h |
| 1-Propanaminium, 3-amino-N-(carboxymethyl)-N,N-dimethyl-, N-coco acyl derivs., hydroxides, inner salts | 61789-40-0 | EC50 | 6.4 mg/l | aquatic invertebrates | 48 h |
| propan-2-ol | 67-63-0 | LC50 | 10,000 mg/l | fish | 96 h |
| Amines, C14-18 and C16-18-unsatd. alkyl, ethoxylated | 68155-39-5 | LC50 | >0.1 – 1 mg/l | rainbow trout (Oncorhynchus mykiss) | 96 h |
| Amines, C14-18 and C16-18-unsatd. alkyl, ethoxylated | 68155-39-5 | EC50 | >0.1 – 1 mg/l | daphnia magna | 48 h |

| Aquatic toxicity (chronic) of components | | | | | |
|--|------------|----------|-------------|-----------------------|---------------|
| Name of substance | CAS No | Endpoint | Value | Species | Exposure time |
| Distillates (petroleum), straight-run middle | 64741-44-2 | EL50 | >1,000 mg/l | microorganisms | 40 h |
| 2-butoxyethanol | 111-76-2 | EC50 | 297 mg/l | aquatic invertebrates | 21 d |

12.2 Persistence and degradability

Biodegradation

The surfactant contained in this preparation complies with the biodegradability criteria as laid down in Regulation (EC) No 648/2004 on detergents.

| Degradability of components | | | | | | |
|--|------------|---------------------------|------------------|------|--------|--------|
| Name of substance | CAS No | Process | Degradation rate | Time | Method | Source |
| Distillates (petroleum), straight-run middle | 64741-44-2 | oxygen depletion | 57.5 % | 28 d | | ECHA |
| 2-butoxyethanol | 111-76-2 | carbon dioxide generation | 18.3 % | 3 d | | ECHA |

AL-86

Version number: 1.0

Date of compilation: 2025-02-06

| Degradability of components | | | | | | |
|--|------------|------------------|------------------|------|--------|--------|
| Name of substance | CAS No | Process | Degradation rate | Time | Method | Source |
| propan-2-ol | 67-63-0 | oxygen depletion | 53 % | 5 d | | ECHA |
| Amines, C14-18 and C16-18-unsatd. alkyl, ethoxylated | 68155-39-5 | DOC removal | 60 % | 28 d | | |

12.3 Bioaccumulative potential

Data are not available.

| Bioaccumulative potential of components | | | | |
|--|------------|------|---------------------------|----------|
| Name of substance | CAS No | BCF | Log KOW | BOD5/COD |
| 2-butoxyethanol | 111-76-2 | | 0.81 (pH value: 7, 25 °C) | |
| 1-Propanaminium, 3-amino-N-(carboxymethyl)-N,N-dimethyl-, N-coco acyl derivs., hydroxides, inner salts | 61789-40-0 | | -1.28 | |
| Amines, C14-18 and C16-18-unsatd. alkyl, ethoxylated | 68155-39-5 | <500 | | |

12.4 Mobility in soil

Data are not available.

12.5 Results of PBT and vPvB assessment

Data are not available.

12.6 Endocrine disrupting properties

Does not contain an endocrine disruptor (ED) in a concentration of $\geq 0.1\%$.

12.7 Other adverse effects

Data are not available.

13 Disposal considerations

13.1 Waste treatment methods

Dispose of contents/container in accordance with local/regional/national/international regulations.

Waste treatment-relevant information

Solvent reclamation/regeneration.

Sewage disposal-relevant information

Do not empty into drains. Avoid release to the environment. Refer to special instructions/safety data sheets.

Waste treatment of containers/packages

Completely emptied packages can be recycled. Handle contaminated packages in the same way as the substance itself.

Remarks

Please consider the relevant national or regional provisions. Waste shall be separated into the categories that can be handled separately by the local or national waste management facilities.

14 Transport information

14.1 UN number

not subject to transport regulations

14.2 UN proper shipping name

not relevant

AL-86

Version number: 1.0

Date of compilation: 2025-02-06

- 14.3 Transport hazard class(es)** none
- 14.4 Packing group** not assigned
- 14.5 Environmental hazards** non-environmentally hazardous acc. to the dangerous goods regulations
- 14.6 Special precautions for user**
There is no additional information.
- 14.7 Transport in bulk according to IMO instruments**
The cargo is not intended to be carried in bulk.

Information for each of the UN Model Regulations

Transport information - National regulations - Additional information (UN RTDG)

Not subject to transport regulations: UN RTDG

International Maritime Dangerous Goods Code (IMDG) - Additional information

Not subject to IMDG.

International Civil Aviation Organization (ICAO-IATA/DGR) - Additional information

Not subject to ICAO-IATA.

15 Regulatory information

15.1 Safety, health and environmental regulations specific for the product in question

National regulations (United States)

Toxic Substance Control Act (TSCA)

all ingredients are listed (ACTIVE) or exempt from listing

Superfund Amendment and Reauthorization Act (SARA TITLE III)

- Specific Toxic Chemical Listings (EPCRA Section 313)

Toxics Release Inventory: Specific Toxic Chemical Listings

| Name of substance | CAS No | Remarks | Effective date |
|-------------------|---------|---|----------------|
| propan-2-ol | 67-63-0 | only persons who manufacture by the strong acid process are subject, supplier notification not required | 1986-12-31 |

Clean Air Act

none of the ingredients are listed

Right to Know Hazardous Substance List

- Cleaning Product Right to Know Act Substance List (CA-RTK)

| Name of substance | CAS No | Functionality | Authoritative Lists |
|--|------------|---------------|--------------------------------|
| Quaternary ammonium compounds, dicocooalkyldimethyl, chlorides | 61789-77-3 | | CECBP - Priority Chemicals |
| 2-butoxyethanol | 111-76-2 | | ATSDR Neurotoxics OEHA RELs |
| propan-2-ol | 67-63-0 | | OEHA RELs |

AL-86

Version number: 1.0

Date of compilation: 2025-02-06

- Toxic or Hazardous Substance List (MA-TURA)

| Name of substance | CAS No | DEP CODE | PBT / HHS / LHS | PBT / HHS Threshold | De Minimis Concentration Threshold |
|-------------------|---------|----------|-----------------|---------------------|------------------------------------|
| 2-butoxyethanol | | 1022 | | | 1.0 % |
| propan-2-ol | 67-63-0 | | | | 1.0 % |

- Hazardous Substances List (MN-ERTK)

| Name of substance | CAS No | References | Remarks |
|-------------------|----------|------------|---------|
| 2-butoxyethanol | 111-76-2 | A, O | skin |
| propan-2-ol | 67-63-0 | A, N, O | |

Legend

- A American Conference of Governmental Industrial Hygienists (ACGIH), "Threshold Limit Values for Chemical Substances and Physical Agents and Biological Exposure Indices for 1992-93", available from ACGIH
- N National Institute for Occupational Safety and Health (NIOSH), "Recommendations for Occupational Safety and Health Standards," August 1988, available from NIOSH, Publications Dissemination Office, Division of Standards Development and Technology Transfer
- O Occupational Safety and Health Administration (OSHA), Safety and Health Standards, Code of Federal Regulations, title 29, part 1910, subpart Z, "Toxic and Hazardous Substances, 1990." General information: Minnesota Department of Labor and Industry, Occupational Safety and Health Division
- skin If a potential for absorption from skin contact merits special consideration, the word "skin" follows the substance name.

- Hazardous Substance List (NJ-RTK)

| Name of substance | CAS No | Remarks | Classifications |
|-------------------|----------|---------|-----------------|
| 2-butoxyethanol | 111-76-2 | | CA F2 |
| propan-2-ol | 67-63-0 | | F3 |

Legend

- CA Carcinogenic
- F2 Flammable - Second Degree
- F3 Flammable - Third Degree

- Hazardous Substance List (Chapter 323) (PA-RTK)

| Name acc. to inventory | CAS No | Classification |
|------------------------|----------|----------------|
| ETHANOL, 2-BUTOXY- | 111-76-2 | |
| 2-PROPANOL | 67-63-0 | E |

Legend

- E Environmental hazard

- Hazardous Substance List (RI-RTK)

| Name of substance | CAS No | References |
|-------------------|----------|------------|
| 2-butoxyethanol | 111-76-2 | T |
| 2-butoxyethanol | 111-76-2 | T |
| propan-2-ol | 67-63-0 | T, F |

Legend

- F Flammability (NFPA®)
- T Toxicity (ACGIH®)

AL-86

Version number: 1.0

Date of compilation: 2025-02-06

California Environmental Protection Agency (Cal/EPA): Proposition 65 - Safe Drinking Water and Toxic Enforcement Act of 1987

| Proposition 65 List of chemicals | | | |
|--------------------------------------|---------|---------------|----------------------|
| Name acc. to inventory | CAS No | Conc. | Type of the toxicity |
| dichloroacetic acid | 79-43-6 | 0.0003491 wt% | cancer |
| dichloroacetic acid | 79-43-6 | 0.0003491 wt% | developmental, male |
| dichloromethane (methylene chloride) | 75-09-2 | 0.01079 wt% | cancer |

Industry or sector specific available guidance(s)

NPCA-HMIS® III

Hazardous Materials Identification System. American Coatings Association.

| Category | Rating | Description |
|---------------------|--------|--|
| Chronic | / | none |
| Health | 3 | major injury likely unless prompt action is taken and medical treatment is given |
| Flammability | 2 | material that must be moderately heated or exposed to relatively high ambient temperatures before ignition can occur |
| Physical hazard | 0 | material that is normally stable, even under fire conditions, and will not react with water, polymerize, decompose, condense, or self-react. Non-explosive |
| Personal protection | - | |

NFPA® 704

National Fire Protection Association: Standard System for the Identification of the Hazards of Materials for Emergency Response (United States).

| Category | Degree of hazard | Description |
|----------------|------------------|--|
| Flammability | 2 | material that must be moderately heated or exposed to relatively high ambient temperatures before ignition can occur |
| Health | 3 | material that, under emergency conditions, can cause serious or permanent injury |
| Instability | 0 | material that is normally stable, even under fire conditions |
| Special hazard | | |

National regulations (Canada)

Domestic Substances List (DSL)/Non-domestic Substances List (NDSL)

all ingredients are listed

National inventories

| Country | Inventory | Status |
|---------|------------|-------------------------------------|
| CA | DSL/NDSL | all ingredients are listed |
| EU | REACH Reg. | not all ingredients are listed |
| US | TSCA | all ingredients are listed (ACTIVE) |

Legend

DSL/NDSL Domestic Substances List (DSL)/Non-domestic Substances List (NDSL)
REACH Reg. REACH registered substances
TSCA Toxic Substance Control Act

AL-86

Version number: 1.0

Date of compilation: 2025-02-06

15.2 Chemical Safety Assessment

Chemical safety assessments for substances in this mixture were not carried out.

16 Other information

Indication of changes (revised safety data sheet)

Date of compilation. 2025-02-06.

Abbreviations and acronyms

| Abbr. | Descriptions of used abbreviations |
|-----------------|--|
| "BC Regulation" | OHS Regulation: Section 5.48 (British Columbia) |
| ACGIH® | American Conference of Governmental Industrial Hygienists |
| Acute Tox. | Acute toxicity |
| Asp. Tox. | Aspiration hazard |
| ATE | Acute Toxicity Estimate |
| BCF | Bioconcentration factor |
| BOD | Biochemical Oxygen Demand |
| CAS | Chemical Abstracts Service (service that maintains the most comprehensive list of chemical substances) |
| Ceiling-C | Ceiling value |
| COD | Chemical oxygen demand |
| DEP CODE | Department of Environmental Protection Code |
| DGR | Dangerous Goods Regulations (see IATA/DGR) |
| DNEL | Derived No-Effect Level |
| EC50 | Effective Concentration 50 %. The EC50 corresponds to the concentration of a tested substance causing 50 % changes in response (e.g. on growth) during a specified time interval |
| ED | Endocrine disruptor |
| EL50 | Effective Loading 50 %: the EL50 corresponds to the loading rate required to produce a response in 50% of the test organisms |
| ErC50 | ≡ EC50: in this method, that concentration of test substance which results in a 50 % reduction in either growth (EbC50) or growth rate (ErC50) relative to the control |
| Eye Dam. | Seriously damaging to the eye |
| Eye Irrit. | Irritant to the eye |
| Flam. Liq. | Flammable liquid |
| GHS | "Globally Harmonized System of Classification and Labelling of Chemicals" developed by the United Nations |
| HHS | Higher hazard substance |
| IARC | International Agency for Research on Cancer |
| IARC Monographs | IARC Monographs on the Evaluation of Carcinogenic Risks to Humans |
| IATA | International Air Transport Association |
| IATA/DGR | Dangerous Goods Regulations (DGR) for the air transport (IATA) |
| ICAO | International Civil Aviation Organization |
| IMDG | International Maritime Dangerous Goods Code |
| LC50 | Lethal Concentration 50%: the LC50 corresponds to the concentration of a tested substance causing 50 % lethality during a specified time interval |
| LD50 | Lethal Dose 50 %: the LD50 corresponds to the dose of a tested substance causing 50 % lethality during a specified time interval |

AL-86

Version number: 1.0

Date of compilation: 2025-02-06

| Abbr. | Descriptions of used abbreviations |
|----------------|--|
| LHS | Lower hazard substance |
| LL50 | Lethal Loading 50 %: the LL50 corresponds to the loading rate causing 50 % lethality |
| log KOW | n-Octanol/water |
| MoL | Ministry of Labor: Current Occupational Exposure Limits for Ontario Workplaces Required under Regulation 833 |
| NFPA® | National Fire Protection Association (United States) |
| NPCA-HMIS® III | National Paint and Coatings Association: Hazardous Materials Identification System - HMIS® III, Third Edition |
| OHS Code | Occupational Health and Safety Code: Occupational exposure limits for chemical substances (Alberta) |
| PBT | Persistent, Bioaccumulative and Toxic |
| PNEC | Predicted No-Effect Concentration |
| ppm | Parts per million |
| Regulation OHS | Regulation respecting occupational health and safety: Permissible exposure values for airborne contaminants (Quebec) |
| RTECS | Registry of Toxic Effects of Chemical Substances (database of NIOSH with toxicological information) |
| Skin Corr. | Corrosive to skin |
| Skin Irrit. | Irritant to skin |
| STEL | Short-term exposure limit |
| STOT SE | Specific target organ toxicity - single exposure |
| TWA | Time-weighted average |
| UN RTDG | UN Recommendations on the Transport of Dangerous Good |
| vPvB | Very Persistent and very Bioaccumulative |

Key literature references and sources for data

Hazardous Products Regulations (HPR)
SOR/2022-272: Regulations Amending the Hazardous Products Regulations (GHS, Seventh Revised Edition)
UN Recommendations on the Transport of Dangerous Good. International Maritime Dangerous Goods Code (IMDG).
Dangerous Goods Regulations (DGR) for the air transport (IATA).

Classification procedure

Physical and chemical properties: The classification is based on tested mixture.
Health hazards, Environmental hazards: The method for classification of the mixture is based on ingredients of the mixture (additivity formula).

List of relevant phrases (code and full text as stated in section 2 and 3)

| Code | Text |
|------|---|
| H225 | Highly flammable liquid and vapour. |
| H226 | Flammable liquid and vapour. |
| H227 | Combustible liquid. |
| H301 | Toxic if swallowed. |
| H302 | Harmful if swallowed. |
| H304 | May be fatal if swallowed and enters airways. |
| H311 | Toxic in contact with skin. |
| H314 | Causes severe skin burns and eye damage. |
| H315 | Causes skin irritation. |

AL-86

Version number: 1.0

Date of compilation: 2025-02-06

| Code | Text |
|------|------------------------------------|
| H318 | Causes serious eye damage. |
| H319 | Causes serious eye irritation. |
| H331 | Toxic if inhaled. |
| H332 | Harmful if inhaled. |
| H336 | May cause drowsiness or dizziness. |

Disclaimer

This information is based upon the present state of our knowledge. This SDS has been compiled and is solely intended for this product.