



VIPER VENOM DDR5 AMD RAM 16GB(2X8GB) 5600MT/s UDIMM KIT

Introducing the Patriot Viper Venom AMD DDR5, a memory module made for reliability. Created with blazing fast speeds for an uncompromised performance, each module is 100% hand tested on the latest AMD DDR5 platforms to ensure a seamless experience. Designed with a Venom aluminum dual color heatshield, the memory module looks ensures a striking look while still preventing overheating.

The Patriot Viper Venom AMD DDR5 is AMD EXPO ready, unlocking enhanced speeds for faster setups and maximum system performance. Whether you're multitasking intensive applications, handling demanding workloads, or just catching up on the busyness of everyday life, the Patriot Viper Venom AMD DDR5 delivers the speed and dependability to stay ahead.



PRODUCT INFORMATION

PATRIOT INV. NUMBER:	VV516G56C36AK
DESCRIPTION:	VIPER VENOM DDR5 16GB (2X8GB) 5600MT/s UDIMM KIT
CERTIFICATIONS/SAFETY:	CE/FCC/RoHS/BSMI/UKCA
PRODUCT WARRANTY:	Limited Lifetime Warranty
UNIT UPC:	4711378432824
UNIT WEIGHT:	0.11 lbs / 52 g
UNIT DIMENSIONS:	0.27"(L) x 5.39"(W) x 1.69"(H) 0.7 cm (L) x 13.7 cm (W) x 4.3 cm (H)
PACKAGING TYPE:	Retail Box
PACKAGING WEIGHT:	0.37 lbs / 169 g
PACKAGING DIMENSIONS:	0.79"(L) x 7.08"(W) x 6.24"(H) 2.03 cm (L) x 17.99 cm (W) x 15.87 cm (H)
MASTER CARTON WEIGHT:	22.35 lbs / 10 kg
MASTER CARTON DIMENSIONS:	22.63"(L) x 18.7"(W) x 7.87"(H) 57.5 cm (L) x 47.5 cm (W) x 20 cm (H)
UNITS PER INNER CARTON:	10
UNITS PER MASTER CARTON:	60

FEATURES:

- Series: Viper Venom AMD DDR5 series
- Edition: Matte Black with Red Viper logo / Silver name plate
- Aluminum heat spreader with unique and specific design element
- Feature Overclock: EXPO overclocking supported
- Compatibility: Tested across latest DDR5 platforms for reliably on high performance
- Limited lifetime warranty
- On-Die ECC
- Thermal sensor

SPECIFICATIONS:

- Capacity: 16GB (2 x 8GB)
- Base Frequency: PC5-38400 (4800MHz)
 - Base Timings: 40-40-40-77
 - Base Voltage: 1.1V
- Tested Frequency EXPO Profile 1: PC5-44800 (5600MT/s)
 - Tested Timings: 36-46-46-110
 - Tested Voltage for EXPO Profile 1: 1.35V
- Tested Frequency EXPO Profile 2: PC5-41600 (5200MT/s)
 - Tested Timings: 36-36-36-68
 - Tested Voltage for EXPO Profile 2: 1.2V

For technical support, email us at:
SUPPORT@PATRIOTMEM.COM

MEMORY STORAGE