

## 4500 QM BO

EXTERIOR COLLECTION



# Durablex

## 4500 QM BO - 10 colours


Our **Durablex 4500 QM blackout** perfectly matches the colours of our 5% fabric. It has an exceptional width of 280 cm – the widest available on the market. The 100% blackout version provides complete privacy at night, confidentiality, and total light elimination. We have 10 commercial colours readily available in our warehouse.

- 4500 QM B01  
white uni
- 4500 QM B04  
linen uni
- 4500 QM B02  
white - pearl
- 4500 QM B06  
pearl uni
- 4500 QM B08  
grey - white
- 4500 QM B10  
grey uni
- 4500 QM B11  
grey - coal
- 4500 QM B13  
coal uni
- 4500 QM B17  
deep black uni
- 4500 QM B19  
coastal stone - grey


The colours displayed on this colour card are for reference only. Due to the nature of fabric production, slight colour variations may occur between different batches.

Ref.	Ts % e,n-h	Rs % e,n-h	As %	Tv % v,n-h	Rv % v,n-h	Av %	Tuv %	Double glazing with low emission degree and argon interspace	
								U <sub>g</sub> =1,2 W/(m²K) g=0,59	
								g <sub>tot</sub>	F <sub>c</sub>
QM B01	0	64,7	35,3	0	75,0	25,0	0	0,03	0,05
QM B04	0	55,5	44,5	0	62,5	37,5	0	0,04	0,07
QM B02	0	47,2	52,8	0	52,7	47,3	0	0,05	0,08
QM B06	0	33,4	66,6	0	35,1	64,3	0	0,06	0,10
QM B08	0	34,7	65,3	0	39,1	60,9	0	0,06	0,10
QM B10	0	16,4	83,6	0	16,8	83,2	0	0,07	0,12
QM B11	0	10,3	89,7	0	10,5	89,5	0	0,08	0,13
QM B13	0	5,2	94,8	0	5,4	94,6	0	0,08	0,14
QM B17	0	3,4	96,6	0	3,4	96,6	0	0,09	0,14
QM B19	0	18,4	81,6	0	17,6	82,4	0	0,07	0,12


OF




TS




Tv




Rs



G/tot



AS



# 4500 QM BO

## Technical properties

Technical specifications	Average Values	0%	Standard	
Composition	Fiberglass 19%		ISO 1833-1	
	PVC 70% / PU 11%			
Weight(/sqm)	625 gram ± 5%		ISO 3081	
Thickness	0.83mm ± 5%		ISO 5084	
Fabric count (sq.inch)	50 ends X 35 picks		ISO 7211/2	
Tensile strength (daN/5cm)	201.4 Warp / 141.0 Weft ± 5%		ISO 1421/1	
Tearing strength (daN)	7.1 Warp / 6.5 Weft ± 5%		ISO 4674	
Colorfastness to light	Grade 7-8		ISO 105 B02	
Fire resistance	C s3, d0	B2	EN13501-01(EU)	DIN 4102(DE)
	M1	FR	NF P92-503(FR)	NFPA 701 (US)
Environment	OEKO-TEX Standard 100			
	GREENGUARD			
Standard width	280 cm			
Standard length	30 meter / roll			
Cutting	best result with crush cutting			
Welding	thermal, HF, ultrasonic, sewing			
Cleaning	remove dust from the fabric surface, then wipe gently			
	with a humid soft sponge while using a mild detergent			

## Light performances

Classification EN 14501 (2021-09)

Code	glare control	privacy night	sight contact with the outside	daylight utilisation
QM B01	4	4	0	0
QM B02	4	4	0	0
QM B06	4	4	0	0
QM B08	4	4	0	0
QM B10	4	4	0	0
QM B11	4	4	0	0
QM B13	4	4	0	0
QM B17	4	4	0	0
QM B19	4	4	0	0

Influence on visual comfort					
Class	0	1	2	3	4
	very small effect	small effect	moderate effect	high effect	very high effect

All data are purely indicative and non contractual

## Eco & conformity labels

FIVE YEAR WARRANTY



FIRE RETARDANT



ANTI-BACTERIAL



LEAD FREE

