


3000 CA  
INTERIOR COLLECTION

# Sunshadow

## 3000 CA 3%

This is our hybrid fabric. It is woven with a combination of PVC coated yarn and PES yarn (in the weft) with a weight of only 325 g/m<sup>2</sup> and a thickness of only 0.45 mm.

This yarn combination creates a unique look and see-through. We offer 10 colours in our 2 traditional widths.

- 
- 3000 CA01  
white uni
  - 3000 CA02  
white - moccasin
  - 3000 CA03  
white - grey
  - 3000 CA04  
white - dim grey
  - 3000 CA30  
grey - light grey
  - 3000 CA08  
coal - bronze
  - 3000 CA09  
coal uni
  - 3000 CA71  
coal - apricot
  - 3000 CA32  
grey - dim grey
  - 3000 CA10  
coal - grey

# 3000 CA 3%

## Technical properties

Technical specifications	Average Values		Standard	
Composition	PES 35% PVC 65%		ISO 1833-1	
Weight (/sqm)	320 gr		ISO 3031	
Thickness	0,45 mm		ISO 5084	
Fabric count (sq. Inch)			ISO 7271/2	
Tensile strength (daN/5cm)	Warp 150daN - 120daN		ISO 1421/1	
Tearing strength	Warp 4,5daN - 6,9daN		ISO 4674	
Colorfastness to light	>7		ISO 105 B03	
Fire resistance	C s2 d0	B1	EN 13501-01 (EU)	DIN 4102 (DE)
	M2		NF P92-593 (FR)	NFPA 701 (US)
Environment	OEKO-TEX standard 100			
	GREENGUARD			
Standard width	250 cm - 300 cm			
Standard length	30 meter/roll			
Cutting	best result with ultrasonic cutting			
Welding	thermal, HF, ultrasonic, sewing			
Cleaning	remove dust from the fabric surface, then wipe gently			
	with a humid soft sponge while using a mild detergent			

FIVE YEAR WARRANTY



FIRE RETARDANT



ANTI-BACTERIAL








LEAD FREE



1905063  
Centexbel

Ref.	Ts	Rs	As	Tv	Rv	Av	Tuv	Double glazing with low emission degree and argon interspace	
								$U_g = 1,2 \text{ W}/(\text{m}^2\text{K})$	$g = 0,59$
								$g_{\text{tot}}$	$F_c$
CA01	24	66	10	23	74	3	6,2	0,36	0,61
CA02	22	59	19	20	66	17	6,5	0,38	0,64
CA03	19	58	23	17	65	19	4,7	0,38	0,65
CA04	18	54	28	16	62	24	4,4	0,40	0,67
CA30	15	34	51	12	35	55	7,1	0,46	0,78
CA08	4	5	91	4	5	89	3,8	0,55	0,94
CA09	3	5	92	3	4	92	2,8	0,55	0,94
CA71	6	16	78	5	17	80	4,4	0,52	0,87
CA32	13	33	54	10	34	58	4,8	0,46	0,79
CA10	5	6	89	4	6	90	4,4	0,55	0,93



### Classification EN 14501 (2021 - 09)

Code	glare control	privacy night	sight contact with the outside	daylight utilisation
CA01	0	1	1	2
CA02	0	1	2	2
CA03	0	2	1	2
CA04	0	2	2	2
CA30	0	1	2	2
CA08	1	2	2	1
CA09	3	2	2	1
CA71	1	2	2	1
CA32	0	2	1	1
CA10	1	2	2	1

Influence on visual comfort					
Class	0	1	2	3	4
	very small effect	small effect	moderate effect	high effect	very high effect

All data are purely indicative and non contractual