


CL-616


Emergency Light



Details




Schematic



Type	LED emergency light
Mounting	Sidewall, ceiling
Light source	50.000h operational time, 6000K color temperature
Luminous flux	591 lm
Warranty	5-years warranty
Dimensions	315x102x74mm
Housing color and material	White plastic
Cable connection	Max. 2.5mm ² cross-section solid or sleeved twisted wire
Operating mode:	Non-maintained / Maintained
Constant nominal ambient temperature range	0 °C<Ta<45 °C

LED safety light with IP54 protection for ceilings or sidewalls.

Mounting height (m)		2,5	3	4	6	8	10	15
Escape route min 1 lux	Transverse mounting	9,71	10,48	11,55	13,29	14,17	14,84	0
	Transverse mounting	3,92	4,23	4,52	5,08	5,17	4,66	0
	Axial mounting	11,43	12,8	14,81	13,91	16,46	15,74	0
	Axial mounting	4,9	5,4	4,78	5,96	4,7	2,76	0



Product name	System type	Main supply	Input current	Battery type/time	Product code
CL-616 Slave/Con/MB	Conventional main battery	AC 120-240V	21mA	NIMH 600mA 1 h	300111
CL-616 Slave/Con/MB	Conventional main battery	AC 120-240V	21mA	NIMH 2400mA 3 h	300112
CL-616 Slave/Con/CB ACAC	Conventional central battery	AC 120-240V	31mA	-	300194
CL-616 Slave/Con/CB ACDC	Conventional central battery	AC/DC 120-240V	31mA	-	300129
CL-616 Slave/Con/CB/24V	Conventional central battery	DC 24-32V	235mA	-	300138
CL-616 Slave/MB	Addressable main battery	AC 120-240V	21mA	NIMH 600mA 1 h	300117
CL-616 Slave/MB	Addressable main battery	AC 120-240V	21mA	NIMH 2400mA 3 h	300118
CL-616 Slave/RF/MB	Addressable wireless main battery	AC 120-240V	21mA	NIMH 600mA 1 h	-
CL-616 Slave/RF/MB	Addressable wireless main battery	AC 120-240V	21mA	NIMH 2400mA 3 h	-
CL-616 Slave/CB 24V	Addressable central battery	DC 24-32V	235mA	-	300278
CL-616 Slave/CB	Addressable central battery	AC 120-240V	31mA	-	300047
CL-616 Slave/CB AC-DC	Addressable central battery	AC/DC 120-240V	31mA	-	-