


CL-8017


Luminaire



Details



Schematic



| | |
|--|---|
| Type | Explosion-proof exit sign luminaire |
| Mounting | Sidewall |
| Light source | 50.000h operational time, 6000K color temperature |
| Warranty | 2-years warranty |
| Dimensions | 314mm x 188mm x 72mm |
| Housing color and material | White plastic |
| Cable connection | Max. 2.5mm ² cross-section solid or sleeved twisted wire |
| Operating mode | Non-maintained / Maintained |
| Constant nominal ambient temperature range | 0 °C < Ta < 45 °C |
| Class | Zone 2 |

The CL-8017 is a one-sided, sidewall-mounted, explosion-proof LED exit sign designed for Zone 2 hazardous areas. Due to its IP65 rating, the luminaire is suitable for dry and wet locations (rest room, basement, garage) and for outdoor use as well. Pictogram's direction must be marked during the order.

The following pictograms can be selected:



| Product name | System type | Main supply | Input current | Battery type/time | Product code |
|---------------------------|-----------------------------------|----------------|---------------|-------------------|--------------|
| CL-8017 Slave/Con/MB | Conventional main battery | AC 120-240V | 32mA | NIMH 1600mA 1-3 h | |
| CL-8017 Slave/Con/CB ACAC | Conventional central battery | AC 120-240V | 24mA | - | |
| CL-8017 Slave/Con/CB ACDC | Conventional central battery | AC/DC 120-240V | 24mA | - | |
| CL-8017 Slave/Con/CB/24V | Conventional central battery | DC 24-32V | 80mA | - | |
| CL-8017 Slave/MB | Addressable main battery | AC 120-240V | 32mA | NIMH 1600mA 1-3 h | |
| CL-8017 Slave/RF/MB | Addressable wireless main battery | AC 120-240V | 32mA | NIMH 1600mA 1-3 h | |
| CL-8017 Slave/CB 24V | Addressable central battery | DC 24-32V | 80mA | - | |
| CL-8017 Slave/CB | Addressable central battery | AC 120-240V | 24mA | - | |
| CL-8017 Slave/CB AC-DC | Addressable central battery | AC/DC 120-240V | 24mA | - | |