

CL-6016


Emergency Light



Details




Schematic



Type	LED emergency light
Mounting	Sidewall, ceiling
Light source	50.000h operational time, 6000K color temperature
Luminous flux	24V: 745 lm CON/MB: 567 lm
Warranty	5-years warranty
Dimensions	337mm x 170mm x 62mm
Housing color and material	White plastic
Cable connection	Max. 2.5mm ² cross-section solid or sleeved twisted wire
Operating mode:	Non-maintained

Thanks to IP65 protection it is suitable in dry and wet locations (rest room, basement, garage, etc.) and for outdoor use as well.

Mounting height (m)		2,5	3	4	6	8	10	15
Escape route min 1 lux	Transverse mounting	11	12.2	14.4	16.2	17.5	18.2	4.7
	Axial mounting	4.7	5.1	5.7	6.8	6.8	6.1	5.6
Escape route min 1 lux	Transverse mounting	11	12.2	14.4	16.2	17.5	18.2	4.7
	Axial mounting	4.7	5.1	5.7	6.8	6.8	6.1	5.6



Product name	System type	Main supply	Input current	Battery type/time	Product code
CL-6016 Slave/Con/MB	Conventional main battery	AC 120-240V	21 mA	NIMH 600mA 1 h	300182
CL-6016 Slave/Con/MB	Conventional main battery	AC 120-240V	21 mA	NIMH 2400mA 3 h	300252
CL-6016 Slave/Con/CB ACAC	Conventional central battery	AC 120-240V	31 mA	-	300221
CL-6016 Slave/Con/CB ACDC	Conventional central battery	AC/DC 120-240V	31 mA	-	300240
CL-6016 Slave/Con/CB/24V	Conventional central battery	DC 24-32V	235 mA	-	300331
CL-6016 Slave/MB	Addressable main battery	AC 120-240V	21 mA	NIMH 600mA 1 h	300181
CL-6016 Slave/MB	Addressable main battery	AC 120-240V	21 mA	NIMH 2400mA 3 h	300245
CL-6016 Slave/RF/MB	Addressable wireless main battery	AC 120-240V	21 mA	NIMH 600mA 1 h	-
CL-6016 Slave/RF/MB	Addressable wireless main battery	AC 120-240V	21 mA	NIMH 2400mA 3 h	-
CL-6016 Slave/CB 24V	Addressable central battery	DC 24-32V	235 mA	-	300275
CL-6016 Slave/CB	Addressable central battery	AC 120-240V	31 mA	-	300183
CL-6016 Slave/CB AC-DC	Addressable central battery	AC/DC 120-240V	31 mA	-	-