


Data sheet


Jupiter 550 vertical fixed glass 2 sides




550 vertical fixed glass 2 sides



550 vertical fixed glass 2 sides, airbox behind



550 vertical fixed glass 2 sides, airbox on top



General Information

<i>Manufacturer:</i>	Meteor A/S, Drejervej 1, DK-7451 Sunds
<i>Model:</i>	Jupiter 470 vertical fixed glass 2 sides fireplace insert for combustion with solid fuel
<i>Identification code:</i>	ELAB 2169 Rev 1

Fuel

<i>Fuel type:</i>	wood – suitable for combustion with kiln-dried firewood in accordance with the user manual
<i>Recommended fuel load:</i>	1,62 kg
<i>Basic fire bed weight:</i>	330 g
<i>Suitable for:</i>	intermittent operation – according to EN 16510 definition

Testing

<i>Test report valid from:</i>	07.12.2015
<i>Tested according to:</i>	EN 16510-1:2022 and EN 16510-2-2:2022, Tested by DTI in accordance with Regulation (EU) 2015/1186
<i>Testing institute:</i>	Danish Technological Institute (DTI), #1235
<i>Declaration of Performance (DoP):</i>	01.11.2025
<i>DoP number</i>	DoP-2169-2025-07

Dimensions and Weight

<i>Weight</i>	120 kg
<i>External frame dimensions:</i>	W540 x H750 X D470 mm
<i>Door dimensions:</i>	W453 x H629 mm

Performance Data

<i>Energy efficiency class:</i>	EEl 110, Class A+
<i>Nominal heat output:</i>	6,7 kW
<i>Heat to water:</i>	N/A
<i>Efficiency:</i>	83 %
<i>Seasonal efficiency:</i>	73 %
<i>Emissioner (normal operation, 13 % O₂)</i>	CO: ≤ 1500 mg/Nm ³ NOX: ≤ 200 mg/Nm ³ OGC: ≤ 120 mgC/Nm ³ PM: ≤ 40 mg/Nm ³

CE EN 16510-1:2022 / EN 16510-2-2:2022	Typebetegnelse Type designation Désignation du type Jupiter 550 højformat fast glas 2 sider	Nr. for ydeevnedeklaration Declaration of Performance No. Numéro de déclaration de performance DoP-2169-2025-07	Prøveinstitut Test agency Organisme d'essai NB 1235	Nominel effekt Rated effect Puissance nominale 6,7 kW	Virkningsgrad Efficiency Rendement 83 %
Sæsonbetinget virkningsgrad Seasonal space heating energy efficiency Rendement énergétique saisonnier pour le chauffage des locaux 73 %		CO-emmission (13% O₂) CO CO ≤1500 mg/Nm³	NOx NOx NOx ≤200 mg/Nm³	OGC OGC OGC ≤120 mgC/Nm³	PM PM PM ≤40 mg/m³ Aftrækstemperatur Exhaust temperature Température des fumées 301 °C
Sikkerhedsafstand til brandbart materiale: Se vejledning side 14 Clearance to flammable material: See the instructions page 14 Distance de sécurité aux matériaux combustibles : voir la notice page 14	Møbleringsafstand Minimum distance to furniture Distance minimale aux meubles 1150 mm		Minimum træk Min. flue draught Tirage minimal 12 Pa	Røggasmængde Flue gas mass flow Débit massique des fumées 5,2 g/s	Energieffektivitets indeks (EEI) Energy efficiency Indice d'efficacité énergétique (IEE) 110 (Klasse A+)
Anbefalet brændselstype / betegnelse Recommended fuel designation / designation Combustible recommandé / désignation			Træ / I Wood logs / I Bois (bûches) / I		
Pejseindsats til fast brændsel Fireplace insert for solid fuel Insert de cheminée à combustible solide			Meteor® fire space		
Læs og følg montage- samt brugsvejledning grundigt Read and follow the installation and operating instructions carefully Lire attentivement et respecter les instructions d'installation et d'utilisation			Prod. no. Product No. _____ N° de produit		




ENERG
енергия · ενεργεια



Meteor A/S

Jupiter 550 høj fast
sideglas 1/2 side(r)



6,7
kW

ENERGIA · ЕНЕРГИЯ · ΕΝΕΡΓΕΙΑ · ENERGIJA · ENERGY · ENERGIE · ENERGI

2015/1186