



# TECHNOLOGY SCREENING

HAPPY DIAMOND  
IMO NUMBER 9551947  
SEPTEMBER 2025

# EXECUTIVE SUMMARY

Njord has completed a Technology Screening for vessel Happy Diamond. Below are the key findings.

## KEY FINDINGS

8

Number of techs.  
found relevant

13.7

Savings potential in %

2.89

Return on Investment  
in Years

902,000

Total Investment in USD

311,594

Yearly Bunker Savings in USD



# NJORD SCORE

Njord Score	A	B	C	D	E
Remaining Savings Potential	< 3%	< 6%	< 9%	< 12%	+ 12%

## The Njord Score of vessel HAPPY DIAMOND is E.

The score given is based on how much the vessel can improve its efficiency through the application of a combined Energy Savings Technology package, that does not supersede 2.5 years ROI.

5

Number of techs.  
found commercially  
viable

12.1

Savings potential  
in %

2.05

ROI in  
years

E

Benchmark  
score

*The figures above highlight the total number of commercially viable technologies yet to be explored, their combined savings impact and ROI. The benchmark Njord Score reflects how similar vessels, which Njord has worked on, are currently rated.*

[READ MORE ABOUT THE  
NJORD SCORE HERE](#)





<b>1</b>	<b>EXECUTIVE SUMMARY</b>	<b>2</b>
<b>2</b>	<b>NJORD SCORE</b>	<b>3</b>
<b>3</b>	<b>GENERAL INFORMATION</b>	<b>5</b>
<b>4</b>	<b>VESSEL PARTICULARS</b>	<b>6</b>
<b>5</b>	<b>BUSINESS CASE</b>	<b>8</b>
<b>6</b>	<b>REGULATORY IMPACT</b>	<b>9</b>
<b>7</b>	<b>BASIC TECHNOLOGIES</b>	<b>12</b>
<b>8</b>	<b>NEXT STEP - NJORD'S SOLUTION DESIGN</b>	<b>14</b>



# GENERAL INFORMATION

## METHODOLOGY

This Technology Screening is based on Njord's experience of +500 vessel assessments and +200 Energy Efficiency Technologies (EETs) installations. For HAPPY DIAMOND, Njord has utilized insights from work completed on similar vessels in terms of segment, size, and trading patterns. To avoid overlapping savings when applying multiple technologies, all technologies are prioritized based on impact. For example, if Technology X (priority 1) has a 10% individual impact and Technology Y (priority 2) has a 5% individual impact, Y's effect is calculated on the remaining 90% of fuel consumption. This approach ensures accuracy when applying multiple EETs and the avoidance of counting savings twice. Novel technologies have been considered for the vessel in a separate appendix.

## ASSUMPTIONS

The Technology Screening is based on data provided by Spliethoff's Bevrachtungskantoor B.V. to Njord.

Equipment and installation prices are based on average figures from recent projects, and includes all-in costs (equipment, logistics, and installation). Final prices will depend on the specific project, volume, and negotiations.

The saving potential is divided across two technology categories:

**Direct Savings Technologies (DS)** directly impact vessel performance post-installation and may influence EEXI.


**Enabled Savings Technologies (ES)** improve technical and/or operational efficiency.

The following bunker prices have been considered for the cost calculation:

HFO – 406 USD/MT

MGO – 652 USD/MT

EU Carbon Price – 82.00 USD/MT



# VESSEL PARTICULARS

## General Information of Vessel

Vessel Name	Happy Diamond
IMO Number	9551947
Vessel Owner	Spliethoff's Bevrachtingskantoor B.V.
Commercial Manager	BigLift Shipping B.V.
Technical Manager	BigLift Shipping B.V.
Vessel Type	Heavy lift general cargo with container capacity
Build Year	2011
Flag	NLD
Classification Society	LR
Gross Tonnage	14784
Dead Weight	18148
Next Drydock Scheduled Date	October 2025

Machinery Details	
Main Engine: Type and Make	Wartsila W8L46C
Main Engine: No. of Engines	1
Main Engine: Max Power	8400
Main Engine: Max RPM	500
Main Engine: Power Limitations	abt 85% from MCR(not because of EEXI)
Auxiliary Engine: Type and Make	MITSUBISHI HEAVY INDUSTRIES, LTD. S6R2-MPTKF
Auxiliary Engine: No. of Engines	4
Auxiliary Engine: Max Power	490
Boiler: Type and Make	Heatmaster THH1250
Boiler: Capacity	1250kW
Hull: Antifouling Paint Specification and Paint Name	Jotun Seaforce I shield
Ballast Water Treatment System. Make and model	Panasia model Glo-Patrol 750m3/hr
Loading Computer. Make and model	Seasafe (Gstab3)
Scrubber/EGCS? If yes, Make, Model and Type (Open or Closed Loop)	Ecospray ECO-EGC open loop system

Consumption	
Annual Main Engine Consumption	3835 HFO / 620 LSMGO
Annual Auxiliary Engines Consumption	416 LSMGO
Annual Boiler Consumption	87 LSMGO
Annual "Other" Consumption	11 LSMGO





Operation Profile	
No. of Days Ballast in 1 year	43
No. of Days Laden in 1 year	136
No. of Days Idle/Load port in 1 year	109
No. of Days discharging in 1 year	61
General trade route of the vessel (voyages and ports/topography)	Worldwide
Total Annual Distance (365 days)	59755 NM

Existing Energy saving devices and Equipment	
Main Engine	Power control CPP, running constant RPM
Hull	none
Auxiliary Engines	none
Boiler	no, only alarm when dump cooler and boiler are active same time
Others	Shaft Generator
Voyage Planning	SPOS / One Ocean
Is Auto Logging available on the vessel?	Spliethoff Datacollector
Are Mass Flow Meters installed? If yes, which are the consumers?	Main engine VAF J5025PT2Aux / boiler VAF J5025PT2
Is BWTS Installed? if yes, type and capacity	Yes see above
Is the vessels installed with a scrubber? if yes, please specify Open Loop / Closed Loop	Yes see above
Which consumers are covered by the scrubber? example ME, Auxiliary Engines, Boiler	Main engine
kWHr meter available?	no
Shaft Power Meter available?	Installed but needs service (incorrect data)
Economisers (EGB) fitted on AEs and ME?	Main engine only
Are VFDs installed? If YES, which all equipment are covered?	For spray pumps scrubber and for Dilution pump for steering gear 2 pcs for pumps
Other Machinery Details where ESDs applicable (e.g. Cargo plant for Gas Carriers)	not applicable
Make and Model of Loading software onboard	Seasafe (Gstab3)

Any other information	
-----------------------	--



# BUSINESS CASE

## ANNUAL SAVINGS POTENTIAL OF THE TECHNOLOGIES CONSIDERED

Savings potential

**13.7%**

MT CO<sub>2</sub> per year savings

**2,159**

MT Fuel savings

**683**

Main Engine

**631**

Aux Engine

**50**

Other

**2**

A total of 8 technologies have been used out of which 4 are of direct saving category and 4 are enabled savings.

2 technologies will have impact on EEXI value, and 8 technologies will have impact on CII ratings

## FINANCIALS FOR THE TECHNOLOGIES CONSIDERED

Return of investment (years)

**2.89**

Total investment USD

**902,000**

Yearly bunker savings USD

**311,594**

Bunker prices, as mentioned in the assumption section of this report, has been considered for calculation of yearly bunker savings and return on investment.





# REGULATORY IMPACT

## EU-ETS IMPACT

Return Of Investment (Years)

# 2.36

Total investment USD

# 902,000

Yearly bunker savings of USD

# 311,594

The vessel is found to be trading less than 40 % in the EU region. We have considered for reference assuming 40% of the vessel trades in the EU region.

Estimated savings from EU ETS CO<sub>2</sub> for the years:

- 2026 (100%)

The carbon credits price is taken as 82.00 USD/ CO<sub>2</sub>-MT

# 70,829 USD

The amended return on investment stated above takes into consideration the amount of EU carbon tax saved by applying the technologies suggested over 1 years only. Any additional EU trading beyond this point will improve the business case further.



## FUELEU MARITIME IMPACT

Existing penalty – 117,850 \$  
Penalty post ESD – 101,704 \$  
Savings – 16,146 \$

Return Of Investment (Years)

# 2.26

Total investment USD

# 902,000

Yearly bunker savings of USD

# 311,594

For reference, we assumed that 40% of the vessel trades were in the EU region, based on last five year average.

Total savings towards FuelEU:

# 16,146 USD

The amended return on investment stated above takes into consideration the amount of FuelEU Penalty savings and the EU carbon tax saved by applying the technologies suggested over one year only. Any additional EU trading beyond this point will improve the business case further.

The FuelEU maritime regulation sets the limit on the GHG intensity of energy used on board in the EU and imposes a penalty if a vessel's GHG intensity goes beyond the prescribed limit. Thus, the regulation promotes the use of shore power, certified renewable, and low-carbon fuels without recommending any particular type of fuel.



## CII IMPACT







Year	2025	2026	2027	2028	2029	2030
Required CII	11.85	11.59	11.25	10.91	10.57	10.23
CII Rating	E	E	E	E	E	E
Corrected Rating- NJORD ESD	D	D	D	E	E	E

1. Annual Efficiency Ratio (AER) and CII Ratings are calculated on basis of submitted IMO DCS data for the year 2025 and as per MEPC. 78
2. Operational profile of vessel for the following years is assumed to be same as 2025 and after adoption of Njord EET the Deadweight remains unchanged.
3. After applying the suggested Njord EET package, improvement in savings rate is observed. It remains in 'D' till 2027 from "E" the current rating.





# BASIC TECHNOLOGIES

\*The savings ranges stated in this table showcases how technologies will perform on respective machinery (Main Engine/Auxiliary Engine/Boiler) if installed individually.

Technology		Description	Savings Category	Regulatory Impact EEXI/CII	Install in Drydock / Service	Savings Range %	Cost Range (USD)
	Main Engine Lube Oil Fine Filters	Filtering engine oil instead of purification in a separator saves on separator running costs and lube oil replenishing intervals and eases the operation.	ES	CII	Both	0.2-0.8	20K-40K
	Propeller Fouling Protection - Ultrasound for Propeller	Ultrasonic propeller antifouling system. This device emits ultrasonic waves through the shaft to prevent marine growth on the propeller blades. As it's a preventive system, installation must begin with a clean propeller surface.	DS	CII	Both	0.5-1.0	25K-35K
	Auto Pilot Upgrade	Updated autopilot includes unique algorithms that ensure highly precise steering performance where it is needed, even at low speed	ES	CII	Both	1.0 -2.0	20-30k
	RPM & PITCH Optimisation	RPM and Pitch Optimization systems adjust engine speed and propeller pitch in real time using optimized combinator curves. This helps maintain consistent power and speed throughout a voyage, improving fuel efficiency and overall propulsion performance.	ES	CII and EEXI	Both	8-10	150K-200K
	Flow Stream Duct	A pre-swirl hydrodynamic device to improve the flow into the propeller by creating a swirl in the opposite direction of the propeller's rotation, the device helps to straighten the wake and reduce rotational losses.	DS	CII and EEXI	Drydock	2.0 - 3.0	230K-280K
	Variable Frequency Drives	Variable frequency drives enable capacity control of pumps and fans, instead of on/off operation. These drives operate autonomously by sensing the running parameters of the engine. and system load.	DS	CII	Both	1.2-2.0	180K-220K



Technology		Description	Savings Category	Regulatory Impact EEXI/CII	Install in Drydock / Service	Savings Range %	Cost Range (USD)
	LED	LED lights with low power consumption on AE have a longer running range and are a direct savings.	DS	CII	Both	0.4-1.0	40K-60K
	Auxiliary Engine Lube Oil Fine Filters	Filtering of engine oil instead of purification in a separator. This saves on separator running costs and lube oil replenishing intervals and eases the operation.	ES	CII	Both	0.4-1.0	80K-120K



# NEXT STEP - NJORD'S SOLUTION DESIGN

Get a detailed verification of each technology in scope, and have a tailor-made installation guide, ready to execute.

## NJORD'S SOLUTION DESIGN INCLUDES THE FOLLOWING:

- Confirmation of consumption profiles
- Confirmation of fuel savings per technology
- EEXI and CII impact analysis per technology
- Alignment and retrieval of CFD calculations from suppliers (if required, at cost)
- Recommendations for which supplier to choose per technology
- Determination of cost per technology (including and split in logistics, equipment, and installation costs)
- Performance studies for selected relevant technologies

## WE PARTNER WITH THE LEADING TECHNOLOGY PROVIDERS

to design systems custom made for your vessels. Get to know how this will impact on the existing vessel performance.

**THROUGH OUR SOLUTION DESIGN**, we provide you with the clarity and guidance you need to reduce emissions, comply with regulations, and save fuel.



**OUR TEAM OF INDUSTRY EXPERTS ANALYSE THE SYSTEMS ON THE VESSEL** and find the best suited technology and tailor fit it to the existing environment on board!

When we design solutions, we deep dive into actual operational and consumption profiles in the last 365 days to scope out the best possible fit.

[READ MORE ABOUT SOLUTION DESIGN HERE](#)

**BREAKDOWN OF SAVINGS, COSTS, AND PAYBACK TIME FOR INDIVIDUAL TECHNOLOGIES**

**DETAILED ANALYSIS OF EVERY TECHNOLOGY AND HOW IT AFFECTS**



**Yogesh Yadav**

Technical Solutions Manager  
+91 84258 25510  
yogesh.yadav@njordsolution.com

**Maersk Tankers A/S**

Holmbladsgade 133  
2300 Copenhagen S, Denmark  
www.njordsolution.com

Powered by

