



Titan	Feet	Meters
Maximum Height	28ft 6in	8.7 m
Lowest position	-14 ft	-4.3 m
Maximum travel (from sub floor)	42.5 ft	13 m
Maximum reach (from rotate centre)	29ft 6in	9 m
Maximum reach (from turret)	28 ft	8.5 m

## Rig Dimensions

Lowest Travel Height	7ft 10in	2.4 m
Lowest Rig Height (on Track)	8ft 2in	2.5 m
Base Width	4ft 3in	1.3 m
Shortest Rig Length	15ft 9in	4.8 m

Axis	Range of Travel	Maximum Speeds
Track	As required in 10ft lengths	6ft (2m)
Rotate	Unlimited	30 degrees
Lift	+/- 45 degrees	24 degrees
Arm Extend	22.5 feet (6.9m)	6ft (2m)
Outer Arm	225 degrees	40 degrees
Pan	Unlimited	120 degrees

CAMERACONTROL

Tilt	290 degrees	120 degrees
Roll	Unlimited	120 degrees

Weights	Pounds	Kilograms
Bolt Rig	948 lb	430 kg
Precision Track (10ft / 3m length per piece)	200 lb	90 kg
Power Supply	133 lb	60 kg
Flair Console Flight Case	60 lb	27 kg
Counter Weights	1235 lb	560 kg
Maximum Camera Payload	61 lb	28 kg

## Power Requirements

Stage	120/208
Generator	5 Wire

CAMERACONTROL