



SPX
ROAD / WIDENER™



The Midland SPX Road Widener® has more productivity, maneuverability, safety, and features than any other road widener on the market, period.

The **SPX** builds on the proven SPD-10 platform, delivering the same horsepower, reach, and high-production performance, now enhanced with All-Wheel Drive and All-Wheel Steer technology. Designed for contractors who demand total control, the SPX provides superior traction and maneuverability in any jobsite condition.

What truly sets the SPX apart is its steering versatility. Operators can select Front-Wheel Steer, All-Wheel Steer, or Crab Steer for unmatched positioning and control along the pavement edge. Combined with All-Wheel Drive traction, the SPX delivers stability, visibility, and confidence where other machines fall short.

With the ability to reach 10 ft. beyond the mainline pavement, the SPX makes fast, precise work of shoulder construction above or below grade. Its modular spreader blade quickly adjusts to match project width requirements, making it ideal for both large highway projects and tight-access applications. An 18-inch chain-driven conveyor placing 450+ tons per hour ensures maximum productivity while maintaining accurate material placement.

SPX ROAD / WIDENER™



**PATENT-PENDING HYDRAULIC
PUSH BLADE**



**MARKET-LEADING OPERATOR
CONTROL & VISIBILITY**



10' MAX SPREAD WIDTH



100HP DIESEL ENGINE



FULL-TIME AWD



3.0 CUBIC YARD HOPPER



RIGHT OR LEFT SPREAD



ALL-WHEEL STEER



DUAL BLADE AND COLUMN



450+ TONS PER HOUR



VARIABLE SPEED CONVEYOR

MACHINE SPECS

OVERALL LENGTH	20 FT. 7 IN.
OVERALL WIDTH	11 FT. 11 IN.
OVERALL HEIGHT	8 FT. 3 IN.
INSIDE TURNING RADIUS	15 FT. 8 IN.
WHEELBASE	117 IN.
TRACK WIDTH	80 IN. FRONT 80 IN. REAR

