

[Products ▾](#)[Industries](#)[The company](#)[Catalog](#)[Contact us](#) [+49 9341 848 5500](#)[Products](#) > [Hose lines](#) > [Dryer hoses](#)

SIL | CFX® | S5AS-SR1

FACTS

- + Silicone hose, single layer
- + Flexible hose for hot and cold gases
- + Cord as reinforcement
- + Spring steel wire in the wall
- + Temperature range: -70°C to 260°C, briefly up to 280°C



DOWNLOADS

[Dryer hoses \(DE\)](#)[Dryer hoses \(EN\)](#)

Article no.	Ø mm	WS mm	L m
S5AS-SR1-0022-04	22,0	1,0	4,0
S5AS-SR1-0025-04	25,0	2,0	4,0
S5AS-SR1-0032-04	32,0	1,5	4,0
S5AS-SR1-0038-04	38,0	2,0	4,0
S5AS-SR1-0050-04	50,0	2,5	4,0
S5AS-SR1-0063-04	63,0	2,0	4,0
S5AS-SR1-0070-04	70,0	2,0	4,0
S5AS-SR1-0076-04	76,0	2,0	4,0
S5AS-SR1-0080-04	80,0	2,0	4,0
S5AS-SR1-0083-04	83,0	2,0	4,0
S5AS-SR1-0102-04	102,0	2,0	4,0
S5AS-SR1-0127-04	127,0	2,5	4,0
S5AS-SR1-0152-04	152,0	2,5	4,0
S5AS-SR1-0203-04	203,0	2,5	4,0

SIL | CFX® | S5AS-SR2

FACTS

- + Silicone hose, double-layered
- + Flexible hose for hot and cold gases
- + Cord as reinforcement
- + Spring steel wire in the wall
- + Temperature range: -70°C to 260°C, briefly up to 280°C



DOWNLOADS

[Dryer hoses \(DE\)](#)

Article no.	Ø mm	WS mm	L m
S5AS-SR2-0022-04	22,0	1,5	4,0
S5AS-SR2-0025-04	25,0	2,5	4,0
S5AS-SR2-0032-04	32,0	2,0	4,0
S5AS-SR2-0038-04	38,0	2,5	4,0
S5AS-SR2-0045-04	45,0	2,0	4,0
S5AS-SR2-0050-04	50,0	3,0	4,0
S5AS-SR2-0063-04	63,0	2,5	4,0
S5AS-SR2-0070-04	70,0	2,5	4,0
S5AS-SR2-0076-04	76,0	2,5	4,0
S5AS-SR2-0080-04	80,0	2,5	4,0
S5AS-SR2-0083-04	83,0	2,5	4,0
S5AS-SR2-0102-04	102,0	2,5	4,0
S5AS-SR2-0121-04	121,0	3,0	4,0
S5AS-SR2-0127-04	127,0	3,0	4,0
S5AS-SR2-0152-04	152,0	3,0	4,0
S5AS-SR2-0160-04	160,0	3,0	4,0
S5AS-SR2-0203-04	203,0	3,0	4,0

SIL | CFX® | S7AS-NE1

FACTS

- + Neoprene tube, single layer
- + Flexible hose for hot and cold gases
- + Cord as reinforcement
- + Spring steel wire in the wall
- + Temperature range: -35°C to 135°C, briefly up to 150°C



DOWNLOADS

Article no.	Ø mm	WS mm	L m
S7AS-NE1-0220-04	22,0	1,0	4,0
S7AS-NE1-0250-04	25,0	2,0	4,0
S7AS-NE1-0320-04	32,0	1,5	4,0
S7AS-NE1-0380-04	38,0	2,0	4,0
S7AS-NE1-0500-04	50,0	2,0	4,0
S7AS-NE1-0630-04	63,0	2,0	4,0
S7AS-NE1-0760-04	76,0	2,0	4,0
S7AS-NE1-0800-04	80,0	2,0	4,0
S7AS-NE1-1020-04	102,0	2,0	4,0
S7AS-NE1-1270-04	127,0	2,5	4,0
S7AS-NE1-1520-04	152,0	2,5	4,0
S7AS-NE1-2000-04	200,0	2,5	4,0

SIL | CFX® | S7AS-NE2

FACTS

- + Neoprene tube, double-layered
- + Flexible hose for hot and cold gases
- + Cord as reinforcement
- + Spring steel wire in the wall
- + Temperature range: -35°C to 135°C, briefly up to 150°C



DOWNLOADS

-  [Dryer hoses \(DE\)](#)
-  [Dryer hoses \(EN\)](#)

Article no.	Ø mm	WS mm	L m
S7AS-NE2-0220-04	22,0	1,5	4,0
S7AS-NE2-0250-04	25,0	2,5	4,0
S7AS-NE2-0320-04	32,0	2,0	4,0
S7AS-NE2-0380-04	38,0	2,5	4,0
S7AS-NE2-0500-04	50,0	2,5	4,0
S7AS-NE2-0630-04	63,0	2,5	4,0
S7AS-NE2-0760-04	76,0	2,5	4,0
S7AS-NE2-0800-04	80,0	2,5	4,0
S7AS-NE2-1020-04	102,0	2,5	4,0
S7AS-NE2-1270-04	127,0	3,0	4,0
S7AS-NE2-1520-04	152,0	3,0	4,0
S7AS-NE2-2000-04	200,0	3,0	4,0

[Products](#) > [Hose lines](#) > [Dryer hoses](#)



Products

Round tubes	Pipe bend
Tube fittings	Pipe connector
Pipe couplings	Hose lines

Michel Tube Engineering GmbH

Industriepark A81
Falk-Müller-Straße 30
97941 Tauberbischofsheim

info@michel-tube.com

Tel.: +49 9341 848 550-0
Fax: +49 9341 848 550-5



Hose couplings

Material distributor

Magnetic separator

Coded labeling

Suction lances

System components

Industries

The company

Catalog

Contact us

