


Products > Pipe couplings > Strain relief

PURE STRAIN RELIEF 350MM

FACTS

- + Material: Galvanized steel / stainless steel 1.4301
- + For pipe couplings with overall length 150 / 200 mm
- + Strain relief for axial tensile forces
- + Can also be retrofitted



DOWNLOADS

 Strain relief (EN)

 Strain relief (EN)

Galvanized steel | 350 mm

Article no.	Ø [mm]	L mm
RV3S-0650-0650-150-ZL	65,0	350
RV3S-0700-0700-150-ZL	70,0	350
RV3S-0761-0761-150-ZL	76,1	350
RV3S-0800-0800-150-ZL	80,0	350
RV3S-0840-0840-150-ZL	84,0	350
RV3S-0850-0850-150-ZL	85,0	350
RV3S-0889-0889-150-ZL	88,9	350
RV3S-0950-0950-150-ZL	95,0	350
RV3S-1000-1000-150-ZL	100,0	350
RV3S-1016-1016-150-ZL	101,6	350
RV3S-1040-1040-150-ZL	104,0	350
RV3S-1080-1080-150-ZL	108,0	350
RV3S-1100-1100-150-ZL	110,0	350
RV3S-1143-1143-150-ZL	114,3	350
RV3S-1200-1200-150-ZL	120,0	350
RV3S-1250-1250-150-ZL	125,0	350
RV3S-1270-1270-150-ZL	127,0	350
RV3S-1290-1290-150-ZL	129,0	350

PURE STRAIN RELIEF 400MM

FACTS

- + Material: Galvanized steel / stainless steel 1.4301
- + For pipe couplings with overall length 150 / 200 mm
- + Strain relief for axial tensile forces



+ Can also be retrofitted



Galvanized steel | 400 mm (up to Ø150.0 mm)

Article no.	Ø [mm]	L mm
RV3S-0650-0650-200-ZL	65,0	400
RV3S-0700-0700-200-ZL	70,0	400
RV3S-0761-0761-200-ZL	76,1	400
RV3S-0800-0800-200-ZL	80,0	400
RV3S-0840-0840-200-ZL	84,0	400
RV3S-0850-0850-200-ZL	85,0	400
RV3S-0889-0889-200-ZL	88,9	400
RV3S-0950-0950-200-ZL	95,0	400
RV3S-1000-1000-200-ZL	100,0	400
RV3S-1016-1016-200-ZL	101,6	400
RV3S-1040-1040-200-ZL	104,0	400
RV3S-1080-1080-200-ZL	108,0	400
RV3S-1100-1100-200-ZL	110,0	400
RV3S-1143-1143-200-ZL	114,3	400
RV3S-1200-1200-200-ZL	120,0	400
RV3S-1250-1250-200-ZL	125,0	400
RV3S-1270-1270-200-ZL	127,0	400
RV3S-1290-1290-200-ZL	129,0	400
RV3S-1330-1330-200-ZL	133,0	400
RV3S-1350-1350-200-ZL	135,0	400
RV3S-1397-1397-200-ZL	139,7	400
RV3S-1460-1460-200-ZL	146,0	400
RV3S-1500-1500-200-ZL	150,0	400

Galvanized steel | 400 mm (from Ø150.0 mm)

Article no.	Ø [mm]	L mm
RV3S-1520-1520-200-ZL	152,0	400
RV3S-1550-1550-200-ZL	155,0	400
RV3S-1590-1590-200-ZL	159,0	400
RV3S-1683-1683-200-ZL	168,3	400
RV3S-1740-1740-200-ZL	174,0	400
RV3S-1800-1800-200-ZL	180,0	400
RV3S-1910-1910-200-ZL	191,0	400
RV3S-1930-1930-200-ZL	193,0	400
RV3S-2000-2000-200-ZL	200,0	400
RV3S-2040-2040-200-ZL	204,0	400
RV3S-2100-2100-200-ZL	210,0	400
RV3S-2190-2190-200-ZL	219,0	400
RV3S-2300-2300-200-ZL	230,0	400
RV3S-2500-2500-200-ZL	250,0	400
RV3S-2600-2600-200-ZL	260,0	400
RV3S-2660-2660-200-ZL	266,0	400
RV3S-2730-2730-200-ZL	273,0	400
RV3S-2800-2800-200-ZL	280,0	400

We recommend the use of strain reliefs in the event of pressure surges or for mechanical stabilization and support of the pipes. As pipe couplings only have a sealing function, we generally recommend the use of strain reliefs to additionally secure the pipes. The strain relief consists of special half shells that are connected to each other by a load distribution element.

PICTURE GALLERY



[Products](#) > [Pipe couplings](#) > [Strain relief](#)



pipes | bends | couplings

Michel Tube Engineering GmbH

Industriepark A81
Falk-Müller-Straße 30
97941 Tauberbischofsheim

info@michel-tube.com

Tel.: +49 9341 848 550-0

Fax: +49 9341 848 550-5



Products

Round tubes	Pipe bend
Tube fittings	Pipe connector
Pipe couplings	Hose lines
Hose couplings	Coded labeling
Material distributor	Suction lances
Magnetic separator	System components

Industries

The company

Catalog

Contact us

