

Standard Tube Connectors

Lightweight clamping connectors with a sealing insert for vacuum and suction conveying. Each pipe end is inserted halfway into the connector and clamped using two screws. A grounding strap carries electrical charges across the connection.

Standard | Metal / Metal



- + Material: Stainless steel 1.4510 / 1.4016
- + Lightweight design for vacuum conveying
- + For connecting stainless steel pipes

Stainless steel | 100 mm - 2 screws M8

Article No.	Ø [mm]	Connection	Max. Temp.
RV1S-0380-0380-100-SW	38.0	Metal / Metal	80 °C
RV1S-0400-0400-100-SW	40.0	Metal / Metal	80 °C
RV1S-0450-0450-100-SW	45.0	Metal / Metal	80 °C
RV1S-0500-0500-100-SW	50.0	Metal / Metal	80 °C
RV1S-0540-0540-100-SW	54.0	Metal / Metal	80 °C
RV1S-0603-0603-100-SW	60.3	Metal / Metal	80 °C
RV1S-0650-0650-100-SW	65.0	Metal / Metal	80 °C
RV1S-0761-0761-100-SW	76.1	Metal / Metal	80 °C
RV1S-0800-0800-100-SW	80.0	Metal / Metal	80 °C
RV1S-0840-0840-100-SW	84.0	Metal / Metal	80 °C
RV1S-0889-0889-100-SW	88.9	Metal / Metal	80 °C
RV1S-1016-1016-100-SW	101.6	Metal / Metal	80 °C
RV1S-1040-1040-100-SW	104.0	Metal / Metal	80 °C
RV1S-1080-1080-100-SW	108.0	Metal / Metal	80 °C
RV1S-1100-1100-100-SW	110.0	Metal / Metal	80 °C
RV1S-1143-1143-100-SW	114.3	Metal / Metal	80 °C

Open product page

en.michel-tube.com/rohrverbinder-standard



Standard Tube Connectors

Standard | Glass / Metal and Glass / Glass



- + Material: Stainless steel 1.4510 / 1.4016
- + Lightweight design for vacuum conveying
- + For connecting glass and stainless steel pipes

Stainless steel | 100 mm - 2 screws M8

Article No.	Ø [mm]	Connection	Max. Temp.
RV1G-0470-0400-100-SW	47.0 / 40.0	Glass / Metal	80 °C
RV1G-0470-0470-100-SW	47.0 / 47.0	Glass / Glass	80 °C
RV1G-0483-0450-100-SW	48.3 / 45.0	Glass / Metal	80 °C
RV1G-0483-0483-100-SW	48.3 / 48.3	Glass / Glass	80 °C
RV1G-0540-0500-100-SW	54.0 / 50.0	Glass / Metal	80 °C
RV1G-0540-0540-100-SW	54.0 / 54.0	Glass / Glass	80 °C
RV1G-0560-0500-100-SW	56.0 / 50.0	Glass / Metal	80 °C
RV1G-0560-0560-100-SW	56.0 / 56.0	Glass / Glass	80 °C
RV1G-0650-0603-100-SW	65.0 / 60.3	Glass / Metal	80 °C
RV1G-0650-0650-100-SW	65.0 / 65.0	Glass / Glass	80 °C
RV1G-0660-0603-100-SW	66.0 / 60.3	Glass / Metal	80 °C
RV1G-0660-0660-100-SW	66.0 / 66.0	Glass / Glass	80 °C
RV1G-0800-0761-100-SW	80.0 / 76.1	Glass / Metal	80 °C
RV1G-0800-0800-100-SW	80.0 / 80.0	Glass / Glass	80 °C

Open product page

en.michel-tube.com/rohrverbinder-standard

