

# Galvanized Steel Pipe Couplings

Heavy-duty pipe couplings for pressure conveying, for example at outdoor silos. Available lengths are 150 and 200 mm. The couplings seal the pipe joint; Michel Tube recommends additional strain relief to secure it against axial forces caused by pressure surges.

## Galvanized Steel | 150 mm, 3 Screws



- + Material: Galvanized steel / Aluminum
- + Heavy-duty design for pressure conveying
- + With double inner jacket and grounding strap

| Article No.           | Ø [mm] | Seal                  | Max. Temp. |
|-----------------------|--------|-----------------------|------------|
| RV3S-0650-0650-150-WE | 65.0   | NR/SBR, light-colored | 80 °C      |
| RV3S-0700-0700-150-WE | 70.0   | NR/SBR, light-colored | 80 °C      |
| RV3S-0761-0761-150-WE | 76.1   | NR/SBR, light-colored | 80 °C      |
| RV3S-0800-0800-150-WE | 80.0   | NR/SBR, light-colored | 80 °C      |
| RV3S-0840-0840-150-WE | 84.0   | NR/SBR, light-colored | 80 °C      |
| RV3S-0850-0850-150-WE | 85.0   | NR/SBR, light-colored | 80 °C      |
| RV3S-0889-0889-150-WE | 88.9   | NR/SBR, light-colored | 80 °C      |
| RV3S-0950-0950-150-WE | 95.0   | NR/SBR, light-colored | 80 °C      |
| RV3S-1000-1000-150-WE | 100.0  | NR/SBR, light-colored | 80 °C      |
| RV3S-1016-1016-150-WE | 101.6  | NR/SBR, light-colored | 80 °C      |
| RV3S-1040-1040-150-WE | 104.0  | NR/SBR, light-colored | 80 °C      |
| RV3S-1080-1080-150-WE | 108.0  | NR/SBR, light-colored | 80 °C      |
| RV3S-1100-1100-150-WE | 110.0  | NR/SBR, light-colored | 80 °C      |
| RV3S-1143-1143-150-WE | 114.3  | NR/SBR, light-colored | 80 °C      |
| RV3S-1200-1200-150-WE | 120.0  | NR/SBR, light-colored | 80 °C      |
| RV3S-1250-1250-150-WE | 125.0  | NR/SBR, light-colored | 80 °C      |
| RV3S-1270-1270-150-WE | 127.0  | NR/SBR, light-colored | 80 °C      |
| RV3S-1290-1290-150-WE | 129.0  | NR/SBR, light-colored | 80 °C      |

**Open product page**

[en.michel-tube.com/rohrkupplung-stahl-verzinkt](https://en.michel-tube.com/rohrkupplung-stahl-verzinkt)



# Galvanized Steel Pipe Couplings

## Galvanized Steel | 200 mm, 4 Screws



- + Material: Galvanized steel / Aluminum
- + Heavy-duty design for pressure conveying
- + With double inner jacket and grounding strap

| Article No.           | Ø [mm] | Seal                  | Max. Temp. |
|-----------------------|--------|-----------------------|------------|
| RV3S-0650-0650-200-WE | 65.0   | NR/SBR, light-colored | 80 °C      |
| RV3S-0700-0700-200-WE | 70.0   | NR/SBR, light-colored | 80 °C      |
| RV3S-0761-0761-200-WE | 76.1   | NR/SBR, light-colored | 80 °C      |
| RV3S-0800-0800-200-WE | 80.0   | NR/SBR, light-colored | 80 °C      |
| RV3S-0840-0840-200-WE | 84.0   | NR/SBR, light-colored | 80 °C      |
| RV3S-0850-0850-200-WE | 85.0   | NR/SBR, light-colored | 80 °C      |
| RV3S-0889-0889-200-WE | 88.9   | NR/SBR, light-colored | 80 °C      |
| RV3S-0950-0950-200-WE | 95.0   | NR/SBR, light-colored | 80 °C      |
| RV3S-1000-1000-200-WE | 100.0  | NR/SBR, light-colored | 80 °C      |
| RV3S-1016-1016-200-WE | 101.6  | NR/SBR, light-colored | 80 °C      |
| RV3S-1040-1040-200-WE | 104.0  | NR/SBR, light-colored | 80 °C      |
| RV3S-1080-1080-200-WE | 108.0  | NR/SBR, light-colored | 80 °C      |
| RV3S-1100-1100-200-WE | 110.0  | NR/SBR, light-colored | 80 °C      |
| RV3S-1143-1143-200-WE | 114.3  | NR/SBR, light-colored | 80 °C      |
| RV3S-1200-1200-200-WE | 120.0  | NR/SBR, light-colored | 80 °C      |
| RV3S-1250-1250-200-WE | 125.0  | NR/SBR, light-colored | 80 °C      |
| RV3S-1270-1270-200-WE | 127.0  | NR/SBR, light-colored | 80 °C      |
| RV3S-1290-1290-200-WE | 129.0  | NR/SBR, light-colored | 80 °C      |
| RV3S-1330-1330-200-WE | 133.0  | NR/SBR, light-colored | 80 °C      |
| RV3S-1350-1350-200-WE | 135.0  | NR/SBR, light-colored | 80 °C      |
| RV3S-1397-1397-200-WE | 139.7  | NR/SBR, light-colored | 80 °C      |

**Open product page**

[en.michel-tube.com/rohrkupplung-stahl-verzinkt](https://en.michel-tube.com/rohrkupplung-stahl-verzinkt)



# Galvanized Steel Pipe Couplings

| Article No.           | Ø [mm] | Seal                  | Max. Temp. |
|-----------------------|--------|-----------------------|------------|
| RV3S-1460-1460-200-WE | 146.0  | NR/SBR, light-colored | 80 °C      |
| RV3S-1500-1500-200-WE | 150.0  | NR/SBR, light-colored | 80 °C      |
| RV3S-1520-1520-200-WE | 152.0  | NR/SBR, light-colored | 80 °C      |
| RV3S-1550-1550-200-WE | 155.0  | NR/SBR, light-colored | 80 °C      |
| RV3S-1590-1590-200-WE | 159.0  | NR/SBR, light-colored | 80 °C      |
| RV3S-1683-1683-200-WE | 168.3  | NR/SBR, light-colored | 80 °C      |
| RV3S-1740-1740-200-WE | 174.0  | NR/SBR, light-colored | 80 °C      |
| RV3S-1800-1800-200-WE | 180.0  | NR/SBR, light-colored | 80 °C      |
| RV3S-1910-1910-200-WE | 191.0  | NR/SBR, light-colored | 80 °C      |
| RV3S-1930-1930-200-WE | 193.0  | NR/SBR, light-colored | 80 °C      |
| RV3S-2000-2000-200-WE | 200.0  | NR/SBR, light-colored | 80 °C      |
| RV3S-2040-2040-200-WE | 204.0  | NR/SBR, light-colored | 80 °C      |
| RV3S-2100-2100-200-WE | 210.0  | NR/SBR, light-colored | 80 °C      |
| RV3S-2190-2190-200-WE | 219.0  | NR/SBR, light-colored | 80 °C      |
| RV3S-2300-2300-200-WE | 230.0  | NR/SBR, light-colored | 80 °C      |
| RV3S-2500-2500-200-WE | 250.0  | NR/SBR, light-colored | 80 °C      |
| RV3S-2600-2600-200-WE | 260.0  | NR/SBR, light-colored | 80 °C      |
| RV3S-2660-2660-200-WE | 266.0  | NR/SBR, light-colored | 80 °C      |
| RV3S-2730-2730-200-WE | 273.0  | NR/SBR, light-colored | 80 °C      |
| RV3S-2800-2800-200-WE | 280.0  | NR/SBR, light-colored | 80 °C      |

**Open product page**

[en.michel-tube.com/rohrkupplung-stahl-verzinkt](https://en.michel-tube.com/rohrkupplung-stahl-verzinkt)

