

Conveying Hoses

PUR hoses for conveying bulk materials and plastic granules. The range extends from medium-heavy to super-heavy versions for different abrasion loads. Hinged bolt clamps and worm-drive clamps complete the hose attachment options.

PUR | CFX® PUR 950 AS



- + Flexible conveying hose for abrasive bulk material / granules
- + Medium-heavy version, highly abrasion-resistant
- + Temperature range: -40°C to +90°C

Article No.	Ø [mm]	W.T. [mm]	L [m]
SOAS-PUR-0300-10	30.0	approx. 0.7	10.0
SOAS-PUR-0380-10	38.0	approx. 0.7	10.0
SOAS-PUR-0400-10	40.0	approx. 0.7	10.0
SOAS-PUR-0450-10	45.0	approx. 0.7	10.0
SOAS-PUR-0500-10	50.0	approx. 0.7	10.0
SOAS-PUR-0550-10	55.0	approx. 0.7	10.0
SOAS-PUR-0600-10	60.0	approx. 0.7	10.0
SOAS-PUR-0650-10	63.0-65.0	approx. 0.7	10.0
SOAS-PUR-0700-10	70.0	approx. 0.7	10.0
SOAS-PUR-0760-10	75.0-76.0	approx. 0.7	10.0
SOAS-PUR-0800-10	80.0	approx. 0.7	10.0
SOAS-PUR-0889-10	89.0-90.0	approx. 0.7	10.0
SOAS-PUR-1020-10	100.0-102.0	approx. 0.7	10.0
SOAS-PUR-1100-10	110.0	approx. 0.7	10.0

Open product page

en.michel-tube.com/foerderschlaeuche



Conveying Hoses

PUR | CFX[®] PUR 955 AS



- + Flexible conveying hose for abrasive bulk material / granules
- + Heavy-duty design, highly abrasion-resistant
- + Temperature range: -40°C to +90°C

Article No.	Ø [mm]	W.T. [mm]	L [m]
S1AS-PUR-0300-15	30.0	approx. 1.4 - 1.5	15
S1AS-PUR-0380-20	38.0	approx. 1.4 - 1.5	20
S1AS-PUR-0400-20	40.0	approx. 1.4 - 1.5	20
S1AS-PUR-0450-15	45.0	approx. 1.4 - 1.5	15
S1AS-PUR-0500-20	50.0	approx. 1.4 - 1.5	20
S1AS-PUR-0550-15	55.0	approx. 1.4 - 1.5	15
S1AS-PUR-0600-20	60.0	approx. 1.4 - 1.5	20
S1AS-PUR-0650-20	63.0-65.0	approx. 1.4 - 1.5	20
S1AS-PUR-0700-10	70.0	approx. 1.4 - 1.5	10
S1AS-PUR-0760-10	75.0-76.0	approx. 1.4 - 1.5	10
S1AS-PUR-0800-10	80.0	approx. 1.4 - 1.5	10
S1AS-PUR-0889-10	89.0-90.0	approx. 1.4 - 1.5	10
S1AS-PUR-1020-10	100.0-102.0	approx. 1.4 - 1.5	10
S1AS-PUR-1100-10	110.0	approx. 1.4 - 1.5	10
S1AS-PUR-1140-10	114.0-115.0	approx. 1.4 - 1.5	10

Open product page

en.michel-tube.com/foerderschlaeuche



Conveying Hoses

PUR | CFX[®] PUR 956 AS



- + Flexible conveying hose for extremely abrasive bulk material / granules
- + Super heavy-duty design, extremely abrasion-resistant
- + Temperature range: -40°C to +90°C

Article No.	Ø [mm]	W.T. [mm]	L [m]
S3AS-PUR-0320-10	32.0	approx. 2.0 - 2.5	10
S3AS-PUR-0380-10	38.0	approx. 2.0 - 2.5	10
S3AS-PUR-0400-10	40.0	approx. 2.0 - 2.5	10
S3AS-PUR-0450-10	45.0	approx. 2.0 - 2.5	10
S3AS-PUR-0500-10	50.0	approx. 2.0 - 2.5	10
S3AS-PUR-0550-10	55.0	approx. 2.0 - 2.5	10
S3AS-PUR-0600-10	60.0	approx. 2.0 - 2.5	10
S3AS-PUR-0650-10	65.0	approx. 2.0 - 2.5	10
S3AS-PUR-0700-10	70.0	approx. 2.0 - 2.5	10
S3AS-PUR-0760-10	76.0	approx. 2.0 - 2.5	10
S3AS-PUR-0800-10	80.0	approx. 2.0 - 2.5	10
S3AS-PUR-0900-10	90.0	approx. 2.0 - 2.5	10
S3AS-PUR-1000-10	100.0	approx. 2.0 - 2.5	10
S3AS-PUR-1020-10	102.0	approx. 2.0 - 2.5	10
S3AS-PUR-1100-10	110.0	approx. 2.0 - 2.5	10
S3AS-PUR-1150-10	115.0	approx. 2.0 - 2.5	10

Open product page

en.michel-tube.com/foerderschlaeuche



Conveying Hoses

Hinged Bolt Clamp



- + For securing medium-heavy to heavy hoses
- + Easy and quick to assemble
- + Material: Galvanized steel

Article No.	SB [mm]	BB [mm]
S-GB-SCHELLE-0360-0390	36.0 - 39.0	20
S-GB-SCHELLE-0400-0430	40.0 - 43.0	20
S-GB-SCHELLE-0440-0470	44.0 - 47.0	20
S-GB-SCHELLE-0480-0510	48.0 - 51.0	20
S-GB-SCHELLE-0520-0550	52.0 - 55.0	20
S-GB-SCHELLE-0560-0590	56.0 - 59.0	20
S-GB-SCHELLE-0590-0630	59.0 - 63.0	20
S-GB-SCHELLE-0640-0670	64.0 - 67.0	25
S-GB-SCHELLE-0680-0730	68.0 - 73.0	25
S-GB-SCHELLE-0730-0790	73.0 - 79.0	25
S-GB-SCHELLE-0800-0850	80.0 - 85.0	25
S-GB-SCHELLE-0860-0910	86.0 - 91.0	25
S-GB-SCHELLE-0980-1030	98.0 - 103.0	25
S-GB-SCHELLE-1040-1120	104.0 - 112.0	25
S-GB-SCHELLE-1130-1210	113.0 - 121.0	25
S-GB-SCHELLE-1220-1300	122.0 - 130.0	25

Open product page

en.michel-tube.com/foerderschlaeuche



Conveying Hoses

Worm-Drive Clamp



- + For securing lightweight hoses
- + Easy and quick to assemble
- + Material: Galvanized steel

Article No.	SB [mm]	BB [mm]
S-SG-SCHELLE-0300-W1	30.0 - 45.0	12
S-SG-SCHELLE-0400-W1	35.0 - 50.0	12
S-SG-SCHELLE-0500-W1	40.0 - 60.0	12
S-SG-SCHELLE-0600-W1	50.0 - 70.0	12
S-SG-SCHELLE-0650-W1	60.0 - 80.0	12
S-SG-SCHELLE-0760-W1	70.0 - 90.0	12
S-SG-SCHELLE-0890-W1	80.0 - 100.0	12

Open product page

en.michel-tube.com/foerderschlaeuche

