

Dryer Hoses

Flexible hoses for hot and cold gases at granule dryers. Single- and double-layer silicone and neoprene versions are available for different temperature ranges. Cord and spring steel wire reinforce the hose wall.

Silicone | CFX® S5AS-SR1, Single Layer



- + Silicone hose, single-layered
- + Flexible hose for hot and cold gases
- + Cord as reinforcement
- + Spring steel wire in the wall
- + Temperature range: -70°C to 260°C, briefly up to 280°C

Article No.	Ø [mm]	W.T. [mm]	L [m]
S5AS-SR1-0022-04	22.0	1.0	4.0
S5AS-SR1-0025-04	25.0	2.0	4.0
S5AS-SR1-0032-04	32.0	1.5	4.0
S5AS-SR1-0038-04	38.0	2.0	4.0
S5AS-SR1-0050-04	50.0	2.5	4.0
S5AS-SR1-0063-04	63.0	2.0	4.0
S5AS-SR1-0070-04	70.0	2.0	4.0
S5AS-SR1-0076-04	76.0	2.0	4.0
S5AS-SR1-0080-04	80.0	2.0	4.0
S5AS-SR1-0083-04	83.0	2.0	4.0
S5AS-SR1-0102-04	102.0	2.0	4.0
S5AS-SR1-0127-04	127.0	2.5	4.0
S5AS-SR1-0152-04	152.0	2.5	4.0
S5AS-SR1-0203-04	203.0	2.5	4.0

Open product page

en.michel-tube.com/trocknerschlauche



Dryer Hoses

Silicone | CFX® S5AS-SR2, Double Layer



- + Silicone hose, double-layered
- + Flexible hose for hot and cold gases
- + Cord as reinforcement
- + Spring steel wire in the wall
- + Temperature range: -70°C to 260°C, briefly up to 280°C

Article No.	Ø [mm]	W.T. [mm]	L [m]
S5AS-SR2-0022-04	22.0	1.5	4.0
S5AS-SR2-0025-04	25.0	2.5	4.0
S5AS-SR2-0032-04	32.0	2.0	4.0
S5AS-SR2-0038-04	38.0	2.5	4.0
S5AS-SR2-0045-04	45.0	2.0	4.0
S5AS-SR2-0050-04	50.0	3.0	4.0
S5AS-SR2-0063-04	63.0	2.5	4.0
S5AS-SR2-0070-04	70.0	2.5	4.0
S5AS-SR2-0076-04	76.0	2.5	4.0
S5AS-SR2-0080-04	80.0	2.5	4.0
S5AS-SR2-0083-04	83.0	2.5	4.0
S5AS-SR2-0102-04	102.0	2.5	4.0
S5AS-SR2-0121-04	121.0	3.0	4.0
S5AS-SR2-0127-04	127.0	3.0	4.0
S5AS-SR2-0152-04	152.0	3.0	4.0
S5AS-SR2-0160-04	160.0	3.0	4.0
S5AS-SR2-0203-04	203.0	3.0	4.0

Open product page

en.michel-tube.com/trocknerschlauche



Dryer Hoses

Neoprene | CFX® S7AS-NE1, Single Layer



- + Neoprene hose, single-layered
- + Flexible hose for hot and cold gases
- + Cord as reinforcement
- + Spring steel wire in the wall
- + Temperature range: -35°C to 135°C, briefly up to 150°C

Article No.	Ø [mm]	W.T. [mm]	L [m]
S7AS-NE1-0220-04	22.0	1.0	4.0
S7AS-NE1-0250-04	25.0	2.0	4.0
S7AS-NE1-0320-04	32.0	1.5	4.0
S7AS-NE1-0380-04	38.0	2.0	4.0
S7AS-NE1-0500-04	50.0	2.0	4.0
S7AS-NE1-0630-04	63.0	2.0	4.0
S7AS-NE1-0760-04	76.0	2.0	4.0
S7AS-NE1-0800-04	80.0	2.0	4.0
S7AS-NE1-1020-04	102.0	2.0	4.0
S7AS-NE1-1270-04	127.0	2.5	4.0
S7AS-NE1-1520-04	152.0	2.5	4.0
S7AS-NE1-2000-04	200.0	2.5	4.0

Open product page

en.michel-tube.com/trocknerschlauche



Dryer Hoses

Neoprene | CFX® S7AS-NE2, Double Layer



- + Neoprene hose, double-layered
- + Flexible hose for hot and cold gases
- + Cord as reinforcement
- + Spring steel wire in the wall
- + Temperature range: -35°C to 135°C, briefly up to 150°C

Article No.	Ø [mm]	W.T. [mm]	L [m]
S7AS-NE2-0220-04	22.0	1.5	4.0
S7AS-NE2-0250-04	25.0	2.5	4.0
S7AS-NE2-0320-04	32.0	2.0	4.0
S7AS-NE2-0380-04	38.0	2.5	4.0
S7AS-NE2-0500-04	50.0	2.5	4.0
S7AS-NE2-0630-04	63.0	2.5	4.0
S7AS-NE2-0760-04	76.0	2.5	4.0
S7AS-NE2-0800-04	80.0	2.5	4.0
S7AS-NE2-1020-04	102.0	2.5	4.0
S7AS-NE2-1270-04	127.0	3.0	4.0
S7AS-NE2-1520-04	152.0	3.0	4.0
S7AS-NE2-2000-04	200.0	3.0	4.0

Open product page

en.michel-tube.com/trocknerschlauche

