

Declaration of Performance Ydeevnedeklaration



Product Name: Roof step / Tagtrin

1: ID number:

186000, 186001, 186002, 186003, 16000G, 186001G, 186002G, 186001s-hv, 186002s-hv

2: Intended use

Access device for pitched roof of roof tiles eg. clay or concrete etc. NOT to be used as anchorpoints.

Class 1

3: Manufacturer / Fabrikant:

Mul10 Metal ApS

Gammelgårdvej 18, 7130 Juelsminde

4: System and Assessment and inspection of performance / system og kontrol af ydeevne:

AVCP System 3, Assessment and ongoing inspection are conducted by in house inspections

5: Harmonized standard / harmoniseret standard:

EN 516:2006

6: Notified body / bemyndiget organ:

Teknologisk Institut DK, NB 1235

Characteristics	Performance	Remarks
Mechanical strength - static load (class 1 according to 7.1)	Fulfills	
External fire resistance	Fulfills	Fire class A2-s1, d0

7: Additional information

Installation of roof steps dedicated for use on or with roof tiles, are made of 2.0mm (sideprofiles) and 3.0mm (steps) aluminum. The installation is done in accordance with the Installation Guide No. M001. Roof pitch min 15° - max 65°

Signed for the manufacturer and on behalf of:

Chris Eriksen, Adm. direktør Mul10 Metal ApS
Man. Director

11.09-2026