

X-SPLASH 7001D

X-SPLASH 7001D Microporous Coverall with Collar, Elastic Wrists and Ankles.



Key Features & Benefits:

- Breathable, Durable, Comfortable and affordable Microporous Coverall.
- Provides all day protection from particulates, some liquids and aerosols.
- Attached Collar, Elastic Wrists and Ankles.
- Zipper Closure and Surged Seams.
- Easy to don and doff.

Applications:	Industries:	Certifications/Ratings:
• Asbestos/Lead Abatement • Spill Containment • Mold Remediation • Food Processing • Pesticides	• Pharmaceutical • Agriculture • Environmental • Sanitation • Construction	• ASTM D5034-21 (Grab Method) -Warp/Length lbf 20.6 -Weft/Width lbf 14.0
		• ASTM D5733-99 -Warp/Length lbf 10.00 -Weft/Width lbf 14.0
Ordering:	Composition:	Certifications/Ratings:
• Unit of Sale: 1 cs • Case Pack: 25 ea • Country of Origin: Bangladesh • Available Sizes: SM -5XL	• 100% Microporous	• ASTM D3776/D3776M-20, OPT C -Weight oz/yd² 1.42 -Weight oz/yd² 48.2
	 Warning: Cancer & Reproductive Harm- www.P65Warnings.ca.gov	• EN 1149-5:2018, CLAUSE 4.2.1 -Electrostatic Material Requirements -

X-SPLASH 7001D

X-SPLASH 7001D Microporous Coverall with Collar,
Elastic Wrists and Ankles.



Key Features & Benefits:

Item Number	Item Number UPC	Dozen UPC	Case UPC	Case L(in)	Case W(in)	Case H(in)	Weight (lbs)
7001DS	196852113385		196852113385	14.2	10.6	14.2	9.00
7001DM	196852107704		196852107704	14.2	10.6	14.2	9.90
7001DL	196852107711		196852107711	14.2	10.6	14.2	10.34
7001DXL	196852107728		196852107728	14.2	10.6	14.2	11.00
7001D2XL	196852107735		196852107735	14.2	10.6	14.2	11.88
7001D3XL	196852107742		196852107742	14.2	10.6	15.8	12.98
7001D4XL	196852107759		196852107759	14.2	10.6	15.8	13.42
7001D5XL	196852107766		196852107766	14.2	10.6	16.5	13.42



X-SPLASH 7001D

X-SPLASH 7001D Microporous Coverall with Collar,
Elastic Wrists and Ankles.



PACKAGING DIMENSIONS

	X-SMALL	SMALL	MEDIUM	LARGE	X-LARGE	2X-LARGE	3X-LARGE	4X-LARGE	5X-LARGE
CHEST	20.5 (52.1)	22.0 (55.9)	23.5 (59.7)	25.0 (63.5)	26.5 (67.3)	28.0 (71.1)	29.5 (74.9)	31.3 (79.0)	31.88 (81.0)
INSEAM	26.5 (67.3)	27.52 (69.9)	28.0 (71.1)	29.0 (73.7)	29.5 (74.9)	30.5 (77.5)	31.5 (80.0)	33.5 (85.1)	34.3 (87.0)
SLEEVE OUTSEAM	29.0 (73.7)	31.0 (78.7)	32.5 (82.6)	33.5 (85.1)	35.0 (88.9)	36.5 (92.7)	37.0 (94.0)	38.2 (97.0)	39.4 (100)
BODY LENGTH	31.0 (78.7)	33.0 (83.8)	35.0 (88.9)	37.0 (94.0)	38.5 (97.8)	40.5 (102.9)	42.5 (108)	44.1 (112)	45.7 (116)
SLEEVE OPENING	5.5 (14.0)	5.5 (14.0)	6.0 (15.2)	6.0 (15.2)	6.0 (15.2)	6.0 (15.2)	6.5 (16.5)	7.1 (18.0)	7.48 (19.0)
LEG OPENING	9.5 (24.1)	9.5 (24.1)	10.0 (25.4)	10.0 (25.4)	10.0 (25.4)	10.0 (25.4)	10.5 (26.7)	11.0 (28.0)	11.4 (29.0)
FRONT OPENING	21.5 (54.6)	21.5 (54.6)	25.5 (64.8)	25.5 (64.8)	25.5 (64.8)	27.5 (69.9)	27.5 (69.9)	79.1 (73.7)	30.7 (78.0)

PACKAGING DIMENSIONS

PHYSICAL DATA	UNIT	RESULT		TEST METHOD	CLASS	
Abrasion resistance	Cycles	40		EN530 Method 2	1	
Tensile strength	N	50.3		EN ISO 13934-1	1	
Flex cracking resistance	Cycles	>50000		ISO7854 Method B	5	
Puncture resistance	N	6.5		EN863	1	
Tear resistance	N	37.6		EN ISO 9073.4	2	
Seam strength	N	88		EN 13935-2	3	
Type 6: Spray test	—	PASS		EN 17491-4	—	
Type 5: Aerosol inward leakage test	—	IL82/90 (≤30%) 88 TILS8/10 (≤15%) 10		EN ISO 13982-2	PASS	
Resistance penetration and repellency by liquid		Penetration	Repellency	EN 160 6530	P	R
H2SO4 30%	%	0.0	97		3	3
NaOH 10%	%	0.0	98		3	3
o-xylene	%	0.0	95.9		3	3
Butanol-1-ol	%	0.0	98		3	3
Surface resistance	Ω	≤9.6 x 10 ⁷		EN 1149-1	PASS	