

X-SLASH 1122G

X-SLASH, Salt & Pepper, 13 Gauge Engineered HPPE Shell, Black Sandy Foam Nitrile over Flat Nitrile Palm Coating, ANSI Cut A6, Touchscreen, Sanitized®



Key Features & Benefits:

- ANSI A6 Cut Resistance for working with sharp or jagged materials.
- Sandy Foam Nitrile over Flat Nitrile Palm coating offers maximum abrasion resistance for longer lasting wear in harsh conditions.
- Elastic Knit Wrist helps prevent dirt and debris from entering the glove.
- ANSI Abrasion Level 6 and ANSI Puncture Level 4.

ANSI/ISEA 105



Applications:	Industries:	Certification/Ratings:
• Handling Metal Sheets • Handling Sharp/Rough Parts • Cutting Glass Sheets • Structural Components • Press Shop Operators	• Automotive • Manufacturing • Machinery & Equipment • Metal Fabrication • General Industry	ANSI/ISEA-105 • Cut Level: A6 • Abrasion Level: 6 • Puncture Level: 4
		ANSI/ISEA-138 • Impact Level: N/A
Ordering:	Composition:	Additional Information:
• Unit of Sale: 1 pr • Case Pack: 144 pr • Country of Origin: China • Available Sizes: XS -2XL	• 13 Gauge, Engineered HPPE Shell • Sandy Nitrile over Flat Nitrile Palm • Knitwrist	Wash using warm water and commercial laundry detergent. Water temperature not to exceed 122°F/50°C. Air-dry or tumble-dry with no heat.  Warning: Cancer & Reproductive Harm- www.P65Warnings.ca.gov

X-SLASH 1122G

X-SLASH, Salt & Pepper, 13 Gauge Engineered HPPE Shell, Black Sandy Foam Nitrile over Flat Nitrile Palm Coating, ANSI Cut A6, Touchscreen, Sanitized®



Key Features & Benefits:

Item Number	Item Number UPC	Dozen UPC	Case UPC	Case L(in)	Case W(in)	Case H(in)	Weight (lbs)
1122GXS	196852106608	40196852106606	50196852106603	17.7	10.6	16.5	26.0
1122GS	196852106615	40196852106613	50196852106610	17.7	10.6	16.5	26.7
1122GM	196852106622	40196852106620	50196852106627	17.7	10.6	16.5	27.3
1122GL	196852106639	40196852106637	50196852106634	17.7	10.6	16.5	27.9
1122GXL	196852106646	40196852106644	50196852106641	17.7	10.6	16.5	28.6
1122G2XL	196852106653	40196852106651	50196852106658	17.7	10.6	16.5	29.2

