



PRODUCT DATA SHEET

Enua Wallmount

Enua Wallmount

A smart wall mount that is ready to use in minutes.

With our Wallmount you can easily and securely create charge ready connection points for Enea Charge and Charge E. Whether it is for existing buildings, new constructions, or commercial buildings. Our solution is designed to suite all scenarios.

Tested by thousands of electricians, it is proven time over time to give you among the fastest installation time compared to our competitors. This is achieved by heavy-duty Wago Cage-Clamp for electrical connections, possibility for easy daisy-chaining and step-by-step configuration in our Enea Installer app.

After installation you can attach a Enea Charge or Charge E or leave it up to the customer to attach a charging station when needed. When installed correctly an IP45 classification protects the surroundings and all configurations are connected to the Wallmount. The charging station will automatically configure based on the stored data when connected.

Front



Back



Inside



Technical data

Article number

27003

Temperature range

-30°C to +50°C

Material

PC/ASA

Weight

0,70 kg

Protection grade

UV resistant

IP45 enclosure rating

IK10 impact protection

UL94-V0 flame resistance

Dimensions (mm)

H: 143 x W: 135 x D: 77

Mounting


4 mounting points - 5mm

Installation

All national and local requirements for low voltage installations must be followed during installation. Maximum 63A current flow when daisy chaining Enea Wallmounts in a row.

Connection

- Wire diameter: 12-20mm when using Enea's cable grommet.
- Handles both solid core and stranded conductors.
- No requirement for use of ferrules.
- Supports TN, IT and TT grid. 1-phase and 3-phase connection (PE+N+L1/L2/L3).
- 5 cable entries.



contact@enua.io
www.enua.io