


DATASHEET

RID 350 B-SERIES DIESEL GENERATOR 350 KVA




symbolic image



RID 350 B-SERIES S DIESEL GENERATOR 350 KVA



symbolic image



Power rating

Output power	
Power	350 kVA 280 kW
Current	505,1 A 404,1 A
Voltage	230 / 400 V
Frequency	50 Hz
Power factor	0,8 cos φ

Product overview

Order number open	713748	
Order number closed	713749	
Alternator model	Linz PRO28M F/4	LeroySomer TAL 046 H
Engine type	Hyundai DPI26LB	
Generator type	synchronous	
Control panel	RID 3000-A	
CE certified in accordance with Machinery Directive 2006/42/EC		

Dimensions and weights Generator

	Length (L)	Width (W)	Height (H)	Weight	Tank
Open	2850 mm	1700 mm	2210 mm	3050 kg	1000 l
Closed	3351 mm	1740 mm	2411 mm	3700 kg	1000 l

Noise level

	1 Meter	4 Meter	7 Meter	10 Meter
Open	87 dB(A)	86 dB(A)	85 dB(A)	84 dB(A)
Closed	81 dB(A)	76 dB(A)	71 dB(A)	69 dB(A)

Fuel consumption

	25% load	50% load	75% load	100% load
Consumption	20,2 l/h	38,4 l/h	57,1 l/h	76,0 l/h

Engine technical data

Engine output	327 kW
Engine type	Hyundai DP126LB
Engine size	6-Cylinder, V
Rotational-speed range	1500 u/min
Speed regulation	electricial
Displacement	11,051 l
Engine w/o cooling system	1008 kg

Alternator data

Alternator model	Linz PRO28M F/4	LeroySomer TAL 046 H
Insulation Class	H	
Regulation type	AVR	
Execution	brushless	
Protection class	IP 23	
Airflow Requirement	2370 m³/h	1728 m³/Stunde

Intake and exhaust system

Silencer type	industrial
Max. exhaust gas temperature	520 °C
Exhaust gas flow	3984 m³/h
Max. exhaust back pressure	59 mbar
Air filter type	replaceable element

Engine lubrication

Oil type	RID 10W30
Oil filter type	replaceable element
Total oil volume	44 l
Max. oil temperature	120 °C

Engine cooling

Cooling system	water + air
Cooling system capacity	51 l
Fan power consumption	16 kW
Cooling air flow	31320 m³/h

Controller RID 3000-A



Functions

Current	Battery voltage	Operating hours counter
Frequency	Power (kVA-kW)	Rotational-speed range
Voltage	Power factor Cosφ.	Fuel level (%)

Commands and other

- Four operating modes: OFF – Manual Start – Automatic Start – Automatic Test
- Push button to force the mains contactor or the generator contactor
- Push buttons: Start/Stop, Error Reset, Up/Down/Side Selection/Enter
- Remote start possible
- Audible alarm
- Protective functions with shutdown
- Engine protection: low fuel level, low oil pressure, high engine temperature
- Generator protection: undervoltage/overvoltage, overload, battery undervoltage/overvoltage, battery charger failure
- Protocols: GSM, Ethernet, Modbus, Canbus