PRODUCT SHEET

STALICO® Standard

8.5 m LED light mast — no extra concrete ballast



Light mast extended to 8.5 m

The STALICO® light mast is installed without extra concrete ballast. The light mast container is made of hot-dip galvanised steel and is therefore weather-resistant. As standard it is fitted with powerful 150 W LED MATRIX lamps that spread a pleasant white light; it is also available without lamps or with a higher-output lamp unit. Up to 6 masts can be linked to a single power point. Supplied with an NEN-EN 50110 / NEN 3140 inspection certificate.

BENEFITS

- No extra ballast, no fencing needed
- Up to 6 masts linked on 1 power point
- Steel cage protects mast and equipment
- Winch lockable with padlock
- Stackable per 2

TECHNICAL SPECIFICATIONS

Mast height	Telescopic, adjustable 2.5 – 8.5 m
Weight	420 kg
Dimensions closed	120 × 120 × 253 cm
Dimensions deployed	200 × 200 × 850 cm
Lighting	150 W LED MATRIX lamps
Total consumption	300 / 600 W
Power supply	230 V grid or generator
Switching	Per 2 lamps · switch 0-I-II · astronomical clock
Protection	2 automatic circuit breakers
Connections	CEE inlet + CEE outlet (link-through)
Cable	PUR spiral cable
Certificate	NEN-EN 50110 / NEN 3140

OPTIONS

- Surveillance camera — 360° protection day and night with lamp unit
- Version without lamps or higher-output lamp unit
- Antenna mast conversion (e.g. WiFi links)

APPLICATIONS

- Emergency lighting
- Events
- Construction
- Military
- Gas, oil & mining

IDEAL FOR safe, cost-efficient site lighting — no ballast blocks, no fencing, quick to link in series.